SPIRE ICC

User Requirements Document Interactions with PACS and HIFI ICCs

Written by: M. Sauvage

Draft 2

5 December 2000

۲		····· S	External SPIRE expertise – person	11.4
9		Se	External SPIRE expertise - resourc	4.10
9			PACS and HIFI expertise	4.9
9			Instrumental effects	4.8
9			Observing expertise	7.4
<u>۲</u>			Telescope status	9.4
<u>۲</u>			Instrument status	4'2
<u>۲</u>		sləbom	Publication of calibration sources and	4.4
<u>۲</u>			Calibration models	4.3
Þ			Calibration sources	4.2
Þ			Preparatory program	1.4
÷				SNI +
V				
۲			Notification	5.5
۲			Visibility	3.2
£			Commonality	1.5
۶				3 DE
U				- u v
£			користіои Аир Соитехт	Z INT
£			DIFICATION HISTORY	oM l
			SILI-SILIO 10	ומחוב ו
			stratro 1 t	, aldeT
		Page ک\7	sOOI IAIH bns SOA9 diw sno	Interacti
	Date:6/12/2000	ZU :9ussi	sdnirements document	∪ser Ke
	SPIRE-SAp	Doc. No:		<u> </u>
			- 100	CDIDE

anteractions with PACS and HIFI ICCs	Page 3/7	
User Requirements document	SG :9ussl	Date:6/12/2000
SPIRE ICC	Doc. No:	948-37198

Modification history

Rephrased some requirements, used document template.	egevus2 .M	DS	2/17/00
Document creation	egevus2 .M	DI	00/20/91
Change description	Author	Version	Date

Introduction and Context - 7.

Scope Document as follows: This subsection of the SPIRE ICC URD is intended to cover the topics described in the URD

commonality. multiple FIRST instrument. There are also requirements stemming from areas of instrument and telescope status, and (3) to coordinate observations of a given source with obtained by other FIRST instruments, (2) to transfer information SPIRE may obtain on Requirements stemming from the need (1) to cross-check calibration measurements

earlier in the development of the project than all first three points. In fact the last sentence of this description is concerned with actions that will have to be taken

control. actually be different when one is dealing with building ICC systems or with the actual instrument describing in more details the type of interactions that are foreseen between the ICCs. These will Before going on to the requirement section, let us make this summary more explicit by

are covered in a different section of the ICC URD. instruments. Similar interaction should occur between the SPIRE ICC and the FSC, but these reason to interact with other FIRST ICCs will be to exchange knowledge on the status of the development rather than one in each ICC. When dealing with actual instrument control, the main identify areas when common system can exist and design, if possible, ways to make a single When building ICC systems, the main reason to interact with other FIRST ICCs is to try and

section The two distinct areas we have just identified lead us to two distinct sections of the present URD

Development of ICC systems 3

the ICCs Once again, the main rationale here is to identify areas of common interests of need between

VillenommoD 1.5

common systems possible. team up with the other FIRST ICC to try and design ways to make single developments of these those developed in the other FIRST ICCs are searched for and identified. The SPIRE ICC shall The ICC shall make sure that all possible sources of commonality between its systems and

Here

1 - Source

	Highly desirable Yearly AVM	2 - Phase 3 - Frequency 2 - Importance
0002/21/0:9380	Z⊂ :∋ussi	озег Requirements accument Interactions with PACS and HIFI ICCs
SPIRE-SAp	Doc. No:	SPIRE ICC

YilidieiV S.S

We assume that the other FIRST ICCs will also try and identify these common areas. Thus the SPIRE ICC shall implement an internal structure that clearly identifies a person leading each development of the ICC, so that interfaces between the SPIRE and the PACS and HIFI ICCs can be promptly established.

92614 - 4	MVA
3 - Frequency	λ early
2 - Importance	Highly desirable
1 - Source	Here

3.3 Notification

As new needs, or new systems, are found to be requested by the SPIRE ICC, it shall design a system such that these decisions can be easily noticed and understand by the other ICCs. This is to allow them to notify the SPIRE ICC of their possible interest in participating to this new development.

ΜVΑ	4 - Phase
Хезиу	3 - Frequency
Highly desirable	2 - Importance
Here	1 - Source

4 Instrument Control and Monitoring

Here we are mainly dealing with the first part of the above summary.

4.1 Preparatory program

It is likely that there will be a ground- or space-based preparatory calibration program for FIRST. The SPIRE ICC shall be in close contact with, or participate to, the team in charge of this program, in order to make sure of its relevance for the SPIRE instrument.

MVA	assd9 - ₽
Үеану	3 - Frequency
Highly desirable	2 - Importance
Here	1 - Source

4.2 Calibration sources

Given that the three FIRST instruments have some wavebands in common, the SPIRE ICC shall check whether its chosen external calibration sources can be shared with the other ICCs, or whether it can use other instrument's calibration sources.

	Here Highly desirable Yearly MVA	1 - Phase 2 - Frequency 3 - Frequency
	Page 5∖7	Interactions with PACS and HIFI ICCs
Date:6/12/2000	SG :9ussl	User Requirements document
QAS-3AI92	Doc. No:	SPIRE ICC

4.3 Calibration models

Prediction of the calibration sources flux will very likely rely on models. The SPIRE ICC shall ensure the compatibility of its models with those used by the other ICCs, or design ways, possibly through new FIRST calibration measurements, to ensure this compatibility.

əsed9 - 4	ΜΛΑ
3 - Frequency	Үеану
2 - Importance	Highly desirable
1 - Source	Here

4.4 Publication of calibration sources and models

To allow an easy access to its calibration source lists and models, for consultation by the other ICCs, the SPIRE ICC shall make this information available to the other ICCs in one form or another and maintain it up-to-date.

əsed9 - 4	ΜΛΑ
3 - Frequency	Хезиу
2 - Importance	Highly desirable
1 - Source	Here

4.5 Instrument status

Due to the build-up of instrument expertise, it is assumed that the calibration accuracies of the SPIRE instrument as well as other calibration-related properties (i.e. photometric calibration, spectral response) will evolve in time. The SPIRE ICC shall make sure that the information on the calibration status of the instrument is made available in an appropriate form to the other ICCs.

as6d - 4	MVA
3 - Frequency	Үезну
2 - Importance	Highly desirable
1 - Source	Here

4.6 Telescope status

It is also foreseen that the increased instrument expertise will lead to the ability for the SPIRE ICC to derive information on the telescope status itself (e.g. beam profile). This information can be quite relevant to other ICCs (it can be cross-checked with PACS, and is of key importance to a non-imaging instrument such as HIFI). The SPIRE ICC shall make sure that this general information on the telescope status is made available in an appropriate form to the other ICCs.

	Here Highly desirable Yearly Commissioning	1 - Source 2 - Importance 3 - Frequency
	Page 6/7	Interactions with PACS and HIFI ICCs
Date:6/12/2000	SD :9ussl	User Requirements document
GAS-37192	Doc. No:	SPIRE ICC

92.1 Observing expertise

SPIRE ICC shall make sure that this information is properly conveyed to the other FIRST ICCs. it will be able to issue recommendations on the proper/best use of each SPIRE AOTs. The It is to be expected that as the SPIRE ICC gains a better knowledge of the instrument behavior,

əsedq - 4	ΜVΑ
3 - Frequency	Хезну
2 - Importance	Highly desirable
1 - Source	Here

etrumental 8.4

for these collaborations to occur. other instrumental team. Therefore the SPIRE ICC shall make sure that it has the right interfaces insight can be gained in their treatment and correction when comparing the approach chosen by It is to be expected that the FIRST instruments will suffer from similar instrumental effects. Much

4 - Phase	ຽດເກຕອາຊຸດທາງ
3 - Frequency	Yearly
2 - Importance	Highly desirable
1 - Source	Here

4.9 PACS and HIFI expertise

access to the tools required to prepare an observation with PACS and HIFI. expertise with PACS and HIFI. In particular, the SPIRE ICC shall make sure that it has internal measurements the SPIRE ICCs shall make sure that it has gathered the proper training and measurements by two or more FIRST instrument. To be able to judge the feasibility of such It will quite likely happen that some calibration observation will highly benefit from joint

əsed q - ⊅	Ground Segment Testing
3 - Frequency	Yearly
2 - Importance	Highly desirable
1 - Source	Here

4.10 External SPIRE expertise - resources

required by external ICC members to obtain this expertise. ICC shall make sure that it has the necessary resources to provide the training and information Similar needs for SPIRE expertise will quite likely occur in the other FIRST ICCs. The SPIRE

1 - Source Here

	Highly desirable Yearly	2 - Frequency 3 - Frequency
	Γ\7 ∋gsЯ	Interactions with PACS and HIFI ICCs
Date:6/12/2000	SD :9ussl	User Requirements document
GAS-37192	Doc. No:	SPIRE ICC

Ground Segment Testing

4.11 External SPIRE expertise – persons

əsbd9 - 4

If possible, the SPIRE ICC should contact the other FIRST ICC to identify early on the person in charge of acquiring SPIRE expertise, so that close contact can be maintained with them throughout the mission.

1 - SourceHere2 - ImportanceHighly desirable3 - FrequencyNot applicable4 - PhaseGround Segment Testing