

- 1. INTRODUCTION6
 - 1.1 The SPIRE instrument and its scientific programme6
 - 1.2 Purpose of this document6
 - 1.3 Scope8
- 2. INSTRUMENT OVERVIEW9
 - 2.1 Photometer design drivers9
 - 2.2 Spectrometer design drivers9
 - 2.3 Instrument functional block diagram10
 - 2.3.1 Imaging photometer12
 - 2.3.2 Fourier transform spectrometer15
 - 2.3.3 Helium-3 cooler18
- 3. Instrument System Design19
 - 3.1 SPIRE subsystems19
 - 3.2 The SPIRE instrument as a system25
 - 3.3 Structural design and FPU integration30
 - 3.4 Optical Design32
 - 3.4.1 Common optics and photometer optics32
 - 3.4.2 Spectrometer optical design35
 - 3.5 Straylight control39
 - 3.5.1 Bandpass filtering39
 - 3.5.2 Baffling40
 - 3.5.3 Diffraction limited optical analysis44
 - 3.5.4 Optical alignment47
 - 3.6 Thermal design47
 - 3.6.1 Instrument temperature levels47
 - 3.6.2 Cryogenic heat loads48
 - 3.6.3 Temperature stability49
 - 3.7 EMC49
 - 3.7.1 Signal quality49
 - 3.7.2 Grounding and RF shield49
 - 3.7.3 Microphonics54
 - 3.8 System-level criticality54
 - 3.9 Redundancy scheme55
 - 3.10 System budgets55
- 4. Subsystem Design56
 - 4.1 Warm Electronics56
 - 4.1.1 Digital Processing Unit (HSDPU)56
 - 4.1.2 Detector Readout and Control Unit (HSDRCU)60
 - 4.1.3 Detector Control Unit (HSDCU)66
 - 4.2 RF Filters68
 - 4.3 JFET units69
 - 4.4 Bolometric Detector Arrays71
 - 4.4.1 Principle of semiconductor bolometers71
 - 4.4.2 SPIRE bolometer performance requirements71
 - 4.4.3 SPIRE bolometer design and specifications72
 - 4.4.4 Bolometer readout electronics72
 - 4.4.5 Feedhorns and bolometer cavities73
 - 4.4.6 Bolometer array thermal-mechanical design75
 - 4.5 Mirrors76
 - 4.6 Filters, beam splitters80
 - 4.6.1 Photometer filtering scheme81
 - 4.6.2 Spectrometer filtering scheme84
 - 4.7 Internal calibrators86
 - 4.7.1 Photometer calibrator (PCAL)86

4.7.2	Spectrometer calibrator (SCAL)	87
4.8	Beam Steering Mechanism (BSM)	89
4.9	Spectrometer Mechanism	93
4.9.1	Requirements on the mirror mechanism	93
4.9.2	Control System and Readout	95
4.9.3	The cryogenic mechanism (SMECM)	96
4.9.4	Position measurement	96
4.9.5	The preamplifier (SMECP)	96
4.10	FPU structure	97
4.11	Helium-3 Cooler	101
4.12	Thermal straps	106
4.12.1	2-K to 4-K	106
4.12.2	300 mK	107
4.13	Harness	108
4.14	Shutter	111
5.	Instrument Operating Modes	114
5.1	Spacecraft pointing	114
5.2	Spacecraft movements during SPIRE observing	114
5.2.1	Nod	115
5.2.2	Raster	115
5.2.3	Line Scan	116
5.3	Photometer Observatory Functions	117
5.3.1	Point Source Photometry (POF1 and POF2)	117
5.3.2	Jiggle Mapping (POF3 and POF4)	118
5.3.3	Scan mapping (POF 4 and POF5)	119
5.3.4	Photometer peak-up (POF7)	119
5.3.5	Operation of photometer internal calibrator (POF8)	119
5.4	Spectrometer Observatory Functions	120
5.4.1	Point source spectrum (SOF1)	120
5.4.2	Fully-sampled spectral map (SOF2)	120
6.	Spire Sensitivity Estimation	121
7.	References	123