



SPIRE
INSTRUMENT BLOCK DIAGRAM

Doc #: SPIRE-RAL-DWG-000646
Issue: 4.4
Date: 1st June 2002
Page 1 of 7

Subject: **SPIRE BLOCK DIAGRAM**

PREPARED BY: J. DELDERFIELD **Date:**

APPROVED BY: K. KING..... **Date:**



SPIRE
INSTRUMENT BLOCK DIAGRAM

Doc #: SPIRE-RAL-DWG-000646
Issue: 4.4
Date: 1st June 2002
Page 2 of 7

CHANGE RECORD

| ISSUE | DATE | CHANGE(S) MADE |
|-------|----------|---|
| 2.0 | 7/6/01 | First Controlled Issue after IIDR |
| 2.1 | 18/6/01 | Deleted S/C Synchronisation. Added Master Clock Lines Split FCU into Modules, avoiding mixing Prime and Redundant connections via same motherboard, and requiring BSM module to be split Prime/Redundant, TBC. Re-ordered signal channels into harnesses to get breaks between BDAs to better align with LIA divisions. Removed last vestiges of showing Fast and Slow I/Fs separately as they are linked by W1-W6. Fix FCU J26 duplication. |
| 2.2 | 29/6/01 | Put BDA connector numbers in line with JPL's that indicate which of the six geometric positions are used. Bundle back-harness wires as per JPL diagram. Define LCL names. |
| 2.3 | 7/7/01 | Rearrange JFETs to stress "modularity" |
| 2.4 | 7/8/01 | Increase FCU J21 and J22 to 25way...to take calibrator heater wires that were omitted. Swop JFETs to using 37way filters with partially populated contacts. |
| 2.5 | 8/8/01 | Put in FPU clamshell connectors as harness name "breaks". Delete TBD. |
| 2.6 | 7/9/01 | Update SMEC connectors on FPU from 50 way to 2x37way each side. |
| 2.7 | 9/10/01 | Put in fully updated HSFCU |
| 2.8 | 12/10/01 | Correct way I harness tails split on to FCU...in error in version 2.7 Remove branch from F12A and route 300mK temperature "detectors" via HSJFS J7 AND J8 and new F 28. Correct PMW BDA Allocation. Add note to F20 and F21 so clear that each has one "Cernox" that is actually a 300Mk heater. Put in HSDCU with connectors drawn to scale. |
| 2.9 | 18/10/01 | Correct errors with W3-6 labels that crept into issue 2.8 |
| 3.0 | 30/10/01 | Swop numbers on connector lines for DCU redundant bias generator so they fit with harness definition document, and connectors 29-34 remain if generators were to be put on one module or otherwise reconfigured. |
| 3.1 | 31/10/01 | Remove Filter Modules from JFET racks, thus adopting JPL's intention to use filter connectors and spliced harness. |
| 3.2 | 9/11/01 | Reduce HSDCU Bias module front panel sizes and house them in one double sided module. Call S4 T1 as per Doug's drawings. |
| 3.3 | 21/11/01 | Add last few connector IDs to JFET racks. |
| 3.4 | 11/12/01 | Got J1-J4 on FCU the correct way around [SCU to MCU!] |
| 3.5 | 18/12/01 | Move Connectors around on HSFPFU to match CEA's v0.5 HSFPFU ICD. Keep JTAG connectors shown elsewhere in DRCU ICD/Spec..but renumber as J37 and J38 Combine HSFCU SCU's DPU I/F and Cooler/Stimulus Modules Re-jig Shutter DRCU connectors to not be wired via HSFCU Modules Reduce J25/J26 Connector sizes as moving shutter wiring removes some pins |



SPIRE
INSTRUMENT BLOCK DIAGRAM

Doc #: SPIRE-RAL-DWG-000646
Issue: 4.4
Date: 1st June 2002
Page 3 of 7

| | | |
|-----|----------|--|
| | | <p>from them. Change 1553 buses to A & B rather than Prime & Redundant Change J23 and J24 sizes because of HSFCU PCB frame restrictions. Move HSFCU Connectors to be in correct physical layout. Add J29 and J30 to shutter wiring to accommodate non-shutter launch latch confirm inputs. Change J15 and J16 to 25way as Doug's given the shutter more wires. Change HSFCU Shutter J17 and J18 to 21way MDM to match. Show power links on DRCU unit because these are not internal. Update HSDCU Bias connectors J29/32 to use 78-way HD triple row connectors after their acceptance by ESA.</p> |
| 3.6 | 20/12/01 | Frederic's comments on J22 and 3TCs implemented. |
| 3.7 | 1/1/02 | HSFCU Duplicate J29/30 Fixed, bumping numbers for JTAGs |
| 3.8 | 1/2/02 | Change SCAL 21 ways to 37 ways. |
| 3.9 | 25/2/02 | As per Passvogel decision, put four "skin" connectors on cryostat associated with cryoharnesses 10-13, to act as access points for EGSE for shutter operation and latch confirmations. Bracket on side of HSFCU deleted, and links to HCDMU's RTUs. |
| | | As HERSCHEL latest accommodation, add connector plate on top of SVM and change cryoharness to include extra/extended/external "E" sections, which are all 1:1 with CVV wall connectors to minimise external RF. loops (except skin connector functions as per above change). "I" harnesses become copper for flight. |
| | | Rationalise sex/sizes of HSFCU internal power connectors |
| 4.0 | 5/3/02 | Route 300 mk temperature control via Harness 2 and not Harness 1 due to needing to keep spare pins on CVV connectors. |
| | | Optimise alignment of drawing |
| 4.1 | 12/4/02 | Correct HSFCU J9/10 & 31-36 shell size as per SVM meeting |
| 4.2 | 22/4./02 | Change E harness category to I and I harness category to S(SVM) to be the same as PACS and HIFI. |
| | | Add caveat about using this diagram as a harness definition diagram |
| | | Show which one of each pair of cryoharness in-line connectors are chassis mounted by adding P/J notes along I/F lines |
| | | Include representation of 300mK cooling busbar and move 300mK sensor/heater unit to show how it links into F harnesses. Call this sub-system HSPTC (Photometer Temperature Control). |
| | | Move EGSE break-out connectors from CVV skin to SCM connector panel as Astrium design implements. |
| 4.3 | 15/5/02 | Corrected one of two J33s to J34 on HSJFP |
| | | Updated BDA Nanonics J numbers...which define their positions |
| | | Move J22 link to SVM panel rather than in air above HSDCU. |
| 4.4 | 1/6/02 | Remove connectors on SME because unfortunately only flying leads can be accommodated. |
| | | Relabel Harness S4 Type 1a not Type 1 because of its small variation compared to other Type 1s, i.e its link to S2. |
| | | Add note to HSDCU J26 saying that this is the connector to which the 6spare SSW bolometer channels would go if they were wired through. They are actually terminated at HSDCU end of S2 with 15KΩ resistors. |



SPIRE

INSTRUMENT BLOCK DIAGRAM

Doc #: SPIRE-RAL-DWG-000646

Issue: 4.4

Date: 1st June 2002

Page 4 of 7

ACRONYM LIST

| Term | Meaning |
|-------|--|
| ADC | Analogue to Digital Converter |
| AIV | Assembly, Integration and Verification |
| AME | Absolute Measurement Error |
| AOCS | Attitude and Orbit Control System |
| APART | Arizona's Program for the Analysis of Radiation Transfer |
| APE | Absolute Pointing Error |
| ASAP | Advanced Systems Analysis Program |
| AVM | Avionics Model |
| BDA | Bolometer Detector Array |
| BFL | Back Focal Length |
| BRO | Breault Research Organization |
| BSM | Beam Steering Mirror |
| CDMS | Command and Data Management System |
| CDMU | Command and Data Management Unit |
| CDR | Critical Design Review |
| CMOS | Complimentary Metal Oxide Silicon |
| CPU | Central Processing Unit |
| CVV | Cryostat Vacuum Vessel |
| DAC | Digital to Analogue Converter |
| DAQ | Data Acquisition |
| DCU | Detector Control Unit = HSDCU |
| DPU | Digital Processing Unit = HSDPU |
| DSP | Digital Signal Processor |
| DQE | Detective Quantum Efficiency |
| EDAC | Error Detection and Correction |
| EGSE | Electrical Ground Support Equipment |
| EMC | Electro-magnetic Compatibility |
| EMI | Electro-magnetic Interference |
| ESA | European Space Agency |
| FCU | FCU Control Unit = HSFCU |
| FIR | Far Infrared |
| FIRST | Far Infra-Red and Submillimetre Telescope |
| FOV | Field of View |
| F-P | Fabry-Perot |
| FPGA | Field Programmable Gate Array |
| FPU | Focal Plane Unit |
| FTS | Fourier Transform Spectrometer |
| FWHM | Full Width Half maximum |
| GSFC | Goddard Space Flight Center |
| HK | House Keeping |
| HOB | Herschel Optical Bench |
| HPDU | Herschel Power Distribution Unit |
| HSDCU | Herschel-SPIRE Detector Control Unit |
| HSDPU | Herschel-SPIRE Digital Processing Unit |
| HSFCU | Herschel-SPIRE FPU Control Unit |
| HSO | Herschel Space Observatory |
| IF | Interface |
| IID-A | Instrument Interface Document - Part A |



SPIRE

INSTRUMENT BLOCK DIAGRAM

Doc #: SPIRE-RAL-DWG-000646

Issue: 4.4

Date: 1st June 2002

Page 5 of 7


| Term | Meaning |
|-------------|---|
| IID-B | Instrument Interface Document - Part B |
| IMF | Initial Mass Function |
| IR | Infrared |
| IRD | Instrument Requirements Document |
| IRTS | Infrared Telescope in Space |
| ISM | Interstellar Medium |
| JFET | Junction Field Effect Transistor |
| ISO | Infrared Space Observatory |
| LCL | Latching Current Limiter |
| LIA | Lock-In Amplifier |
| LVDT | Linear Variable Differential Transformer |
| MAC | Multi Axis Controller |
| LWS | Long Wave Spectrometer (an instrument used on ISO) |
| MCU | Mechanism Control Unit = HSMCU |
| M-P | Martin-Puplett |
| NEP | Noise Equivalent Power |
| NTD | Neutron Transmutation Doped |
| OBS | On-Board Software |
| OMD | Observing Modes Document |
| OPD | Optical Path Difference |
| PACS | Photodetector Array Camera and Spectrometer |
| PCAL | Photometer Calibration source |
| PID | Proportional, Integral and Differential (used in the context of feedback control loop architecture) |
| PLW | Photometer, Long Wavelength |
| PMW | Photometer, Medium Wavelength |
| POF | Photometer Observatory Function |
| PROM | Programmable Read Only Memory |
| PSW | Photometer, Short Wavelength |
| PUS | Packet Utilisation Standard |
| RMS | Root Mean Squared |
| SCAL | Spectrometer Calibration Source |
| SCUBA | Submillimetre Common User Bolometer Array |
| SED | Spectral Energy Distribution |
| SMEC | Spectrometer Mechanics |
| SMPS | Switch Mode Power Supply |
| SOF | Spectrometer Observatory Function |
| SPIRE | Spectral and Photometric Imaging Receiver |
| SRAM | Static Random Access Memory |
| SSSD | SubSystem Specification Document |
| STP | Standard Temperature and Pressure |
| SVM | Service Module |
| TBC | To Be Confirmed |
| TBD | To Be Determined |
| TC | Telecommand |
| URD | User Requirements Document |
| UV | Ultra Violet |
| WE | Warm Electronics |
| ZPD | Zero Path Difference |

HERSCHEL-SPIRE(HS)

HERSCHEL

HERSCHEL-SPIRE(HS)

HERSCHEL



KEY

- Bundled together, not electrical screen
- Master clock
- Herschel to Herschel/Spire I/F lines, drawn simplified...I/Fs are all at HS connector planes
- Flight Harness Identity
- Prime harness
- Redund. harness

CAUTION This instrument block diagram shows how SPIRE units relate functionally, it is not a harness specification. The connectors happen to be labelled with the names of the fixed items on the units, not the mating harness parts.