

<b>DECLARED MATERIALS LIST</b>		<b>ORIGINATOR:</b>			<b>UK ATC</b>		
<b>SPACECRAFT / PROJECT</b>		Herschel		<b>Doc. Number:</b>			<b>SPIRE-ATC-PRJ-710</b>
				<b>Sheet No:</b>			<b>Page 1 of 4</b>
<b>SYSTEM / EXPERIMENT</b>		SPIRE		<b>Issue/Rev:</b>			<b>0.3</b>
<b>SUB-SYSTEM:</b>		BSM		<b>Date:</b>			<b>20.Jul.01</b>

BSM Material List ID	Component ID	Name & Type of Product, Form and Condition	Specification	Size Code	Processing Parameters	Outgassing SCC-Res. Data and Refer	OK to bake at 80°C?	Thermal & Vacuum stable?	OK at 4°K?	Manufacturer	Remarks, Approval Reference
1.	Structure, Jiggle frame, Interface shoe, baffle	Aluminium plate, cold rolled. bar	6082	TBD	T6 (TBC)	TBD	Y	Y	Y	TBD	
2.	Baffle	Aluminium Sheet, welded.	6082	TBD	T6 (TBC)	TBD	Y	Y	Y	TBD	
3.	Mirror	Aluminium	6061	TBD	-T651 or T6511	MSFC-HDBK-527F p88 Corrosion rating 'B'.	Y	Y	Y	TBD	Intermediate cycling per ATC Spec to provide stability.
4.	Fasteners	stainless steel,	austenitic	N/A	TBD	TBD	Y	Y	Y	TBD	
5.	Locking inserts	stainless steel,	TBD	N/A	TBD	TBD	Y	Y	Y	TBD	
5.	Flex pivots	Inconel	718	N/A	TBD	TBD	Y	Y	Y	TBD	Austenitic stainless steel (304 grade) an alternative.
7.	Flex pivot sleeves	stainless steel, aluminium or inconel	TBD	TBD	TBD	TBD	Y	Y	Y	TBD	
3.	Sensor targets	Mild steel (Soft iron grade preferred – TBD)	BS970 220M07	TBD	TBD	TBD	Y	Y	Y	TBD	Corrosion protection by thin layer of varnish, material ID 19

<b>DECLARED MATERIALS LIST</b>				<b>ORIGINATOR:</b>				<b>UK ATC</b>							
<b>SPACECRAFT / PROJECT</b>				Herschel				<b>Doc. Number:</b>				SPIRE-ATC-PRJ-710			
								<b>Sheet No:</b>				Page 2 of 4			
<b>SYSTEM / EXPERIMENT</b>				SPIRE				<b>Issue/Rev:</b>				0.3			
<b>SUB-SYSTEM:</b>				BSM				<b>Date:</b>				20.Jul.01			

BSM Material List ID	Component ID	Name & Type of Product, Form and Condition	Specification	Size Code	Processing Parameters	Outgassing SCC-Res. Data and Refer	OK to bake at 80°C?	Thermal & Vacuum stable?	OK at 4°K?	Manufacturer	Remarks, Approval Reference
9.	Sensor mount, motor housing	Glass fibre epoxy	G-10CR Or G10/40 (TBC)	TBD	TBD	TBD	Y	Y	Y	TUFNOL	TBC if required , may use aluminium instead. Note: A cryogenic grade material consisting of 7628 fabric woven with continuous e-glass fiber in an amine-cure
10.	Potting compound/ Adhesive	Stycast	2850FT	N/A	with Catalyst 11	MAPTIS material 06451	Y	Y	TBC	TBD	Various grades in MAPTIS, MSFC-HDBK. Select correct one NB - LIMITED LIFE MATERIAL
11.	Adhesive, cable run	Eccobond	285	N/A	with catalyst 11	MAPTIS database material 05475	Y	Y	TBC	TBD	ATC practice is to use 286 - NB - LIMITED LIFE MATERIAL
12.	Motor screening	Mu-metal, sheet 0.125mm thick	TBD	TBD	TBD	MSFC-HDBK-527F p181 (spec AMS 7701) Corrosion rating 'B'	TBC	TBC	TBC	Goodfellow	In MSFC HDBK as 'MAGNET HI-PERM-MUMETAL'. TBC if required
13.	Harness - wire core	TBD	TBD	N/A	TBD	TBD	Y	Y	Y	TBD	Get space rated cable from RAL
14.	Harness - insulation	TBD	TBD	N/A	TBD	TBD	Y	Y	TBC	TBD	Get space rated cable from RAL
15.	Harness P-Clips	Brass	TBD	TBD	TBD	TBD	Y	Y	Y	TBD	TBC if required
16.	Solder	Solder	TBD	N/A	TBD	TBD	Y	Y	Y	TBD	Space rated soldering certificate required

<b>DECLARED MATERIALS LIST</b>		<b>ORIGINATOR:</b>		<b>UK ATC</b>
<b>SPACECRAFT / PROJECT</b>		Herschel	<b>Doc. Number:</b>	
			SPIRE-ATC-PRJ-710	
<b>SYSTEM / EXPERIMENT</b>		SPIRE	<b>Sheet No:</b>	
			Page 3 of 4	
<b>SUB-SYSTEM:</b>		BSM	<b>Issue/Rev:</b>	
			0.3	
			<b>Date:</b>	
			20.Jul.01	

BSM Material List ID	Component ID	Name & Type of Product, Form and Condition	Specification	Size Code	Processing Parameters	Outgassing SCC-Res. Data and Refer	OK to bake at 80°C?	Thermal & Vacuum stable?	OK at 4°K?	Manufacturer	Remarks, Approval Reference
17.	Motor Core	NiFe Soft magnetics Laminated sheets	ULTRA PERM 250 or CryoPerm 10	TBD	TBD	TBD	Y (PACS)	Y (PACS)	Y (PACS)	TBD	Latest PACS paper says CryoPerm 10
18.	Motor Winding	Aluminium, high purity	5N	TBD	TBD	TBD	Y (PACS)	Y (PACS)	Y (PACS)	California Fine Wires	TBC , may be 6N copper
19.	Motor insulation	Varnish?	TBD	N/A	TBD	TBD	Y (PACS)	Y (PACS)	Y (PACS)	TBD	Zeiss, PACS approved
20.	Motor winding frames	Vespel	SP-1	TBD	TBD	TBD	Y	Y	Y	DuPont	
21.	Motor Permanent Magnet	NdFeB Permanent magnets	VACODYM 344	TBD	TBD	TBD	TBC	Y (PACS)	Y (PACS)	TBD	
22.	Finish	QMW Black	Mk2	N/A	TBD	TBD	TBC	Y	Y	TBD	TBD if required
23.	Unfinished aluminium parts	Finish - anodize	TBD	N/A	TBD	TBD	Y	Y	Y	TBD	TBC if required
24.	Thermal end stops	Copper (TBD)	TBD	TBD	TBD	TBD	Y	Y	Y	TBD	TBC if required
25.	Surface plating	Copper flashing, Nickel Plate (TBD), Gold plate	TBD	N/A	TBD	TBD	Y	Y	Y	TBD	

<b>DECLARED MATERIALS LIST</b>		<b>ORIGINATOR:</b>		<b>UK ATC</b>
<b>SPACECRAFT / PROJECT</b>		Herschel	<b>Doc. Number:</b>	<b>SPIRE-ATC-PRJ-710</b>
			<b>Sheet No:</b>	<b>Page 4 of 4</b>
<b>SYSTEM / EXPERIMENT</b>		<b>SPIRE</b>	<b>Issue/Rev:</b>	<b>0.3</b>
<b>SUB-SYSTEM:</b>		<b>BSM</b>	<b>Date:</b>	<b>20.Jul.01</b>

<b>BSM Material List ID</b>	<b>Component ID</b>	<b>Name &amp; Type of Product, Form and Condition</b>	<b>Specification</b>	<b>Size Code</b>	<b>Processing Parameters</b>	<b>Outgassing SCC-Res. Data and Refer</b>	<b>OK to bake at 80°C?</b>	<b>Thermal &amp; Vacuum stable?</b>	<b>OK at 4°K?</b>	<b>Manufacturer</b>	<b>Remarks, Approval Reference</b>
26.	Motor Thermal shields	Copper	TBD	N/A	Electroformed	TBD	Y	Y	Y	TBD	Check electroformed Cu is OK
27.	Magnetic Shielding	Niobium plate	TBD		plated	TBD	TBC	TBC	Y	TBD	Use as superconducting magnetic shield