

Prepared by : Jeff Payne & Dave Parker

Test Conductor : Jeff Payne & Dave Parker

Test Operatives : Luc Dubbeldam (SRON)
Erich Weizorrek(MPE)
Andy Matheson (RAL)

Test Date : September 26th & 27th 2001

Test Location : RAL

Test Software : CDMS v0.6

Observers : Otto Bauer (MPE) (27th only), Luc Dubbledam (SRON), Ken King (RAL),
Andy Matheson (RAL), Brian Melton (ESTEC) (27th only),
Dave Parker (RAL), Jeff Payne (RAL), Stefan Thuerey (ESTEC),
Frederick Wechsler (ESTEC), Eric Wiezorrek (MPE),
Stephan Veillat (ESTEC) (27th only)

Prepared by : Jeff Payne & Dave Parker

Date : 25/9/01

Checked by :

Date :

Agreed by :

Date :

Authorised by :

Date :

Distribution: O.Bauer
L.Dubbeldam
K.King
P. Gomez
J-L.Beney
S.Thuerey
F.Wechsler

Document Change Record

Issue

Date Changed

Section Description of Change



CONTENTS

1. INTRODUCTION.....	4
1.1 Purpose.....	4
1.2 Scope.....	4
2. DOCUMENT REFERENCES	5
2.1 Applicable documents	5
2.2 Reference Documents.....	5
3. DELIVERABLES	5
3.1 Hardware	5
3.2 Software.....	5
3.3 Documentation.....	5
4. ENVIRONMENT.....	5
4.1 Remote Terminal (simple instrument simulator)	6
4.2 Router and Test Client.....	6
5. CDMS-Sim Test Requirements Matrix.....	7
5.1 Spacecraft Data Interface Requirements.....	7
5.2 Users Requirements.....	8
6. TEST PROCEDURE.....	10
6.1 1553 Bus Electrical Interfaces.....	10
6.1.1 Output Signal Amplitude	10
6.1.2 Output Risettime	12
6.1.3 Output Zero Crossing	13
6.1.4 Output Distortion.....	14
6.1.5 Output Symmetry.....	14
6.1.6 Output Noise.....	14
6.1.7 Output Isolation	15
6.1.8 Output – Power On/Off noise	15
6.1.9 Output Frequency Stability.....	15
6.1.10 Input Impedance	16
6.2 1553 Bus Data-link Layer Support	17
6.2.1 Mode Commands.....	17
6.2.2 No Response Timeout.....	19
6.2.3 Receive Message	19
6.2.4 Broadcast Message	19
6.2.5 Transmit Message.....	20
6.2.6 Receive Low-Level Command	20
6.2.7 Data-link Error Messages	20
6.3 Satellite 1553 Bus Transfer-Layer Protocol	21
6.3.1 Basic Protocol without TM or TC transfer	21
6.3.2 TC Packet transfer	24
6.3.3 RT Error Conditions	25
6.3.4 TM Packet transfer	26
6.3.5 CDMS-Sim (BC) Error Conditions	27
6.3.6 Bus Polling Sequence: Nominal Mode	27
6.3.7 Burst Mode	31
6.3.8 Memory load Mode	37
6.4 Simulator Stand-Alone Operation.....	43
6.4.1 Front Panel.....	43
6.4.2 Log Files.....	45
6.5 Router Interface	45
6.5.1 Log on.....	46
6.5.2 TC Packet flow	46
6.5.3 TM Packet flow	46

6.6	TM Playback	46
6.7	Remote Operation of Simulator	46
7.	ACCEPTANCE TEST REVIEW	47
8.	Appendix A – DDC Test Report	48

1. INTRODUCTION

The CDMS data interface Simulator forms a connection between the MIL-STD-1553B data bus (which is the data interface for instruments on Herschel/Planck) and a computer network.

The 1553 bus interface hardware used in the CDMS-Sim is a BU65549M2-300 PCI card, which is a standard off-the-shelf product from Data Device Corporation (DDC). The CDMS Simulator software has been developed at RAL using the DDC C code library.

This document describes the tests that shall be carried out before the unit is delivered to and accepted by the Herschel instruments. The purpose of the tests is to ensure compliance of the CDMS Simulator with all aspects of the design and users requirements. The procedure section, filled out with test results together with any associated test logs, will form the acceptance test report.

The test procedure incorporates the test requirements specifications SRON-U/HIFI-SP-5 draft 0.2, and also an Email dated 1 May 2001 from L.Dubbeldam to Wechsler, Bauer, King and Thuerey.

1.1 Purpose

The purpose of this document is to define the activities and responsibilities required for the acceptance testing of the CDMS for the three Herschel instruments.

1.2 Scope

The CDMS Simulator test specifications in the SRON document are derived from a suggested test plan in MIL-HDBK-1553A. However the MIL-HDBK test plan is written to test a 1553 RT device using a 1553 Tester. In our case the CDMS Simulator is a 1553 BC - the *instrument* is the RT, so the plan has to be adapted for our use.

DDC, the manufacturer of the CDMS Simulator bus interface card, has demonstrated that their equipment is compatible with that same 1553 test plan. These measurements have been made with the ACE device (bus interface component) acting as an RT. The DDC report may be found in Appendix A.

This CDMS Simulator test acceptance test comprises:

- Interface hardware measurements
These are performed to confirm the build standard of the DDC card. Measurements of the Simulator output voltages, which may be important for the safety of flight equipment, are made in several different bus configurations. These were not in the requirements, but may be useful for future reference.
- Low-level 1553 bus protocol measurements
These demonstrate the use of the DDC ACE windows menu to generate single messages and short sequences of messages.
- Satellite bus protocol measurements
These demonstrate compliance with the PS-ICD and the Simulator requirements specification.
- Verification of user interface and Router interface
Demonstrating the user interface requirements which were specified in the Simulator requirements specification.

The test procedure verifies the CDMS Simulator only. It does not include any instrument-specific or EGSE testing.

2. DOCUMENT REFERENCES

2.1 Applicable documents

- AD.1. FIRST-PLANCK CDMS interface test-requirements specifications, SRON-U-HIFI-SP-2000-5.
- AD.2 Packet Structure ICD, SCI-PT-ICD-07527 issue 1
- AD.3 Mil-Std-1553B
- AD.4 FIRST/Planck CDMS Simulator Requirements, SRON-U/HIFI/SP/2000-004 issue 1.0

2.2 Reference Documents

- RD.1 Hardware Manual MIL-STD 1553 BC/RT/MT PCI Interface Card, MN-65549-001.
- RD.2 EGSE-ILT Users Requirements Document, FIRST-SPI-DOC-000127.
- RD.3. CDMS Simulator Users Guide, SPIRE-RAL-PRJ-000807.

3. DELIVERABLES

3.1 Hardware

DDC 1553 BUS Card Part No BU-65549M2-300
Personal Computer Pentium III 900Mhz or better, 256Mb Memory.

3.2 Software

This software is provided on a CD which includes an installation procedure:

CDMS_SIM.EXE	(RAL CDMS Simulator LabView VI's in compiled form)
DDC.DLL	(RAL CDMS Simulator C Code)
Remote Terminal.EXE	(Simple instrument simulator)
Example telecommands	
Example buslists	

With hardware deliveries only:

DDC ACE Runtime library
DDC 'ACE Windows menu' program

3.3 Documentation

CDMS Simulator Users Guide

Certificates of Conformance

4. ENVIRONMENT

The CDMS-Sim acceptance tests will be performed at RAL.
Three PCs are used during the tests:

- CDMS-SIM
- Remote Terminal (simple instrument simulator)
- Router

The Router PC can optionally run the Systran 1553 bus monitor software to assist in understanding any problems encountered.

The computers will be isolated from any local computer Network during the testing.

4.1 Remote Terminal (simple instrument simulator)

The simple instrument simulator program used in simulator testing has two modes:

- Echo TC
The program receives a TC packet via the 1553 transfer protocol, changes the packet header into a valid TM header, and re-sends it back to the bus controller.
- Transmit TM
The program creates TM packet data of maximum packet length. It has a valid header containing a packet counter. The data area consists of a counting data pattern. The program generates TM requests and then transfers packet data over the bus at the maximum possible rate.

The instrument simulator can emulate any instrument; a control on the front panel sets the remote terminal (RT) number.

The RT is only intended to support the packet transfer protocol for simulator self-test and EGSE integration purposes. It has not been exhaustively tested in all 1553 configurations.

4.2 Router and Test Client

The Router with software version 0.92 is installed on a separate PC from the CDMS-Sim. This PC also has a simple test client written in Java to send telecommands to and receive telemetry packets from the router.

5. CDMS-SIM TEST REQUIREMENTS MATRIX

5.1 Spacecraft Data Interface Requirements

Note: The CDMS Simulator is not required to perform all of the 'instrument' tests listed in the test matrix of the Test Requirements document, AD1. A bus tester may be required for those instrument-specific tests.

Test Requirement section	Test plan Section	Comments
4.2	Output Characteristics	6.1
4.2.1	Amplitude	6.1.1
4.2.2	Risetime / falltime	6.1.2
4.2.3	Zero crossing stability	6.1.3
4.2.4	Distortion, overshoot and ringing	6.1.4
4.2.5	Output symmetry	6.1.5
4.2.6	Output noise	6.1.6
4.2.7	Output isolation	6.1.7
4.2.8	Power on/off noise	6.1.8
4.2.9	n/a	
4.2.10	n/a	
4.2.11	Frequency stability	6.1.9
4.3.5	Input impedance	6.1.10
4.5.9	Required mode commands	6.2.1
	Transmit status	
	Transmitter shutdown and override	
	Reset remote terminal	
4.7	CDMS Sim data link support	6.2
4.7.1	Mode commands	6.2.1
4.7.2	No response timeout	6.2.2
4.7.3	Receive message	6.2.3
4.7.4	Broadcast message	6.2.4
4.7.5	Transmit message	6.2.5
4.7.6	Receive low-level command	6.2.6
4.8	Satellite data-bus protocol	6.3
4.8.1	EGSE connection	
4.8.2	Basic protocol without TM or TC transfer	6.3.1
4.8.3	Transfer of TC packet	6.3.2
4.8.4	RT error conditions during data transfer	6.3.3
4.8.5	TM packet transfer	6.3.4
4.8.6	CDMS Sim error conditions during data transfer	6.3.5
4.8.7	Nominal mode	6.3.6
4.8.8	Burst mode	6.3.7

5.2 Users Requirements

User Requirement section		Test plan Section	Comments
4.1.1	Implement bus controller functions according to MIL-STD-1553B	6	
4.1.1	Transfer TC packets received from the Router as messages on the 1553 bus.	6.5.2	
4.1.1	Transfer TM packets received as messages over the 1553 bus to the Router.	6.5.3	
4.1.1	Retrieve and send TM packets from file to the Router.	6.6	
4.1.1	Support creation, modification and storage of several bus profiles.	6.3.6 - 6.3.8	Buslists created with EXCEL.
4.1.1	Start up automatically in a reproducible configuration.		
4.1.1	Nominal bus profile: 25 TM packets/sec 2 Async. short TM packets/sec 2 TC packets/sec 2 Async. short TC packets/sec 1 Time / sec	6.3.6	Async messages/packets not yet fully defined, therefore not yet implemented. Time is a message not a packet.
4.1.1	Burst mode bus profile: 50 TM packets/sec 2 Async. short TM packets/sec 2* TC packets/sec 2 Async. short TC packets/sec 1 Time / sec	6.3.7	Async messages/packets not yet fully defined, therefore not yet implemented. TM packets cannot be redefined as TC packets at run-time. Time is a message not a packet.
4.1.1	Memory load mode bus profile: 0 TM packets/sec 2 Async. short TM packets/sec 20 TC packets/sec 2 Async. short TC packets/sec 1 Time / sec	6.3.8	Async messages/packets not yet fully defined, therefore not yet implemented. Time is a message not a packet.
4.1.2	The CDMS Simulator shall be able to operate stand-alone:	6.4	
4.1.2	Implement 1553 Bus Controller functions.	6	
4.1.2	Store TC packets as files.	6.4.1.2	
4.1.2	Edit TC files		Use any text editor eg Notepad
4.1.2	Generate TC packets from application data by adding header and checksum.	-	This requirement was deleted in a working group meeting; see CDMS requirements annex A, 18.
4.1.2	Display TM packets (hex)	6.4.1.3	
4.1.2	Transfer malformed TC packets (Length, APID, checksum)	6.4.1.2	The CDMS-Sim makes no checks on packet contents.
4.1.3	Perform bus monitor functions in addition to Stand-alone or connected functions:	6.4	

4.1.3	Archive TC and TM packets for 30 minutes at maximum rate.	6.3.7, 6.4.2	
4.1.3	Archive 1553 bus messages for 30 minutes at maximum rate.	6.4.2.3	
4.1.3	Display a list of transferred TM/TC packets.	6.4.1.2, 6.4.1.3	
4.1.3	Display individual TM/TC packets.	6.4.1.2, 6.4.1.3	
4.1.3	Display a list of transferred 1553 messages.	6.3.6 - 6.3.8	
4.1.3	Display individual 1553 messages	6.3.6 - 6.3.8	
4.1.3	Display traffic status information in real time.	6.4.1.2, 6.4.1.3	
4.1.3	Archived and displayed packets and messages shall be time-stamped.	6.4	
4.1.4	The CDMS-Sim shall synchronise its time and synchronise instruments according to the PS-ICD procedures:	6.3.1, 6.4.1.1	Full time synchronisation not yet implemented; but 1553 frame is synchronised to PC seconds.
4.1.4	The CDMS-Sim shall provide: 131.072 kHz		not implemented yet
4.1.4	The CDMS-Sim shall provide: 1 Hz synchronised to master time.		not implemented yet
4.1.5	Fault Detection, Isolation and Recovery:	6.4.1.4	
4.1.5	Display BC and RT error messages in real time.	6.4.1.4	
4.1.5	Display detected bus error conditions in real time.	6.4.1.4	
4.1.5	Display protocol errors in real time.	6.4.1.4	
4.1.5	Display CDMS-Sim error conditions.	6.4.1.4	
4.1.5	Switch between bus A and B as part of set-up.	6.4.1.1	
4.3.1	The CDMS-Sim shall interface with up to 4 RTs.	6.3.6	Buslist controls message destinations; can use all RTs.
4.3.3	The CDMS-Sim shall have controls/displays for:	6.4.1.1	
4.3.3	Simulator Configuration	6.4.1.1	
4.3.3	1553 traffic start/stop	6.4.1.1	
4.3.3	TM/TC packets in hex format	6.4.1.2, 6.4.1.3	
4.3.3	1553B messages	6.3	
4.3.3	Simulator status	6.4.1.1	
4.3.3	1553 bus traffic status	6.4.1.1	
4.3.4	The CDMS-Sim shall be capable of commanding, configuration and monitoring from an instrument EGSE.		Not yet implemented

6. TEST PROCEDURE

6.1 1553 Bus Electrical Interfaces

The BU-65549 card has a jumper selection for ‘Direct Coupled’ or ‘Transformer Coupled’ configuration. This refers to the external connection of the bus between units; signals are always isolated on the card by transformers. ‘Transformer Coupled’ is the default configuration for spacecraft connection using bus couplers, but measurements with ‘Direct Coupled’ connection are included here, since this method can be useful during bench tests.

6.1.1 Output Signal Amplitude

6.1.1.1 Open Circuit

Make peak-peak voltage measurements of the BC output signal at points A and B shown in the figure:




Figure 6.1.1.1 – Open Circuit measurement

Jumper setting	Bus A – open circuit pk-pk voltage	Bus B – open circuit pk-pk voltage
Direct Coupled	49.7v (ref 5)	51.2v (ref 6)
Transformer Coupled	35.3v (ref 1)	35.0v (ref 2)

See Appendix B
reference numbers
are attached to
each scope picture.

6.1.1.2 Direct Coupled – with 39 ohm Load

This is the recommended load for direct coupled bench test connections (see RD.1 page 8). It should only be used with direct connections both ends. Connect the DDC BC and RT as shown below:




Figure 6.1.1.2

Make peak-peak voltage measurements of the BC output signal by connecting the oscilloscope across the 39 ohm resistor.

Jumper setting	Bus A pk-pk voltage	Bus B pk-pk voltage
Direct Coupled	9.05V (ref 7)	8.25V (ref 8)

6.1.1.3 Transformer Coupled – Unterminated Bus

Change the DDC card jumpers to transformer-coupled for the remainder of the tests. Connect a North Hills bus coupler type DB40010 or equivalent as shown below. For this test the bus terminations are not fitted to the ends of the coupler (bus unterminated). Connect a link with breakout provision between BC and coupler and a test cable on the RT side, as shown:




Figure 6.1.1.3

Jumper setting :	Bus A voltage (peak-peak)	Bus B voltage (peak-peak)
Transformer coupled		
BC Output at measurement point X	32.1V	35.3V
Coupler Output at measurement point Y	34.1V	34.5V

6.1.1.4 Transformer Coupled – Normal Bus Loads

This is a measurement of the Simulator (BC) connected to an Instrument (RT) via a bus coupler with 75 ohm bus terminations on each end of the bus. In this case the 'bus' is merely the short length inside the multi-stub coupler unit.




Figure 6.1.1.4

Jumper setting : Transformer coupled	Bus A voltage (peak-peak)	Bus B voltage (peak-peak)
BC Output at measurement point X	24.5V (ref 13)	24.4V (ref 15)
Coupler Output at measurement point Y	5.92V (ref 14)	5.68V (ref 16)

spec for voltages measured as above in transformer coupled configuration is 18-27v p-p. at point X.

6.1.2 Output Risetime

Continuing in the configuration of Figure 6.1.1.4 a valid sync command shall be sent from the CDMS Simulator. The risetime and falltime shall be measured between 10% and 90% points, see Figure 6.1.2. The pass criteria are

100nS < Tr < 300nS
100nS < Tf < 300nS

Rise time, Tr	190nS
Fall time, Tf	190nS




Figure 6.1.2 – Output Signal measurements

6.1.3 Output Zero Crossing

Messages shall be sent from the CDMS Simulator with data transitions at time intervals of 500nS, 1000nS, 1500nS and 2000nS (1,2,3,4 bit periods). The zero crossing time shall be measured for positive and negative transitions, see Figure 6.1.3. Specification is ± 25 nS for each case.




Figure 6.1.3– Zero Crossing Interval measurement

Zero Crossing Intervals, nominal	Measurement
500nS +/- 25	Tzcp =
500nS +/- 25	Tzcn =
1000nS +/- 25	Tzcp = 1000
1000nS +/- 25	Tzcn = 1000
1500nS +/- 25	Tzcp = 1490
1500nS +/- 25	Tzcn =
2000nS +/- 25	Tzcp = 2000
2000nS +/- 25	Tzcn =

*Spot checks made here
confirming DDC report
See appendix A.*

6.1.4 Output Distortion

Measure the distortion voltage V_d on the CDMS Simulator signal as defined in Figure 6.1.2. Specification is $< 900\text{mV}$ peak, line-line for transformer-coupled configuration.


Distortion Voltage, V_d	PASS
---------------------------	------

6.1.5 Output Symmetry

32 word messages shall be sent from the CDMS Simulator containing various repeating data values as listed in the table. The output symmetry is determined by measuring the waveform tail-off at the end of each message. The residual voltage (V_r) as shown in Figure 6.1.2 is measured at T_t (2.5 μs after last transition). The pass criterion is $V_r < 250\text{mV}$.

Data Pattern	Residual Voltage, V_r
0x8000	
0x7FFF	Very small V_r
0x0000	
0xFFFF	all $< 100\text{mV}$
0x5555	
0xAAAA	

6.1.6 Output Noise



$R = 70\text{ ohms}$, transformer coupled

Figure 6.1.6 – Configuration for Noise measurement

The RMS voltmeter should have a bandwidth of DC to 10 MHz.

Measure the output noise voltage V_{rms} across the resistor R , with the power off and with the BC disabled.

Specification is $V_{rms} < 14\text{mV}$, for transformer-coupled.

Power	Noise voltage, RMS
Off	See
On, BC disabled	Appendix A

6.1.7 Output Isolation

Start the CDMS Simulator software running in Normal mode, generating a continuous sequence of messages, using the reference Astrium buslist. Measure the signal voltage on the active and inactive busses at the points shown in Figure 6.1.7. Change active bus and repeat the measurement. The specification for isolation is >45dB.




Figure 6.1.7 – Output Isolation measurement

Active Bus	Active Bus Voltage (peak-peak)	Inactive Bus Voltage (peak-peak)	dB (20Log10 Active/Inactive)
A	24.9V (ref 23)	< 20mV (ref 24)	> 60 dB
B	24.7V (ref 27)	25mV (ref 28)	60 dB

6.1.8 Output – Power On/Off noise

Using the configuration of Figure 6.1.7 monitor the voltage on both busses. Shut down the simulator software, then the PC power and record the maximum noise voltage. Repeat the measurement when switching on and starting the Simulator software. Do this test 10 times and record the worst case. Make a copy of oscilloscope traces and attach to the report.

The specification for noise spikes is < +/- 250 mV p-p.

Bus	Max noise transient at Switch Off (peak-peak)		Max noise transient at Switch On (peak-peak)	
	Voltage	Duration	Voltage	Duration
A	< 100mV	not visible	< 100mV	not visible
B	< 100mV	(ref 26)	50mV	10µs (ref 25)

6.1.9 Output Frequency Stability

While running the reference Astrium buslist as in section 6.1.7, monitor the bus signal on an oscilloscope and measure the bit frequency (Fi). Record the minimum (Fsmi) and maximum (Fsmx) over >10,000 measurements. Also measure the average (Fav) over >1000 measurements.

Calculate:

$$SS1 = 100 * (F_{smax} - F_{av}) / F_{av} \quad [spec < 0.01]$$

$$SS2 = 100 * (F_{av} - F_{smin}) / F_{av} \quad [spec < 0.01]$$

$$S1 = 100 * (F_{av} - F_i) / F_i \quad [spec < 0.1]$$

Bit Frequency, F_i	
Minimum, F_{min}	
Maximum, F_{max}	
Average, F_{av}	
SS1	
SS2	
S1	

*Verified by analysis
See DDC report.*

6.1.10 Input Impedance

The input impedance of the BC is measured in the same way as that specified for a RT in section 4.3.5 of the test specifications, RD1. Disable the BC output. Connect a sinewave generator and resistance box to the bus output of the DDC card as shown in the figure. The generator amplitude shall be set to 1 to 2 volts RMS. At each test frequency increase the series resistance from zero until the peak-to-peak voltage measured at point X is halved. (Showing that the input impedance is equal to the resistance box reading).




Figure 6.1.10

Frequency	Impedance, Bus A (ohms)	Impedance, Bus B (ohms)
75 kHz		
100 kHz		
250 kHz	<i>See Appendix A</i>	
500 kHz		
1.0 MHz		

Specification: the impedance should be >1k ohms at all frequencies. (In transformer coupled configuration).

27/09/01.

6.2 1553 Bus Data-link Layer Support

In this section we demonstrate that the Simulator can generate simple messages for later use in testing the instrument RTs. The DDC program "ACE Windows menu" is used. Figure 5.3 shows the setup. A jumper connection is made between channels A and C on the card, to connect BC and BM for bus A.

The RT provided with the simulator is not under test in this section; the aim is to test the Bus Controller which forms part of the CDMS Simulator. The RT is not guaranteed to support all data-link message responses.




Figure 6.2 : Bus Loop-back for data-link tests on Simulator

The RAL CDMS Simulator software is not used in this section, since it is designed to run in a continuous manner controlled by a buslist file. Here only single messages are required.

6.2.1 Mode Commands

Using the DDC program 'ACE Windows menu' in Bus Controller mode create a command message for each of Mode Codes in Table 6-1. Store these commands in configuration file MODECMDS.ACE

Send each mode code command in turn and check that they appear correctly in the bus monitor log file.

i.e load config file MODECMDS.ACE

Run Bus Mon logging.

Send commands

View file Mon.asf

Saved as MON-6.2.1.asf

True 09:15 on 09/27/01

Mode command	Pattern	SA	ref to AD-#3	BC	RT
Dynamic Bus Control	00000	00000	4.3.3.5.1.7.1	NO	NO
Synchronize (without data word *)	00001	00000	4.3.3.5.1.7.2	YES	YES
Transmit Status Word	00010	00000	4.3.3.5.1.7.3	YES	YES
Initiate Self-test **)	00011	00000	4.3.3.5.1.7.4	YES	YES
Transmitter (TX) Shut-Down	00100	00000	4.3.3.5.1.7.5	YES	YES
Override TX Shut-Down	00101	00000	4.3.3.5.1.7.6	YES	YES
Inhibit Terminal Flag	00110	00000	4.3.3.5.1.7.7	YES	YES
Override Inhibit Terminal Flag Bit	00111	00000	4.3.3.5.1.7.8	YES	YES
Reset Remote Terminal **)	01000	00000	4.3.3.5.1.7.9	YES	YES
Transmit Vector Word	10000	00000	4.3.3.5.1.7.11	YES	YES
Synchronize (with data word *)	10001	00000	4.3.3.5.1.7.12	YES	YES
Transmit Last Command	10010	00000	4.3.3.5.1.7.13	YES	YES
Transmit BIT (built-in Test data) Word **)	10011	00000	4.3.3.5.1.7.14	YES	YES
Selected TX Shut Down (SD)	10100	00000	4.3.3.5.1.7.15	NO	NO
Override Selected TX SD	10101	00000	4.3.3.5.1.7.16	NO	NO
Remaining Possible Command pattern (reserved for future use)	all other	00000	4.3.3.5.1.7.10	N/A	N/A

Table 6-1

in file Mon-6.2.1-a.s.f

Mode Code sent	Details	Log Entry
Dynamic bus control: MC0	31-T-00-00	31-T-00-00
Sync without data word: MC1	31-T-00-01	31-T-00-01
Transmit status word: MC2	02-T-00-02	02-T-00-02
Initiate self-test: MC3	31-T-00-03	31-T-00-03
Transmitter shut-down: MC4	31-T-00-04	31-T-00-04
Override Tx shut-down: MC5	31-T-00-05	31-T-00-05
Inhibit terminal flag: MC6	31-T-00-06	31-T-00-06
Override terminal flag inhibit: MC7	31-T-00-07	31-T-00-07
Reset Remote Terminal: MC8	31-T-00-08	31-T-00-08
Transmit Vector word: MC16	02-T-00-16	02-T-00-16
Sync with data: MC17	31-R-00-17, 5555	31-R-00-17, 5555
Transmit last command: MC18	02-T-00-18	02-T-00-18
Transmit built-in-test word: MC19	02-T-00-19	02-T-00-19
Tx shutdown	31-R-00-20, 000A	31-R-00-20, 000A
Override Tx shutdown	31-R-00-21, 000A	31-R-00-21, 000A

6.2.1.1 Required Mode Commands for RT Transmitter Control

This section shows that the simulator can be used to generate messages required by requirements (AD1) section 4.5.9.

Start the Bus Monitor (ACE device 1) logging to a file.

Start the Bus Controller (ACE device 0).

Run the test frame.

Extra test file. f

Examine the MON.ASF file and record the messages transmitted when each command was sent.

saved to Mon 6-2-1-1 - asf

Command	Expected message(s) sent by BC	Bus monitor messages logged.
Valid message PACSCMD1	02-R-11-07 1C80,C000,0007,0102,0008, 0000,0A72	02-R-11-07 1C80,C000,0007,0102,0008 0000,0A72
Expected status	1000	9300 BSW
Mode code: Transmit status, SA0 MC2	02-T-00-02	02-T-00-02
Expected status	1000	9200 BSW
Mode code: Transmitter shutdown MC4	31-T-00-04	31-T-00-04
Expected block status word	8100	8100
Mode code: Override Transmitter shutdown MC5	31-T-00-05	31-T-00-05
Expected block status word	8100	8100
Mode command: Reset remote terminal MC8	31-T-00-08	31-T
Expected block status word	8100	8100

6.2.2 No Response Timeout

Not applicable to the CDMS Simulator BC.

6.2.3 Receive Message

Send the messages listed in Table 6-2 and note the bit pattern recorded in the monitor log file.

in file Section 6-2.ACE

Test receive message	Log Entry
BC send TMConf message to RT2	
02-R-10-02, 1000, 0023	✓

Message # 5.

MON-6-2-4.asf

Table 6-2

6.2.4 Broadcast Message

By design, the CDMS Simulator card will transmit any required bit pattern.

Note: The only apparent anomaly in the specification RD.4 is figure 4.2-1 showing mode code 1 where T/R = 1. However the DDC monitor recognises this as a valid command (and T/R = 0 as invalid).

As a broadcast message test, send a typical spacecraft time broadcast message and note the bit pattern recorded in the monitor log file.

Send to file Mon-6-2A.AC

Test broadcast message	Log Entry
Timecode : 31-R-08-04, 002E, 0102, 0304, 0000	1/1 Msg #4 ✓
Sync without data : 31-T-00-01	1/2 Msg #1 ✓
sync with data : 31-R-00-17, 000C	1/2 Msg #3 ✓

Message #4

Table 6-3

6.2.5 Transmit Message

Send the messages listed in Table 5-2 and note the bit pattern recorded in the monitor log file.

Test transmit message	Log Entry
BC collects TMReq from RT2	1/1 Msg #2 ✓
02-T-10-02	

Message #2

Table 6-4

6.2.6 Receive Low-Level Command

Not applicable to CDMS Simulator.

6.2.7 Data-link Error Messages

Tests to verify the CDMS-Sim response to data-link errors are included in section 6.4.1.4 covering the following errors:

6.2.7.1 RT Status Errors

RT message error
RT busy error
RT subsystem flag
RT terminal flag

6.2.7.2 BC Status Errors

RT transmission error
RT no response timeout
BC loop back error

6.3 Satellite 1553 Bus Transfer-Layer Protocol

6.3.1 Basic Protocol without TM or TC transfer

For this test continue to use the test setup of Figure 6.2 (BC plus bus monitor).

used System Monitor.

Start the ACE menu in Bus monitor mode, ACE device 1.

Run the simulator with buslist file **RT2 buslist** for at least one major frame. (1 second)

Check the bus monitor log file against the list of messages in the table below. Record the start time of each subframe and the offset of each message within a subframe.

Note that this list includes only Broadcast messages (sync, timecode) and TMReq messages. When there is no RT and there are no TCs sent they are the only messages sent on the bus. For an explanation of the buslist format see RD3, CDMS-Sim Users Guide.

Saved to file 6.3.1

Subframe	Message slot (0 - 23)	Start time (uS)	Message type	RT (0 if TC)	SA	Data type	Log file time (uS)	Message MS	Message NMS
0	0	0	MCSync	31	0	None	✓		
1	0	0	MCDData	31	0	SyncFC	✓		
2	0	0	MCDData	31	0	SyncFC	✓		
3	0	0	MCDData	31	0	SyncFC	✓		
3	21	14550	RTtoBC	2	10	TMReq	✓		
4	0	0	MCDData	31	0	SyncFC	✓		
5	0	0	MCDData	31	0	SyncFC	✓		
6	0	0	MCDData	31	0	SyncFC	✓		
6	21	14550	RTtoBC	2	10	TMReq	✓		
7	0	0	MCDData	31	0	SyncFC	✓		
8	0	0	MCDData	31	0	SyncFC	✓		
9	0	0	MCDData	31	0	SyncFC	✓		
9	21	14550	RTtoBC	2	10	TMReq	✓		
10	0	0	MCDData	31	0	SyncFC	✓		
11	0	0	MCDData	31	0	SyncFC	✓		
12	0	0	MCDData	31	0	SyncFC	✓		
12	21	14550	RTtoBC	2	10	TMReq	✓		
13	0	0	MCDData	31	0	SyncFC	✓		
14	0	0	MCDData	31	0	SyncFC	✓		

15	0	0	MCDData	31	0	SyncFC	✓			
16	0	0	MCSync	31	0	SyncFC	✓			
17	0	0	MCDData	31	0	SyncFC	✓			
18	0	0	MCDData	31	0	SyncFC	✓			
19	0	0	MCDData	31	0	SyncFC	✓			
19	21	14550	RTtoBC	2	10	TMReq	✓			
20	0	0	MCDData	31	0	SyncFC	✓			
21	0	0	MCDData	31	0	SyncFC	✓			
22	0	0	MCDData	31	0	SyncFC	✓			
23	0	0	MCDData	31	0	SyncFC	✓			
24	0	0	MCDData	31	0	SyncFC	✓			
25	0	0	MCDData	31	0	SyncFC	✓			
25	21	14550	RTtoBC	2	10	TMReq	✓			
26	0	0	MCDData	31	0	SyncFC	✓			
27	0	0	MCDData	31	0	SyncFC	✓			
28	0	0	MCDData	31	0	SyncFC	✓			
28	21	14550	RTtoBC	2	10	TMReq	✓			
29	0	0	MCDData	31	0	SyncFC	✓			
30	0	0	MCDData	31	0	SyncFC	✓			
31	0	0	MCDData	31	0	SyncFC	✓			
31	21	14550	RTtoBC	2	10	TMReq	✓			
32	0	0	MCDData	31	0	SyncFC	✓			
32	2	900	MCDData	31	8	Timecode	✓			
33	0	0	MCDData	31	0	SyncFC	✓			
34	0	0	MCDData	31	0	SyncFC	✓			
35	0	0	MCDData	31	0	SyncFC	✓			
36	0	0	MCDData	31	0	SyncFC	✓			
37	0	0	MCDData	31	0	SyncFC	✓			
38	0	0	MCDData	31	0	SyncFC	✓			
38	21	14550	RTtoBC	2	10	TMReq	✓			

39	0	0	MCDData	31	0	SyncFC	✓			
40	0	0	MCDData	31	0	SyncFC	✓			
41	0	0	MCDData	31	0	SyncFC	✓			
41	21	14550	RTtoBC	2	10	TMReq	✓			
42	0	0	MCDData	31	0	SyncFC	✓			
43	0	0	MCDData	31	0	SyncFC	✓			
44	0	0	MCDData	31	0	SyncFC	✓			
44	21	14550	RTtoBC	2	10	TMReq	✓			
45	0	0	MCDData	31	0	SyncFC	✓			
46	0	0	MCDData	31	0	SyncFC	✓			
47	0	0	MCDData	31	0	SyncFC	✓			
47	21	14550	RTtoBC	2	10	TMReq	✓			
48	0	0	MCDData	31	0	SyncFC	✓			
49	0	0	MCDData	31	0	SyncFC	✓			
50	0	0	MCDData	31	0	SyncFC	✓			
51	0	0	MCDData	31	0	SyncFC	✓			
51	21	14550	RTtoBC	2	10	TMReq	✓			
52	0	0	MCDData	31	0	SyncFC	✓			
53	0	0	MCDData	31	0	SyncFC	✓			
54	0	0	MCDData	31	0	SyncFC	✓			
54	21	14550	RTtoBC	2	10	TMReq	✓			
55	0	0	MCDData	31	0	SyncFC	✓			
56	0	0	MCDData	31	0	SyncFC	✓			
57	0	0	MCDData	31	0	SyncFC	✓			
57	21	14550	RTtoBC	2	10	TMReq	✓			
58	0	0	MCDData	31	0	SyncFC	✓			
59	0	0	MCDData	31	0	SyncFC	✓			
60	0	0	MCDData	31	0	SyncFC	✓			
60	21	14550	RTtoBC	2	10	TMReq	✓			
61	0	0	MCDData	31	0	SyncFC	✓			
62	0	0	MCDData	31	0	SyncFC	✓			

63	0	0	MCDData	31	0	SyncFC	✓			
63	21	14550	RTtoBC	2	10	TMReq	✓			

	Specification	
Major Frame duration	1.000 seconds	1.048 uS +/- 16 uS
Subframe duration	15,625 mS	15,650 uS +/- 0 uS
Broadcast time increments OK ?	✓	
Subframe counter increments ?	✓	

6.3.2 TC Packet transfer

Connect the Simulator (BC), monitor (BM), and the Remote Terminal (RT) together via a bus coupler unit as shown in Figure 6.3.2.




Figure 6.3.2 – Bus Configuration for TC Packet Transfer

Start the ACE menu as Bus monitor – logging on.
 Select buslist file **RT2 buslist**.
 Select bus A
 Start the Bus Controller
 Set the RT mode to Echo.
 Start the RT running.
 Set TC mode to local.
 Select the TC to **MaxlenTC.txt**; this TC has length = 124 words with the data in a counting pattern.
 Send the TC
 Check the bus monitor log file and record the messages and RT responses in the table below.

	Messages	Expected values	Recorded values from Log file
1	RT2, SA11R, TC transfer	02-R-11-00	02-R-11-32
2	RT status	1000	1000
3	RT2, SA12R, TC transfer	02-R-12-00	02-R-12-32
4	RT status	1000	1000
5	RT2, SA13R, TC transfer	02-R-13-00	02-R-13-32
6	RT status	1000	1000
7	RT2, SA14R, TC transfer	02-R-14-28	02-R-14-28
8	RT status	1000	1000
9	RT2, SA27R, TC descriptor	02-R-27-02, 041C, 0101	02-R-27-02 041C 0102
10	RT status	1000	1000
11	wait 2 subframes		
12	RT2, SA27T, TC confirmation	02-T-27-02, 041C, 0101	02-T-27-02 041C 0102
13	RT status	1000	1000
14	Simulator TC list indicates confirmation received ?		No - part of Error logging.

using Systan Monitor.

Are 1-10 in same subframe ?

☒

Note Command sent was 2nd one,
hence 0102 !
↑
counter.

Message 1 contains data words 1C80 - 001C ?

☒

Message 2 contains data words 001D - 003C ?

☒

Message 3 contains data words 003D - 005C ?

☒

Message 4 contains data words 005D - 0078 ?

☒

6.3.3 RT Error Conditions

6.3.3.1 No TC Confirmation Message

Disable the TC confirmation in the RT software.

Re-send the maximum length TC.

Wait 2 major frames.

Cannot be done.
Not implemented.

Confirm that the Simulator indicates no confirmation on the transmitted TCs list.

☐

6.3.3.2 No Increment of TC Sequence Counter

This condition cannot be simulated by the CDMS Sim software.

There would be no RT error, since an RT cannot detect a new TC without it?

Cannot be done

6.3.4 TM Packet transfer

Continue with same hardware configuration as Figure 6.3.2

Start the Bus monitor software.

Run the simulator with buslist file **RT2 buslist** for at least two major frames.

Run RT with mode = burst (TM packet length is maximum at 512 words, with counting data.)

Check the bus monitor log file for the messages in the table below.

In log file 6.3.4

	Messages	Expected message	Messages from Log file	Time from sync
1	RT2, SA10T, TM Request	02-T-10-02,1000,0001	✓	
2	RT status	1000	✓	
3	wait 2 subframes		✓	
4	RT2, SA11T, TM transfer	data = 0C80 – 0018	✓	2401 μ s
5	RT status	1000	✓	
5	RT2, SA12T, TM transfer	data = 0019 – 0038	✓	3151
6	RT status	1000	✓	
7	RT2, SA13T, TM transfer	data = 0039 – 0058	✓	3900
8	RT status	1000	✓	
9	RT2, SA14T, TM transfer	data = 0059 – 0078	✓	4650
10	RT status	1000	✓	
11	RT2, SA15T, TM transfer	data = 0079 – 0098	✓	5404
12	RT status	1000	✓	
13	RT2, SA16T, TM transfer	data = 0099 – 00B8	✓	6155
14	RT status	1000	✓	
15	RT2, SA17T, TM transfer	data = 00B9 – 00D8	✓	6905
16	RT status	1000	✓	
17	RT2, SA18T, TM transfer	data = 00D9 – 00F8	✓	7656
18	RT status	1000	✓	
19	RT2, SA19T, TM transfer	data = 00F9 – 0118	✓	8407
20	RT status	1000	✓	
21	RT2, SA20T, TM transfer	data = 0119 – 0138	✓	9158
22	RT status	1000	✓	
23	RT2, SA21T, TM transfer	data = 0139 – 0158	✓	9909
24	RT status	1000	✓	
25	RT2, SA22T, TM transfer	data = 0159 – 0178	✓	10659
26	RT status	1000	✓	
27	RT2, SA23T, TM transfer	data = 0179 – 0198	✓	11410
28	RT status	1000	✓	
29	RT2, SA24T, TM transfer	data = 0199 – 01B8	✓	12161
30	RT status	1000	✓	
31	RT2, SA25T, TM transfer	data = 01B9 – 01D8	✓	12912
32	RT status	1000	✓	
33	RT2, SA26T, TM transfer	data = 01D9 – 01F8	✓	13663
34	RT status	1000	✓	
35	RT2, SA10R, TM confirmation	02-R-10-02	✓	
36	RT status	1000	✓	

Record number of messages requested = 0x10

Record number of words in last message

0x10
32

(THREQ = 0x1000, 0001)

All TM transfer messages in same subframe ? ☒Time of transfers correct ? ☒gap = 750 μ s ± 10 Correct number of data words in each message (32) ? ☒Packet displayed correctly on Simulator display ? ☒

6.3.5 CDMS-Sim (BC) Error Conditions

Cannot be tested; won't work without handshake.

6.3.6 Bus Polling Sequence: Nominal Mode

Continue the same hardware configuration as Figure 6.3.2

Same @ 6.3.6 system
Same @ 6.3.6 - CDMS

Start the Bus monitor software.

Run the simulator with the **Astrium buslist**. This is the suggested bus polling sequence for CDMS Nominal mode.

RT mode = burst TM

RT emulated = RT1

Start the RT.

The RT should be capable of generating 16 packets/major frame.

Let the BC run for at least two major frames.

Check the bus monitor log file and find the point where the RT started. Record the messages in the table below. Note that only the bold messages are sent unless there is a TC, or a different RT is present.

Subframe	Message slot (0 - 23)	Start time (uS)	Message type	RT (0 if TC)	SA	Data type	Logfile time (uS)	Message MS	Message NMS
0	0	0	MCSync	31	0	None			
0	4	2400	BCtoRT	0	11	PacketTC			
0	20	14400	BCtoRT	0	27	TCDesc			
1	0	0	MCDData	31	0	SyncFC	34.172375		
1	4	2400	RTtoBC	1	11	PacketTM	34.174776	0000	0005
1	20	14400	BCtoRT	1	10	TMConf	34.186038	1000	0005
1	21	14550	RTtoBC	3	10	TMReq	34.186940	NORSP	
2	0	0	MCDData	31	0	SyncFC	34.187975		
2	4	2400	RTtoBC	2	11	PacketTM			
2	20	14400	BCtoRT	2	10	TMConf			
2	21	14550	RTtoBC	1	10	TMReq	34.190376	1000	0005
2	22	14700	RTtoBC	0	27	TCConf			
3	0	0	MCDData	31	0	SyncFC			
3	4	2400	RTtoBC	3	11	PacketTM			
3	20	14400	BCtoRT	3	10	TMConf			
4	0	0	MCDData	31	0	SyncFC			
4	4	2400	RTtoBC	1	11	PacketTM			
4	20	14400	BCtoRT	1	10	TMConf			
5	0	0	MCDData	31	0	SyncFC	34.234775		
5	21	14550	RTtoBC	1	10	TMReq	34.249926	1000	0006

2401 μ s ✓
14414 μ s ✓
14565 μ s ✓2401 μ s *
NCR514551 μ s ✓

6	0	0	MCDData	31	0	SyncFC	✓			
7	0	0	MCDData	31	0	SyncFC	✓	34.265975		
7	4	2400	RTtoBC	1	11	PacketTM	✓	.268376		
7	20	14400	BCtoRT	1	10	TMConf	✓	.290389	1000	0006
8	0	0	MCDData	31	0	SyncFC	✓			
8	21	14550	RTtoBC	1	10	TMReq	✓		1000	0007
9	0	0	MCDData	31	0	SyncFC	✓			
10	0	0	MCDData	31	0	SyncFC	✓			
10	4	2400	RTtoBC	1	11	PacketTM	✓		0000	0007
10	20	14400	BCtoRT	1	10	TMConf	✓		1000	0007
11	0	0	MCDData	31	0	SyncFC	✓			
11	21	14550	RTtoBC	1	10	TMReq	✓		1000	0008
12	0	0	MCDData	31	0	SyncFC	✓			
12	21	14550	RTtoBC	2	10	TMReq	✓		No RSP	
13	0	0	MCDData	31	0	SyncFC	✓	34.359576		
13	4	2400	RTtoBC	1	11	PacketTM	✓	34.361977	0000	0008
13	20	14400	BCtoRT	1	10	TMConf	✓	.373989	1000	0008
13	21	14550	RTtoBC	3	10	TMReq	✓	.374140	No RSP	
14	0	0	MCDData	31	0	SyncFC	✓			
14	4	2400	RTtoBC	2	11	PacketTM				
14	20	14400	BCtoRT	2	10	TMConf				
14	21	14550	RTtoBC	1	10	TMReq	✓		1000	0008
15	0	0	MCDData	31	0	SyncFC	✓			
15	4	2400	RTtoBC	3	11	PacketTM				
15	20	14400	BCtoRT	3	10	TMConf				
16	0	0	MCDData	31	0	SyncFC	✓	.406376		
16	4	2400	BCtoRT	0	11	PacketTC				
16	20	14400	BCtoRT	0	27	TCDesc				
16	21	14550	RTtoBC	10	10	TMReq	✓	.408777		
17	0	0	MCDData	31	0	SyncFC	✓			
17	4	2400	RTtoBC	1	11	PacketTM				
17	20	14400	BCtoRT	1	10	TMConf				
18	0	0	MCDData	31	0	SyncFC	✓			
18	4	2400	RTtoBC	10	11	PacketTM				
18	20	14400	BCtoRT	10	10	TMConf				
18	21	14550	RTtoBC	1	10	TMReq	✓		1000	0009
18	22	14700	RTtoBC	0	27	TCConf				
19	0	0	MCDData	31	0	SyncFC	✓			
20	0	0	MCDData	31	0	SyncFC	✓	.468776		
20	4	2400	RTtoBC	1	11	PacketTM	✓	.471177	0000	0009
20	20	14400	BCtoRT	1	10	TMConf	✓	.483190	1000	0009
20	21	14550	RTtoBC	11	10	TMReq	✓	.483341	No RSP	
21	0	0	MCDData	31	0	SyncFC	✓			
21	21	14550	RTtoBC	1	10	TMReq	✓		1000	0009
22	0	0	MCDData	31	0	SyncFC	✓			
22	4	2400	RTtoBC	11	11	PacketTM				
22	20	14400	BCtoRT	11	10	TMConf				
22	21	14550	RTtoBC	12	10	TMReq	✓			

2401 μ S ✓
14414 μ S ✓2401 μ S ✓
14413 μ S ✓
14564 μ S ✓2401 X NCR
S← SLOW R-
HERE

MCDData

23	0	0	MCDData	31	0	SyncFC	✓			
23	4	2400	RTtoBC	1	11	PacketTM				
23	20	14400	BCtoRT	1	10	TMConf				
24	0	0	MCDData	31	0	SyncFC	✓			
24	4	2400	RTtoBC	12	11	PacketTM				
24	20	14400	BCtoRT	12	10	TMConf				
24	21	14550	RTtoBC	1	10	TMReq	✓			
25	0	0	MCDData	31	0	SyncFC	✓			
26	0	0	MCDData	31	0	SyncFC	✓			
26	4	2400	RTtoBC	1	11	PacketTM	✓			
26	20	14400	BCtoRT	1	10	TMConf	✓			
27	0	0	MCDData	31	0	SyncFC	✓			
27	21	14550	RTtoBC	1	10	TMReq	✓			
28	0	0	MCDData	31	0	SyncFC	✓			
29	0	0	MCDData	31	0	SyncFC	✓			
29	4	2400	RTtoBC	1	11	PacketTM	✓			
29	20	14400	BCtoRT	1	10	TMConf	✓			
30	0	0	MCDData	31	0	SyncFC	✓			
30	21	14550	RTtoBC	1	10	TMReq	✓			
31	0	0	MCDData	31	0	SyncFC	✓			
32	0	0	MCDData	31	0	SyncFC	✓	34-655976		
32	2	900	MCDData	31	8	Timecode	✓	656877	002E 0000 0518 0000	901 ✓
32	4	2400	BCtoRT	0	11	PacketTC				
32	20	14400	BCtoRT	0	27	TCDesc				
32	21	14550	RTtoBC	13	10	TMReq	✓	658378	NA-RSP	2402 X NERS
33	0	0	MCDData	31	0	SyncFC	✓			
33	4	2400	RTtoBC	1	11	PacketTM	✓			
33	20	14400	BCtoRT	1	10	TMConf	✓			
34	0	0	MCDData	31	0	SyncFC	✓			
34	4	2400	RTtoBC	13	11	PacketTM				
34	20	14400	BCtoRT	13	10	TMConf				
34	21	14550	RTtoBC	1	10	TMReq	✓			
34	22	14700	RTtoBC	0	27	TCConf				
35	0	0	MCDData	31	0	SyncFC	✓			
35	21	14550	RTtoBC	14	10	TMReq	✓			
36	0	0	MCDData	31	0	SyncFC	✓			
36	4	2400	RTtoBC	1	11	PacketTM				
36	20	14400	BCtoRT	1	10	TMConf				
37	0	0	MCDData	31	0	SyncFC	✓			
37	4	2400	RTtoBC	14	11	PacketTM				
37	20	14400	BCtoRT	14	10	TMConf				
37	21	14550	RTtoBC	1	10	TMReq	✓			
38	0	0	MCDData	31	0	SyncFC	✓			
38	21	14550	RTtoBC	2	10	TMReq	✓			
39	0	0	MCDData	31	0	SyncFC	✓			
39	4	2400	RTtoBC	1	11	PacketTM	✓			
39	20	14400	BCtoRT	1	10	TMConf	✓			

slow RT

901

2402 X NERS

40	0	0	MCDData	31	0	SyncFC	✓			
40	4	2400	RTtoBC	2	11	PacketTM				
40	20	14400	BCtoRT	2	10	TMConf				
40	21	14550	RTtoBC	1	10	TMReq	✓			
41	0	0	MCDData	31	0	SyncFC	✓			
42	0	0	MCDData	31	0	SyncFC	✓			
42	4	2400	RTtoBC	1	11	PacketTM				
42	20	14400	BCtoRT	1	10	TMConf				
43	0	0	MCDData	31	0	SyncFC	✓			
44	0	0	MCDData	31	0	SyncFC	✓			
45	0	0	MCDData	31	0	SyncFC	✓			
46	0	0	MCDData	31	0	SyncFC	✓			
47	0	0	MCDData	31	0	SyncFC	✓			
48	0	0	MCDData	31	0	SyncFC	✓			
48	4	2400	BCtoRT	0	11	PacketTC				
48	20	14400	BCtoRT	0	27	TCDesc				
49	0	0	MCDData	31	0	SyncFC	✓			
50	0	0	MCDData	31	0	SyncFC	✓			
50	21	14550	RTtoBC	1	10	TMReq	✓			
50	22	14700	RTtoBC	0	27	TCConf				
51	0	0	MCDData	31	0	SyncFC	✓			
52	0	0	MCDData	31	0	SyncFC	✓			
52	4	2400	RTtoBC	1	11	PacketTM	✓			
52	20	14400	BCtoRT	1	10	TMConf	✓			
52	21	14550	RTtoBC	3	10	TMReq	✓			
53	0	0	MCDData	31	0	SyncFC	✓			
53	21	14550	RTtoBC	1	10	TMReq	✓			
54	0	0	MCDData	31	0	SyncFC	✓			
54	4	2400	RTtoBC	3	11	PacketTM				
54	20	14400	BCtoRT	3	10	TMConf				
55	0	0	MCDData	31	0	SyncFC	✓			
55	4	2400	RTtoBC	1	11	PacketTM				
55	20	14400	BCtoRT	1	10	TMConf				
56	0	0	MCDData	31	0	SyncFC	✓			
57	0	0	MCDData	31	0	SyncFC	✓			
58	0	0	MCDData	31	0	SyncFC	✓			
59	0	0	MCDData	31	0	SyncFC	✓			
60	0	0	MCDData	31	0	SyncFC	✓			
61	0	0	MCDData	31	0	SyncFC	✓			
62	0	0	MCDData	31	0	SyncFC	✓			
62	21	14550	RTtoBC	1	10	TMReq	✓			
63	0	0	MCDData	31	0	SyncFC	✓			

63	21	14550	RTtoBC	2	10	TMReq	✓			
----	----	-------	--------	---	----	-------	---	--	--	--

Check the following:

All TM packet transfer subframes are filled?
(bitrate = 131k bits/sec)

NO

RT is sometimes slow with a new TM Req.

Major Frame duration

1.0485 Sec

Major Frame Sync message

✓

Subframe Sync message

✓

Subframe counter increments correctly ?

✓

Make a printout of the TM packet logfile.
Check that the datalink layer TM packet counter increments from 1 to 255 then resets to 1 at rollover.

✓

TELEMETRY-26-SEP-01.TXT

Make a printout of the 1553 message logfile.

See annex

6.3.7 Burst Mode

Use the same hardware configuration as Figure 6.4.2

Start the Bus monitor software.

RT mode = burst TM

RT emulated = RT2

The RT should be capable of generating 60 packets/major frame.

Start the RT.

Saved to file 6.3.7 system
saved to file 6.3.7 CDMS

Run the simulator with buslist file **RT2 BurstMode buslist**. for at least two major frames.

Check the bus monitor log file for the messages in the table below.

Subframe	Message slot (0 - 23)	Start time (uS)	Message type	RT (0 if TC)	SA	Data type	Log file time (uS)	Message MS	Message NMS
0	0	0	MCSync	31	0	None	✓ 68.327573	FC01	
0	4	2400	BCtoRT	0	11	PacketTC			
0	20	14400	BCtoRT	0	27	TCDesc			
1	0	0	MCDData	31	0	SyncFC	✓ .343173	F811	1001
1	4	2400	RTtoBC	2	11	PacketTM	✓ .345574	0C80	0000
1	20	14400	BCtoRT	2	10	TMConf	✓ .357586	1000	0000
1	21	14550	RTtoBC	2	10	TMReq	✓ .357738	1000	0000
2	0	0	MCDData	31	0	SyncFC	✓		
2	4	2400	RTtoBC	2	11	PacketTM			
2	20	14400	BCtoRT	2	10	TMConf			
2	21	14550	RTtoBC	2	10	TMReq	✓	1000	0000
2	22	14700	RTtoBC	0	27	TCCConf			
3	0	0	MCDData	31	0	SyncFC	✓		
3	4	2400	RTtoBC	2	11	PacketTM			
3	20	14400	BCtoRT	2	10	TMConf		1000	0000
3	21	14550	RTtoBC	2	10	TMReq	✓		

4	0	0	MCDData	31	0	SyncFC	✓		
4	4	2400	RTtoBC	2	11	PacketTM	✓		
4	20	14400	BCtoRT	2	10	TMConf	✓		
4	21	14550	RTtoBC	2	10	TMReq	✓	1500	500E
5	0	0	MCDData	31	0	SyncFC	✓		
5	4	2400	RTtoBC	2	11	PacketTM	✓	0C80	500E
5	20	14400	BCtoRT	2	10	TMConf	✓	1500	500E
5	21	14550	RTtoBC	2	10	TMReq	✓	1500	500E
6	0	0	MCDData	31	0	SyncFC	✓		
6	4	2400	RTtoBC	2	11	PacketTM	✓		
6	20	14400	BCtoRT	2	10	TMConf	✓		
6	21	14550	RTtoBC	2	10	TMReq	✓	1500	500E
7	0	0	MCDData	31	0	SyncFC	✓		
7	4	2400	RTtoBC	2	11	PacketTM	✓		
7	20	14400	BCtoRT	2	10	TMConf	✓		
7	21	14550	RTtoBC	2	10	TMReq	✓	1500	500F
8	0	0	MCDData	31	0	SyncFC	✓		
8	4	2400	RTtoBC	2	11	PacketTM	✓		
8	20	14400	BCtoRT	2	10	TMConf	✓		
8	21	14550	RTtoBC	2	10	TMReq	✓	1500	500F
9	0	0	MCDData	31	0	SyncFC	✓		
9	4	2400	RTtoBC	2	11	PacketTM	✓	0C90	500F
9	20	14400	BCtoRT	2	10	TMConf	✓	1500	500F
9	21	14550	RTtoBC	2	10	TMReq	✓	1500	500F
10	0	0	MCDData	31	0	SyncFC	✓		
10	4	2400	RTtoBC	2	11	PacketTM	✓		
10	20	14400	BCtoRT	2	10	TMConf	✓		
10	21	14550	RTtoBC	2	10	TMReq	✓	1500	500F
11	0	0	MCDData	31	0	SyncFC	✓		
11	4	2400	RTtoBC	2	11	PacketTM	✓		
11	20	14400	BCtoRT	2	10	TMConf	✓		
11	21	14550	RTtoBC	2	10	TMReq	✓	1500	5010
12	0	0	MCDData	31	0	SyncFC	✓		
12	4	2400	RTtoBC	2	11	PacketTM	✓		
12	20	14400	BCtoRT	2	10	TMConf	✓		
12	21	14550	RTtoBC	2	10	TMReq	✓	1500	5010
13	0	0	MCDData	31	0	SyncFC	✓		
13	4	2400	RTtoBC	2	11	PacketTM	✓	0C80	5010
13	20	14400	BCtoRT	2	10	TMConf	✓	1500	5010
13	21	14550	RTtoBC	2	10	TMReq	✓	1500	5010
14	0	0	MCDData	31	0	SyncFC	✓		
14	4	2400	RTtoBC	2	11	PacketTM	✓		
14	20	14400	BCtoRT	2	10	TMConf	✓		
14	21	14550	RTtoBC	2	10	TMReq	✓	1500	5010
15	0	0	MCDData	31	0	SyncFC	✓		
15	4	2400	RTtoBC	2	11	PacketTM	✓		
15	20	14400	BCtoRT	2	10	TMConf	✓		
15	21	14550	RTtoBC	2	10	TMReq	✓	1500	5011

Acceptance Test Plan

Ref: SPIRE-RAL-PRJ-
000733

Issue: 1

Date: 26/9/01

Page: 33

Data									
16	0	0	MCSync	31	0	SyncFC	✓		
16	4	2400	BCtoRT	0	11	PacketTC			
16	20	14400	BCtoRT	0	27	TCDesc			
17	0	0	MCDData	31	0	SyncFC	✓		
17	4	2400	RTtoBC	2	11	PacketTM		0080	0011
17	20	14400	BCtoRT	2	10	TMConf	✓	1000	0011
17	21	14550	RTtoBC	2	10	TMReq	✓	1000	0011
18	0	0	MCDData	31	0	SyncFC	✓		
18	4	2400	RTtoBC	10	11	PacketTM			
18	20	14400	BCtoRT	10	10	TMConf			
18	21	14550	RTtoBC	2	10	TMReq	✓	1000	0011
18	22	14700	RTtoBC	0	27	TCConf			
19	0	0	MCDData	31	0	SyncFC	✓		
19	4	2400	RTtoBC	2	11	PacketTM			
19	20	14400	BCtoRT	2	10	TMConf			
19	21	14550	RTtoBC	2	10	TMReq	✓	1000	0012
20	0	0	MCDData	31	0	SyncFC	✓		
20	4	2400	RTtoBC	2	11	PacketTM			
20	20	14400	BCtoRT	2	10	TMConf			
20	21	14550	RTtoBC	2	10	TMReq	✓	1000	0012
21	0	0	MCDData	31	0	SyncFC	✓		
21	4	2400	RTtoBC	2	11	PacketTM	✓	0080	0012
21	20	14400	BCtoRT	2	10	TMConf	✓	1000	0012
21	21	14550	RTtoBC	2	10	TMReq	✓	1000	0012
22	0	0	MCDData	31	0	SyncFC	✓		
22	4	2400	RTtoBC	2	11	PacketTM			
22	20	14400	BCtoRT	2	10	TMConf			
22	21	14550	RTtoBC	2	10	TMReq	✓		
23	0	0	MCDData	31	0	SyncFC	✓		
23	4	2400	RTtoBC	2	11	PacketTM			
23	20	14400	BCtoRT	2	10	TMConf	✓		
23	21	14550	RTtoBC	2	10	TMReq	✓		
24	0	0	MCDData	31	0	SyncFC	✓		
24	4	2400	RTtoBC	12	11	PacketTM			
24	20	14400	BCtoRT	12	10	TMConf			
24	21	14550	RTtoBC	2	10	TMReq	✓		
25	0	0	MCDData	31	0	SyncFC	✓		
25	4	2400	RTtoBC	12	11	PacketTM	✓		
25	20	14400	BCtoRT	12	10	TMConf	✓		
25	21	14550	RTtoBC	2	10	TMReq	✓		
26	0	0	MCDData	31	0	SyncFC	✓		
26	4	2400	RTtoBC	2	11	PacketTM			
26	20	14400	BCtoRT	2	10	TMConf			
26	21	14550	RTtoBC	2	10	TMReq	✓		
27	0	0	MCDData	31	0	SyncFC	✓		
27	4	2400	RTtoBC	12	11	PacketTM			
27	20	14400	BCtoRT	12	10	TMConf	✓		
27	21	14550	RTtoBC	2	10	TMReq	✓		
28	0	0	MCDData	31	0	SyncFC	✓		

28	4	2400	RTtoBC	12	11	PacketTM			
28	20	14400	BCtoRT	12	10	TMConf	✓		
28	21	14550	RTtoBC	2	10	TMReq	✓		
29	0	0	MCDData	31	0	SyncFC	✓		
29	4	2400	RTtoBC	2	11	PacketTM	✓		
29	20	14400	BCtoRT	2	10	TMConf	✓		
29	21	14550	RTtoBC	2	10	TMReq	✓		
30	0	0	MCDData	31	0	SyncFC	✓		
30	4	2400	RTtoBC	2	11	PacketTM			
30	20	14400	BCtoRT	2	10	TMConf			
30	21	14550	RTtoBC	2	10	TMReq	✓		
31	0	0	MCDData	31	0	SyncFC	✓		
31	4	2400	RTtoBC	2	11	PacketTM			
31	20	14400	BCtoRT	2	10	TMConf			
31	21	14550	RTtoBC	2	10	TMReq	✓		
32	0	0	MCDData	31	0	SyncFC	✓		
32	2	900	MCDData	31	8	Timecode	✓		
32	4	2400	BCtoRT	0	11	PacketTC			
32	20	14400	BCtoRT	0	27	TCDesc			
33	0	0	MCDData	31	0	SyncFC	✓		
33	4	2400	RTtoBC	2	11	PacketTM	✓		
33	20	14400	BCtoRT	2	10	TMConf	✓		
33	21	14550	RTtoBC	2	10	TMReq	✓		
34	0	0	MCDData	31	0	SyncFC	✓		
34	4	2400	RTtoBC	13	11	PacketTM			
34	20	14400	BCtoRT	13	10	TMConf			
34	21	14550	RTtoBC	2	10	TMReq	✓		
34	22	14700	RTtoBC	0	27	TCCConf			
35	0	0	MCDData	31	0	SyncFC	✓		
35	4	2400	RTtoBC	2	11	PacketTM			
35	20	14400	BCtoRT	2	10	TMConf			
35	21	14550	RTtoBC	2	10	TMReq	✓		
36	0	0	MCDData	31	0	SyncFC	✓		
36	4	2400	RTtoBC	2	11	PacketTM			
36	20	14400	BCtoRT	2	10	TMConf			
36	21	14550	RTtoBC	2	10	TMReq	✓		
37	0	0	MCDData	31	0	SyncFC	✓		
37	4	2400	RTtoBC	14	11	PacketTM	✓		
37	20	14400	BCtoRT	14	10	TMConf	✓		
37	21	14550	RTtoBC	2	10	TMReq	✓		
38	0	0	MCDData	31	0	SyncFC	✓		
38	4	2400	RTtoBC	2	11	PacketTM			
38	20	14400	BCtoRT	2	10	TMConf			
38	21	14550	RTtoBC	2	10	TMReq	✓		
39	0	0	MCDData	31	0	SyncFC	✓		
39	4	2400	RTtoBC	2	11	PacketTM			
39	20	14400	BCtoRT	2	10	TMConf			
39	21	14550	RTtoBC	2	10	TMReq	✓		
40	0	0	MCDData	31	0	SyncFC	✓		

40	4	2400	RTtoBC	2	11	PacketTM			
40	20	14400	BCtoRT	2	10	TMConf			
40	21	14550	RTtoBC	2	10	TMReq	✓		
41	0	0	MCDData	31	0	SyncFC	✓		
41	4	2400	RTtoBC	2	11	PacketTM	✓		
41	20	14400	BCtoRT	2	10	TMConf	✓		
41	21	14550	RTtoBC	2	10	TMReq	✓		
42	0	0	MCDData	31	0	SyncFC	✓		
42	4	2400	RTtoBC	2	11	PacketTM			
42	20	14400	BCtoRT	2	10	TMConf	✓		
42	21	14550	RTtoBC	2	10	TMReq	✓		
43	0	0	MCDData	31	0	SyncFC	✓		
43	4	2400	RTtoBC	2	11	PacketTM			
43	20	14400	BCtoRT	2	10	TMConf			
43	21	14550	RTtoBC	2	10	TMReq	✓		
44	0	0	MCDData	31	0	SyncFC	✓		
44	4	2400	RTtoBC	2	11	PacketTM			
44	20	14400	BCtoRT	2	10	TMConf			
44	21	14550	RTtoBC	2	10	TMReq	✓		
45	0	0	MCDData	31	0	SyncFC	✓		
45	4	2400	RTtoBC	2	11	PacketTM	✓		
45	20	14400	BCtoRT	2	10	TMConf	✓		
45	21	14550	RTtoBC	2	10	TMReq	✓		
46	0	0	MCDData	31	0	SyncFC	✓		
46	4	2400	RTtoBC	2	11	PacketTM			
46	20	14400	BCtoRT	2	10	TMConf			
46	21	14550	RTtoBC	2	10	TMReq	✓		
47	0	0	MCDData	31	0	SyncFC	✓		
47	4	2400	RTtoBC	2	11	PacketTM			
47	20	14400	BCtoRT	2	10	TMConf			
47	21	14550	RTtoBC	2	10	TMReq	✓		
48	0	0	MCDData	31	0	SyncFC	✓		
48	4	2400	BCtoRT	0	11	PacketTC			
48	20	14400	BCtoRT	0	27	TCDesc			
49	0	0	MCDData	31	0	SyncFC	✓		
49	4	2400	RTtoBC	2	11	PacketTM	✓		
49	20	14400	BCtoRT	2	10	TMConf	✓		
49	21	14550	RTtoBC	2	10	TMReq	✓		
50	0	0	MCDData	31	0	SyncFC	✓		
50	4	2400	RTtoBC	2	11	PacketTM			
50	20	14400	BCtoRT	2	10	TMConf			
50	21	14550	RTtoBC	2	10	TMReq	✓		
50	22	14700	RTtoBC	0	27	TCCConf			
51	0	0	MCDData	31	0	SyncFC	✓		
51	4	2400	RTtoBC	2	11	PacketTM			
51	20	14400	BCtoRT	2	10	TMConf			
51	21	14550	RTtoBC	2	10	TMReq	✓		
52	0	0	MCDData	31	0	SyncFC	✓		
52	4	2400	RTtoBC	2	11	PacketTM			

52	20	14400	BCtoRT	2	10	TMConf				
52	21	14550	RTtoBC	2	10	TMReq	✓			
53	0	0	MCDData	31	0	SyncFC	✓			
53	4	2400	RTtoBC	2	11	PacketTM	✓			
53	20	14400	BCtoRT	2	10	TMConf	✓			
53	21	14550	RTtoBC	2	10	TMReq	✓			
54	0	0	MCDData	31	0	SyncFC	✓			
54	4	2400	RTtoBC	2	11	PacketTM	✓			
54	20	14400	BCtoRT	2	10	TMConf	✓			
54	21	14550	RTtoBC	2	10	TMReq	✓			
55	0	0	MCDData	31	0	SyncFC	✓			
55	4	2400	RTtoBC	2	11	PacketTM	✓			
55	20	14400	BCtoRT	2	10	TMConf	✓			
55	21	14550	RTtoBC	2	10	TMReq	✓			
56	0	0	MCDData	31	0	SyncFC	✓			
56	4	2400	RTtoBC	2	11	PacketTM	✓			
56	20	14400	BCtoRT	2	10	TMConf	✓			
56	21	14550	RTtoBC	2	10	TMReq	✓			
57	0	0	MCDData	31	0	SyncFC	✓			
57	4	2400	RTtoBC	2	11	PacketTM	✓			
57	20	14400	BCtoRT	2	10	TMConf	✓			
57	21	14550	RTtoBC	2	10	TMReq	✓			
58	0	0	MCDData	31	0	SyncFC	✓			
58	4	2400	RTtoBC	2	11	PacketTM	✓			
58	20	14400	BCtoRT	2	10	TMConf	✓			
58	21	14550	RTtoBC	2	10	TMReq	✓			
59	0	0	MCDData	31	0	SyncFC	✓			
59	4	2400	RTtoBC	2	11	PacketTM	✓			
59	20	14400	BCtoRT	2	10	TMConf	✓			
59	21	14550	RTtoBC	2	10	TMReq	✓			
60	0	0	MCDData	31	0	SyncFC	✓			
60	4	2400	RTtoBC	2	11	PacketTM	✓			
60	20	14400	BCtoRT	2	10	TMConf	✓			
60	21	14550	RTtoBC	2	10	TMReq	✓			
61	0	0	MCDData	31	0	SyncFC	✓			
61	4	2400	RTtoBC	2	11	PacketTM	✓			
61	20	14400	BCtoRT	2	10	TMConf	✓			
61	21	14550	RTtoBC	2	10	TMReq	✓			
62	0	0	MCDData	31	0	SyncFC	✓			
62	4	2400	RTtoBC	2	11	PacketTM	✓			
62	20	14400	BCtoRT	2	10	TMConf	✓			
62	21	14550	RTtoBC	2	10	TMReq	✓			
63	0	0	MCDData	31	0	SyncFC	✓			
63	4	2400	RTtoBC	2	11	PacketTM	✓			
63	20	14400	BCtoRT	2	10	TMConf	✓			
63	21	14550	RTtoBC	2	10	TMReq	✓			

Check the following:

All TM packet transfer subframes are filled?
(bitrate = 491k bits/sec)

☐

1 PACKET / 4 SUBFRAMES
2 LOST DUE TO DOUBLE-BUFFERING.
1 LOST DUE TO RT SPEED.

Make a printout of the TM packet logfile.

☐

Make a printout of the 1553 message logfile.

☐ See annex

6.3.8 Memory load Mode

Use the same hardware configuration as Figure 6.3.2

Start the Router

Start Test client module, Commander.

Run RT software to echo received TC packets as TM packets.

Start the Bus monitor software.

Start the simulator.

Ligon to Router, and specify APIDs of required packets.

Select buslist file RT3 MemoryLoad buslist.

Run the BC.

Pause the TC display.

In Commander load and run script to send commands.

Check the bus monitor log file for the messages in the table below.

*Files saved to 6.3.8
in system
- CDMS.*

Subframe	Message slot (0 - 23)	Start time (uS)	Message type	RT	SA	Data type	Log file time (uS)	Message MS	Message NMS	
0	0	0	MCSync	31	0	None	✓ 25.118846			
0	4	2400	BCtoRT	0	11	PacketTC	✓ 121247	1C80	C003	2401µs
0	20	14400	BCtoRT	0	27	TCDesc	✓ 133248	0109	0104	14402µs
0	21	14550	RTtoBC	2	10	TMReq	✓ 133399	NORSP		14553µs
1	0	0	MCDData	31	0	SyncFC	✓			
1	4	2400	RTtoBC	1	11	PacketTM				
1	20	14400	BCtoRT	1	10	TMConf				
2	0	0	MCDData	31	0	SyncFC	✓ 25.150046			
2	4	2400	RTtoBC	2	11	PacketTM				
2	20	14400	BCtoRT	2	10	TMConf	X			
2	21	14550	RTtoBC	3	10	TMReq	✓ 152447			2401µs
2	22	14700	RTtoBC	0	27	TCConf	✓ 152598	NORSP	No RT	2552µs
3	0	0	MCDData	31	0	SyncFC	✓ 165647			X NCR5
3	4	2400	BCtoRT	0	11	PacketTC	✓ 168047	1C80	C004	2400µs
3	20	14400	BCtoRT	0	27	TCDesc	✓ 180047	0109	0105	1440µs
3	21	14550	RTtoBC	1	10	TMReq	✓ 180199			14552µs
4	0	0	MCDData	31	0	SyncFC	✓			
4	4	2400	RTtoBC	3	11	PacketTM				
4	20	14400	BCtoRT	3	10	TMConf				
5	0	0	MCDData	31	0	SyncFC	✓			
5	4	2400	RTtoBC	1	11	PacketTM				
5	20	14400	BCtoRT	1	10	TMConf				

Acceptance Test Plan

Ref: SPIRE-RAL-PRJ-
000733

Issue: 1

Date: 26/9/01

Page: 38

5	21	14550	RTtoBC	2	10	TMReq			
5	22	14700	RTtoBC	0	27	TCCConf	✓		
6	0	0	MCDData	31	0	SyncFC	✓		
6	4	2400	BCtoRT	0	11	PacketTC	✓	1080	0005
6	20	14400	BCtoRT	0	27	TCDesc	✓	0109	0106
6	21	14550	RTtoBC	3	10	TMReq	✓		
7	0	0	MCDData	31	0	SyncFC	✓		
7	4	2400	RTtoBC	2	11	PacketTM			
7	20	14400	BCtoRT	2	10	TMConf			
8	0	0	MCDData	31	0	SyncFC	✓		
8	4	2400	RTtoBC	3	11	PacketTM			
8	20	14400	BCtoRT	3	10	TMConf			
8	21	14550	RTtoBC	1	10	TMReq	✓		
8	22	14700	RTtoBC	0	27	TCCConf	✓		
9	0	0	MCDData	31	0	SyncFC	✓		
9	4	2400	BCtoRT	0	11	PacketTC	✓	1080	0006
9	20	14400	BCtoRT	0	27	TCDesc	✓	0109	0107
9	21	14550	RTtoBC	2	10	TMReq	✓		
10	0	0	MCDData	31	0	SyncFC	✓		
10	4	2400	RTtoBC	1	11	PacketTM			
10	20	14400	BCtoRT	1	10	TMConf			
11	0	0	MCDData	31	0	SyncFC	✓		
11	4	2400	RTtoBC	2	11	PacketTM			
11	20	14400	BCtoRT	2	10	TMConf			
11	21	14550	RTtoBC	3	10	TMReq	✓		
11	22	14700	RTtoBC	0	27	TCCConf	✓		
12	0	0	MCDData	31	0	SyncFC	✓		
12	4	2400	BCtoRT	0	11	PacketTC	✓	1080	0007
12	20	14400	BCtoRT	0	27	TCDesc	✓	0109	0108
12	21	14550	RTtoBC	1	10	TMReq	✓		
13	0	0	MCDData	31	0	SyncFC	✓		
13	4	2400	RTtoBC	3	11	PacketTM			
13	20	14400	BCtoRT	3	10	TMConf			
14	0	0	MCDData	31	0	SyncFC	✓		
14	4	2400	RTtoBC	1	11	PacketTM			
14	20	14400	BCtoRT	1	10	TMConf			
14	21	14550	RTtoBC	2	10	TMReq	✓		
14	22	14700	RTtoBC	0	27	TCCConf	✓		
15	0	0	MCDData	31	0	SyncFC	✓		
15	4	2400	BCtoRT	0	11	PacketTC	✓		
15	20	14400	BCtoRT	0	27	TCDesc	✓		
15	21	14550	RTtoBC	3	10	TMReq	✓		
16	0	0	MCDData	31	0	SyncFC	✓		
16	4	2400	RTtoBC	2	11	PacketTM			
16	20	14400	BCtoRT	2	10	TMConf			
17	0	0	MCDData	31	0	SyncFC	✓		
17	4	2400	RTtoBC	3	11	PacketTM			

Acceptance Test Plan

Ref: SPIRE-RAL-PRJ-
000733

Issue: 1

Date: 26/9/01

Page: 39

17	20	14400	BCtoRT	3	10	TMConf			
17	21	14550	RTtoBC	1	10	TMReq	✓		
17	22	14700	RTtoBC	0	27	TCCConf	✓		
18	0	0	MCDData	31	0	SyncFC	✓		
18	4	2400	BCtoRT	0	11	PacketTC	✓		
18	20	14400	BCtoRT	0	27	TCDesc	✓		
18	21	14550	RTtoBC	2	10	TMReq	✓		
19	0	0	MCDData	31	0	SyncFC	✓		
19	4	2400	RTtoBC	1	11	PacketTM	✓		
19	20	14400	BCtoRT	1	10	TMConf	✓		
20	0	0	MCDData	31	0	SyncFC	✓		
20	4	2400	RTtoBC	2	11	PacketTM	✓		
20	20	14400	BCtoRT	2	10	TMConf	✓		
20	21	14550	RTtoBC	3	10	TMReq	✓		
20	22	14700	RTtoBC	0	27	TCCConf	✓		
21	0	0	MCDData	31	0	SyncFC	✓		
21	4	2400	BCtoRT	0	11	PacketTC	✓		
21	20	14400	BCtoRT	0	27	TCDesc	✓		
21	21	14550	RTtoBC	1	10	TMReq	✓		
22	0	0	MCDData	31	0	SyncFC	✓		
22	4	2400	RTtoBC	3	11	PacketTM	✓		
22	20	14400	BCtoRT	3	10	TMConf	✓		
23	0	0	MCDData	31	0	SyncFC	✓		
23	4	2400	RTtoBC	1	11	PacketTM	✓		
23	20	14400	BCtoRT	1	10	TMConf	✓		
23	21	14550	RTtoBC	2	10	TMReq	✓		
23	22	14700	RTtoBC	0	27	TCCConf	✓		
24	0	0	MCDData	31	0	SyncFC	✓		
24	4	2400	BCtoRT	0	11	PacketTC	✓		
24	20	14400	BCtoRT	0	27	TCDesc	✓		
24	21	14550	RTtoBC	3	10	TMReq	✓		
25	0	0	MCDData	31	0	SyncFC	✓		
25	4	2400	RTtoBC	2	11	PacketTM	✓		
25	20	14400	BCtoRT	2	10	TMConf	✓		
26	0	0	MCDData	31	0	SyncFC	✓		
26	4	2400	RTtoBC	3	11	PacketTM	✓		
26	20	14400	BCtoRT	3	10	TMConf	✓		
26	21	14550	RTtoBC	1	10	TMReq	✓		
26	22	14700	RTtoBC	0	27	TCCConf	✓		
27	0	0	MCDData	31	0	SyncFC	✓		
27	4	2400	BCtoRT	0	11	PacketTC	✓		
27	20	14400	BCtoRT	0	27	TCDesc	✓		
27	21	14550	RTtoBC	2	10	TMReq	✓		
28	0	0	MCDData	31	0	SyncFC	✓		
28	4	2400	RTtoBC	1	11	PacketTM	✓		
28	20	14400	BCtoRT	1	10	TMConf	✓		
29	0	0	MCDData	31	0	SyncFC	✓		

29	4	2400	RTtoBC	2	11	PacketTM			
29	20	14400	BCtoRT	2	10	TMConf			
29	21	14550	RTtoBC	3	10	TMReq	✓		
29	22	14700	RTtoBC	0	27	TCCConf	✓		
30	0	0	MCDData	31	0	SyncFC	✓		
30	4	2400	BCtoRT	0	11	PacketTC	✓		
30	20	14400	BCtoRT	0	27	TCDesc	✓		
30	21	14550	RTtoBC	1	10	TMReq	✓		
31	0	0	MCDData	31	0	SyncFC	✓		
31	4	2400	RTtoBC	3	11	PacketTM			
31	20	14400	BCtoRT	3	10	TMConf			
32	0	0	MCDData	31	0	SyncFC	✓		
32	2	900	MCDData	31	8	Timecode	✓		
32	4	2400	RTtoBC	1	11	PacketTM			
32	20	14400	BCtoRT	1	10	TMConf			
32	21	14550	RTtoBC	2	10	TMReq	✓		
32	22	14700	RTtoBC	0	27	TCCConf	✓		
33	0	0	MCDData	31	0	SyncFC	✓		
33	4	2400	BCtoRT	0	11	PacketTC	✓		
33	20	14400	BCtoRT	0	27	TCDesc	✓		
33	21	14550	RTtoBC	3	10	TMReq	✓		
34	0	0	MCDData	31	0	SyncFC	✓		
34	4	2400	RTtoBC	2	11	PacketTM			
34	20	14400	BCtoRT	2	10	TMConf			
35	0	0	MCDData	31	0	SyncFC	✓		
35	4	2400	RTtoBC	3	11	PacketTM			
35	20	14400	BCtoRT	3	10	TMConf			
35	21	14550	RTtoBC	1	10	TMReq	✓		
35	22	14700	RTtoBC	0	27	TCCConf	✓		
36	0	0	MCDData	31	0	SyncFC	✓		
36	4	2400	BCtoRT	0	11	PacketTC	✓		
36	20	14400	BCtoRT	0	27	TCDesc	✓		
36	21	14550	RTtoBC	2	10	TMReq	✓		
37	0	0	MCDData	31	0	SyncFC	✓		
37	4	2400	RTtoBC	1	11	PacketTM			
37	20	14400	BCtoRT	1	10	TMConf			
38	0	0	MCDData	31	0	SyncFC	✓		
38	4	2400	RTtoBC	2	11	PacketTM			
38	20	14400	BCtoRT	2	10	TMConf			
38	21	14550	RTtoBC	3	10	TMReq	✓		
38	22	14700	RTtoBC	0	27	TCCConf	✓		
39	0	0	MCDData	31	0	SyncFC	✓		
39	4	2400	BCtoRT	0	11	PacketTC	✓		
39	20	14400	BCtoRT	0	27	TCDesc	✓		
39	21	14550	RTtoBC	1	10	TMReq	✓		
40	0	0	MCDData	31	0	SyncFC	✓		
40	4	2400	RTtoBC	3	11	PacketTM			
40	20	14400	BCtoRT	3	10	TMConf			

Acceptance Test Plan

41	0	0	MCDData	31	0	SyncFC	✓		
41	4	2400	RTtoBC	1	11	PacketTM			
41	20	14400	BCtoRT	1	10	TMConf			
41	21	14550	RTtoBC	2	10	TMReq	✓		
41	22	14700	RTtoBC	0	27	TCCConf	✓		
42	0	0	MCDData	31	0	SyncFC	✓		
42	4	2400	BCtoRT	0	11	PacketTC	✓		
42	20	14400	BCtoRT	0	27	TCDesc	✓		
42	21	14550	RTtoBC	3	10	TMReq	✓		
43	0	0	MCDData	31	0	SyncFC	✓		
43	4	2400	RTtoBC	2	11	PacketTM			
43	20	14400	BCtoRT	2	10	TMConf			
44	0	0	MCDData	31	0	SyncFC	✓		
44	4	2400	RTtoBC	3	11	PacketTM			
44	20	14400	BCtoRT	3	10	TMConf			
44	21	14550	RTtoBC	1	10	TMReq	✓		
44	22	14700	RTtoBC	0	27	TCCConf	✓		
45	0	0	MCDData	31	0	SyncFC	✓		
45	4	2400	BCtoRT	0	11	PacketTC	✓		
45	20	14400	BCtoRT	0	27	TCDesc	✓		
45	21	14550	RTtoBC	2	10	TMReq	✓		
46	0	0	MCDData	31	0	SyncFC	✓		
46	4	2400	RTtoBC	1	11	PacketTM			
46	20	14400	BCtoRT	1	10	TMConf			
47	0	0	MCDData	31	0	SyncFC	✓		
47	4	2400	RTtoBC	2	11	PacketTM			
47	20	14400	BCtoRT	2	10	TMConf	✓		
47	21	14550	RTtoBC	3	10	TMReq	✓		
47	22	14700	RTtoBC	0	27	TCCConf	✓		
48	0	0	MCDData	31	0	SyncFC	✓		
48	4	2400	BCtoRT	0	11	PacketTC	✓		
48	20	14400	BCtoRT	0	27	TCDesc	✓		
48	21	14550	RTtoBC	1	10	TMReq	✓		
49	0	0	MCDData	31	0	SyncFC	✓		
49	4	2400	RTtoBC	3	11	PacketTM			
49	20	14400	BCtoRT	3	10	TMConf			
50	0	0	MCDData	31	0	SyncFC	✓		
50	4	2400	RTtoBC	1	11	PacketTM			
50	20	14400	BCtoRT	1	10	TMConf			
50	21	14550	RTtoBC	2	10	TMReq	✓		
50	22	14700	RTtoBC	0	27	TCCConf	✓		
51	0	0	MCDData	31	0	SyncFC	✓		
51	4	2400	BCtoRT	0	11	PacketTC	✓		
51	20	14400	BCtoRT	0	27	TCDesc	✓		
51	21	14550	RTtoBC	3	10	TMReq	✓		
52	0	0	MCDData	31	0	SyncFC	✓		
52	4	2400	RTtoBC	2	11	PacketTM			

52	20	14400	BCtoRT	2	10	TMConf			
53	0	0	MCDData	31	0	SyncFC	✓		
53	4	2400	RTtoBC	3	11	PacketTM			
53	20	14400	BCtoRT	3	10	TMConf			
53	21	14550	RTtoBC	1	10	TMReq	✓		
53	22	14700	RTtoBC	0	27	TCCConf	✓		
54	0	0	MCDData	31	0	SyncFC	✓		
54	4	2400	BCtoRT	0	11	PacketTC	✓		
54	20	14400	BCtoRT	0	27	TCDesc	✓		
54	21	14550	RTtoBC	2	10	TMReq	✓		
55	0	0	MCDData	31	0	SyncFC	✓		
55	4	2400	RTtoBC	1	11	PacketTM			
55	20	14400	BCtoRT	1	10	TMConf			
56	0	0	MCDData	31	0	SyncFC	✓		
56	4	2400	RTtoBC	2	11	PacketTM			
56	20	14400	BCtoRT	2	10	TMConf			
56	21	14550	RTtoBC	3	10	TMReq	✓		
56	22	14700	RTtoBC	0	27	TCCConf	✓		
57	0	0	MCDData	31	0	SyncFC	✓		
57	4	2400	BCtoRT	0	11	PacketTC			
57	20	14400	BCtoRT	0	27	TCDesc			
57	21	14550	RTtoBC	1	10	TMReq	✓		
58	0	0	MCDData	31	0	SyncFC	✓		
58	4	2400	RTtoBC	3	11	PacketTM			
58	20	14400	BCtoRT	3	10	TMConf			
59	0	0	MCDData	31	0	SyncFC	✓		
59	4	2400	RTtoBC	1	11	PacketTM			
59	20	14400	BCtoRT	1	10	TMConf			
59	21	14550	RTtoBC	2	10	TMReq	✓		
59	22	14700	RTtoBC	0	27	TCCConf			
60	0	0	MCDData	31	0	SyncFC	✓		
60	4	2400	BCtoRT	0	11	PacketTC	✓		
60	20	14400	BCtoRT	0	27	TCDesc	✓		
60	21	14550	RTtoBC	3	10	TMReq	✓		
61	0	0	MCDData	31	0	SyncFC	✓		
61	4	2400	RTtoBC	2	11	PacketTM			
61	20	14400	BCtoRT	2	10	TMConf			
62	0	0	MCDData	31	0	SyncFC	✓		
62	4	2400	RTtoBC	3	11	PacketTM			
62	20	14400	BCtoRT	3	10	TMConf			
62	21	14550	RTtoBC	1	10	TMReq	✓		
62	22	14700	RTtoBC	0	27	TCCConf	✓		
63	0	0	MCDData	31	0	SyncFC	✓		

All TC packet transfer subframes are filled?

YES

Make a printout of the TC packet logfile. Make a printout of the 1553 message logfile.

6.4 Simulator Stand-Alone Operation

6.4.1 Front Panel

6.4.1.1 Simulator Control and Monitoring

6.4.1.1.1 Spacecraft Clock (master time)

Type an initial clock value in the control box, decimal value =

(721)


Start the bus monitor

Start the Simulator bus polling

Check master time increments in display box



Check in the bus log that master time starts at the selected offset and increments as displayed on screen.




002E FFFF
FSB2 0000.
Wrong in this case.
See NCR003

6.4.1.1.2 Buslist

Different buslists have been already used in section 6.3.


Confirm that buslists can be selected from the pull-down menu, and that the selection is displayed in the box.




6.4.1.1.3 1553 Bus Status

Start and stop the bus polling by using the Run and Master Stop buttons

Confirm that the Bus Alive indicator is flashing when the polling is active.



Select Bus B

Confirm that Bus B is indicated and the bus polling runs when started as above.
Stop the polling.

B indicated No polling.

Select Bus A


Confirm that Bus A is indicated and the bus polling runs when started as above.



A indicated No polling.

6.4.1.1.4 Router Status

Confirm that the Router Alive indicator flashes when a router connection is active, see section 6.5.




6.4.1.2 TC displays

Ensure that the Simulator is running.

Select a TC stored on the Simulator from the pull-down menu.


Confirm that the command file name is displayed.

Reselect a different TC if required.




Press the Send button

Confirm that the command header is displayed on the TC list, with the time of transmission.



Click on the TC display line.

Confirm that the complete command packet is displayed in hex format in a pop-up window.



viewed via the log file


Repeat as required.

6.4.1.3 TM displays

Start the Instrument Simulator RT. -

Start the CDMS Simulator. -


Confirm that TM packets are being received by monitoring the TM packet list.



Pause the displayed packet list (logging to file does not stop).

Click on the list.

Confirm that the complete telemetry packet is displayed in hex format in a pop-up window.

**6.4.1.4 Error displays**

Not Implemented.

For this section, use the DDC 'ACE Windows Menu' program in RT mode to generate simple RT messages containing errors.

Start the Simulator, running buslist file **RT2 Only bustlist**.

Monitor the Error display panel.

Confirm that No Response errors are being displayed from RT2, since the Simulator is polling for TMReq messages and there is no RT connected yet.

Record the Error string.

Start the 'ACE Windows menu' as RT2

Confirm that the error messages stop.

Configure the RT to respond to SA11R, generating RT status errors:

Send TCs to RT2 setting one error at a time, as shown in the table below.

Record the displayed error strings.

Status Bit set	Displayed error string
Sub System	
Terminal	

Service	
Busy	

6.4.2 Log Files

6.4.2.1 1553 Message File

The 1553 bus message file has been used extensively during section 6.3 of this document. No other tests are planned at this time.

6.4.2.2 TC Log File

A single TC log file in text format is created per Simulator session.

Open one of the previously generated TC log files with a text editor and check:

Time is written correctly?




Full length (128 word) packets written correctly?




6.4.2.3 TM Log File

Start the Simulator software again running a Burst Mode buslist and leave it running for >60 minutes.

TM packet files are changed after 30 minutes?



Logging continues after one hour by overwriting first TM file?



Check the file contents:

Time is written correctly?



Full length (512 word) packets written correctly?



6.5 Router Interface




Figure 6.5 – Setup for Router Interface Testing

6.5.1 Log on

Use the Log On dialog box to make a connection to the Router.

*IP 130.246.189.94.
Port 9876*

Check that Router Alive indicator on front panel is flashing

**6.5.2 TC Packet flow**

Send a TC from Test Client.

Check that the TC appears on the transmitted TCs list

**6.5.3 TM Packet flow**

Start the Instrument Simulator RT with Command echo facility.
Send a short TC from the Test Client

Check that the TC appears on the CDMS-Sim transmitted
TCs list



Check that a TM packet appears on the CDMS-Sim received
TM list

**6.6 TM Playback**

Playback of TM files recorded during a Simulator session is an offline activity.
Copy the TM files which may be needed later or they will be over-written.

Start the Router

Connect a test client with TC and TM facilities

Open **Playback.vi**

Connect to the Router

Select the required file from the pulldown menu.

Select the required start time.

Press Play.

TM packets received OK by Router and Test Client ?



Stop, fast forward and rewind buttons can be used to navigate through the TM file.

6.7 Remote Operation of Simulator

— Not Implemented.

Define remote command functions
test them

7. ACCEPTANCE TEST REVIEW

Inspect documentation and data package.

8. APPENDIX A – DDC TEST REPORT