

GENERAL TOLERANCE: ±1mm

WEIGHT 6.621 Kg ±10%

DIMENSION 274 X 258 X 194mm³

CENTRE OF GRAVITY (E) X=120; Y=110; Z=96(TBC)

MOMENT OF INERTIA (E) Jx=5.6X10⁻²Kgm²(TBC)

Jy=5.40X10⁻²Kgm²(TBC)

Jz=7.2X10⁻²Kgm²(TBC)

CASING MATERIAL: ANTI-CORRODAL 6082

SURFACE TREATMENT: ALODINE 1200:

alfa solar = 0.604

R-solar = 0.396

epsilon IR = 0.172

R-IR = 0.828

THERMAL CAPACITANCE: 6.621J/C (TBC)


CONTACT AREA OF BASEPLATE PLUS FEET 64428 mm²

FLATNESS OF MOUNTING AREA: 0.1mm/100mm

CONNECTORS:

- J01= DEMA-9P From DPU Prime to PDU Prime
- J02= DEMA-9P From DPU Red. to PDU Red.
- J03= DEMA-9S From DPU Prime to BU& Prime
- J04= DEMA-9S From DPU Prime to BU& Prime
- J05= DEMA-9S From DPU Red. to BU& Red.
- J06= DEMA-9S From DPU Red. to BU& Red.
- J07= DBMA-25P From DPU Prime to DCE Prime
- J10= DBMA-25P From DPU Red. to DCE Red.
- J08= DBMA-25P From DPU Prime to MCE Prime
- J11= DBMA-25P From DPU Red. to MCE Red.
- J09= DBMA-25P From DPU Prime to SCE Prime
- J12= DBMA-25P From DPU Red. to SCE Red.

UPDATED: 10/02/2002P Baldetti
 UPDATED: 29/01/2002P Baldetti
 UPDATED: 16/01/2002P Baldetti

 <p>Consiglio Nazionale delle Ricerche</p> <p>ISTITUTO NAZIONALE di SCIENZE E TECNOLOGIE FISICHE</p>		<p>data: 5/04/2001</p> <p>progetto: Baldetti</p> <p>scala: 1:1</p> <p>disegno: HERSCHEL/HSDPU</p> <p>progetto: HSDPUAVM</p> <p>numero: HER 300502</p>
-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--	-------------------------------------------------------------------------------------------------------------------------------------------------------