



Herschel

SPIRE

DPU Interface Control Document

Distribution List :

K. King		
B. Swinyard		
J. Delderfield		
J.L. Auguères		
C. Cara		
D. Pouliquen		
D. Ferrand		
G. Olofsson		
R. Orfei		
A. Di Giorgio		
A. Longoni		

Prepared by: Riccardo Cerulli-Irelli (Custodian)
Christophe Cara
Renato Orfei
Anna Di Giorgio

	IFSI CNR	Herschel SPIRE DPU Interface Control Document	Ref. : SPIRE-IFS-PRJ-000650
			Issue: 1.1 Date: 11/02/2002 Page: 2 of 42

Document Status Sheet:

Document Title: Herschel- SPIRE DPU Interface Control Document			
Issue	Revision	Date	Reason for Change
Draft 1		22/11/2000	First draft
Draft 2		5/12/2000	Low speed I/F timing
1.0		2/4/2001	
1.1		11/02/2002	Updating

Document Change Record:

Document Title: Herschel- SPIRE DPU Interface Control Document	
DOCUMENT REFERENCE NUMBER: SPIRE-IFS-PRJ-000650	
Document Issue/Revision Number: 1.1	
Section	Reason For Change
3.3	S/C connectors and pin functions
4.2	Low speed I/F protocol and timing definition
3.1	Updated box dimensions
3.2.2	Updated power consumption estimates
5	Added
6	Added
ISSUE 1.1	
	Updated the Applicable Documents table
Sect. 3.1	Box interface control drawing added
Sect. 3.2.3	Synch. Signal removed
Sect. 3.3	Removed the synch. Signals from connectors J03, J04, J05, J06
Sect. 4.2	Updated T2min to -30 Ns
Sect. 7	Updated signal name for Low Speed Clock: LCLK_DCU... And for High Speed Clock: HCLK_DCU....
Sect. 7	Low Speed Clock Shield added on pin 1 of connectors J07 to J12



Applicable documents

Document Reference	Name	Reference
AD1	Herschel/Planck Instrument Interface Document Part A	PT-IID-A-04624
AD2	Herschel/Planck Instrument Interface Document Part B Instrument "SPIRE"	PT-HIFI-02125
AD3	SPIRE Instrument Requirements Document	SPIRE-RAL-PRJ-000034
AD4	Operating Modes of the SPIRE Instrument	SPIRE-RAL-PRJ-000---
AD5	SPIRE Data ICD	SPIRE-RAL-DOC-001078

Reference documents

Document Reference	Title	Reference
RD1	ESA PS-ICD	
RD2	SPIRE DPU Subsystem Specification Document	SPIRE-IFS-PRJ-000462
RD3	DRCU Interface Control Document	Sap-SPIRE-Cca-25-00
RD4	MCU Design Description	LAM/ELE/SPI/000619



Acronyms

CDMS	Central Data Management System
CDMU	Command and Data Management System
CNR	Consiglio Nazionale delle Ricerche
CPU	Control Processing Unit
DCU	Detector Control Unit
DPU	Digital Processing Unit
DRU	Detector Readout Unit
DSP	Digital Signal Processor
EGSE	Electronic Ground Support Equipment
ESA	European Space Agency
FIRST	Far InfraRed and Submillimeter Telescope
HK	HouseKeeping
HW	HardWare
ICD	Interface Control Document
ICU	Instrument Control Unit
I/F	Interface
IFSI	Istituto di Fisica dello Spazio Interplanetario
MCU	Mechanism Control Unit
NA	Not Applicable
OBS	On-Board Software
PDU	Power Distribution Unit
S/C	Spacecraft
S/S	Subsystem
SPIRE	Spectral and Photometric Imaging REceiver
SPU	Signal Processing Unit
SR	Software Requirement
SSD	Software Specification Document
SVVP	Software Verification and Validation Plan
SW	SoftWare
TBC	To Be Confirmed
TBD	To Be Defined
TBW	To Be Written
TC	Telecommand
TM	Telemetry



Table of contents

APPLICABLE DOCUMENTS	3
REFERENCE DOCUMENTS	3
1 SCOPE OF THE DOCUMENT	7
2 DESCRIPTION OF DPU SUBSYSTEM	7
2.1 Overall DPU block diagram.....	7
2.2 Redundancy concept.....	9
3 DPU - SPACECRAFT INTERFACES	9
3.1 Mechanical I/F	9
3.2 Electrical I/F.....	11
3.2.1 Telemetry and Telecommand.....	11
3.2.2 Power	12
3.2.3 DC/DC Synchronisation	12
3.3 Connectors and pin functions	13
3.3.1 DPU to PDU Prime Power Bus	13
3.3.2 DPU-Prime to CDMS-Prime 1553B Bus A.....	13
3.3.3 DPU-Prime to CDMS- Prime 1553B Bus B.....	14
3.3.4 DPU to PDU Redundant Power Bus.....	14
3.3.5 DPU-Redundant to CDMS-Redundant Bus A.....	15
3.3.6 DPU-Redundant to CDMS-Redundant Bus B.....	15
4 DPU - SUBSYSTEMS INTERFACES	16
4.1 General Information.....	16
4.2 Low Speed Interface	17
4.3 High Speed Interface.....	21
4.4 DRU/ICU data.....	22
4.5 Data acquisition Timing.....	23
5 LOW SPEED DATA I/F PROTOCOL.....	24
5.1 Command Word.....	24
5.2 Response Word	25
5.3 Command list	26
5.3.1 DCU specific command list	26
5.3.2 MCU specific command list	28
5.3.3 SCU specific command list.....	29
5.4 Constraints on the command sequencing.....	30
5.5 Typical commanding scenario	30
6 HIGH SPEED DATA I/F PROTOCOL	31
6.1 General Information.....	31
6.2 Overall Interface Diagram	31
6.3 Word definition.....	32
6.4 Frame Definition.....	32
6.4.1 Header	32



6.4.2	Frame time	33
6.4.3	Length	33
6.4.4	Data structure	33
6.4.4.1	DCU Frames Definition.....	33
6.4.4.2	MCU Frame Definition.....	35
6.4.4.3	SCU Frame Definition.....	35
6.4.5	Check word	36
6.5	Test pattern.....	36
7	CONNECTORS AND PIN FUNCTIONS	37
7.1	DPU to DCU - Prime	37
7.2	DPU to MCU - Prime	38
7.3	DPU to SCU - Prime	39
7.4	DPU to DCU - Redundant	40
7.5	DPU to MCU - Redundant.....	41
7.6	DPU to SCU - Redundant	42

1 Scope of the document

This document describes the interfaces of the SPIRE Digital Processing Unit with the Herschel spacecraft (S/C), the Instrument Control Unit (ICU) and the Detector Readout Unit (DRU). The following block diagram shows the simplified overall layout of SPIRE and the interfaces described in this document.




Figure 1-1 SPIRE DPU interfaces schematic view

2 Description of DPU subsystem

The DPU is based on a 20 MHz clock TEMIC TSC21020 Digital Signal Processing (DSP) developed by Analogue Devices and implemented for flight use by TEMIC.

The DSP implements Harvard architecture, i.e. the data bus (32 bit) and the programme bus (48 bit) are completely separated, so increasing the execution speed.

The program area is implemented with PROMs, EEPROMs and RAM. The PROM stores the initial boot loader and emergency recovery modules. The instrument program is stored in EEPROMs and copied in RAM at run time for execution. Program area may be used as data memory.

The DPU includes a free running (about 131072 Hz) DC/DC converter to supply the internal circuitry.

2.1 Overall DPU block diagram

The following diagram shows the main DPU blocks, the electrical interfaces and the memory dimensions.




Figure 2-1 DPU CPU memory organisation

2.2 Redundancy concept

The top level DPU redundancy concept is shown in the following diagram:




Figure 2-2 DPU redundancy concept

The DPU box contains two complete units in cold redundancy states. The S/C prime/redundant 28V power bus controls the switching between the two units.

As a consequence, the DPU interfaces with both S/C and S/S are doubled.

3 DPU - Spacecraft interfaces

3.1 Mechanical I/F

The prime and redundant DPUs are included in the same mechanical box whose dimensions are:
 274x258x194 mm including the feet
 240x258x194 mm without the feet

The box interfaces mechanically with the S/C with 6 feet.


In the following figure the mechanical interface control drawing is shown.



Herschel SPIRE

DPU Interface Control Document

Ref. : SPIRE-IFS-PRJ-000650
Issue: 1.1
Date: 11/02/2002
Page: 10 of 42



GENERAL TOLERANCE $\pm 1\text{mm}$
 MASS 6,621 Kg $\pm 10\%$
 DIMENSIONS 274 X 258 X 104mmh
 CENTRE OF GRAVITY (E) X=120; Y=110; Z=96(TBC)
 MOMENT OF INERTIA (E) $J_x=5.6X10^{-2} \text{ Kg m}^2$ (TBC)
 $J_y=5.40X10^{-2} \text{ Kg m}^2$ (TBC)
 $J_z=7.2X10^{-2} \text{ Kg m}^2$ (TBC)
 CASING MATERIAL: ANTICORODAL 6062
 SURFACE TREATMENT: ALODINE 1200:
 alfa solar = 0,604
 R-solar = 0,396
 epsilon IR = 0,172
 R-IR = 0,828
 THERMAL CAPACITANCE: 6.000J/°C (TBC)
 CONTACT AREA OF BASEPLATE PLUS FEET 64428mm²
 FLATNESS OF MOUNTING AREA: 0.1mm/100mm

CONNECTORS:
 J01- DEMA-0P From DPU Prime to PDU Prime
 J02- DEMA-0P From DPU Red. to PDU Red.
 J03- DEMA-0S From DPU Prime to Bus A
 J04- DEMA-0S From DPU Prime to Bus B
 J05- DEMA-0S From DPU Red. to Bus A
 J06- DEMA-0S From DPU Red. to Bus B
 J07- DBMA-25P From DPU Prime to DCU Prime
 J08- DBMA-25P From DPU Prime to MCU Prime, part of FCU Prime
 J09- DBMA-25P From DPU Prime to SCU Prime, part of FCU Prime
 J10- DBMA-25P From DPU Red. to DCU Red.
 J11- DBMA-25P From DPU Red. to MCU Red., part of FCU Red.
 J12- DBMA-25P From DPU Red. to SCU Red., part of FCU Red.

UPDATED: 29/01/2002 P. Baldetti
 UPDATED: 16/01/2002 P. Baldetti

<p>Consiglio Nazionale delle Ricerche ISTITUTO di FISICA dello SPAZIO INTERPLANETARIO Via dei Fori Imperiali n.102 tel. 06/4993 fax 06/49934383</p>	data: 5/04/2001 <input checked="" type="checkbox"/>	firma: Baldetti nome: Baldetti cognome: Baldetti	data: _____ <input type="checkbox"/>
	scala: _____ titolo: _____ progetto: HERSCHEL- HSDPU data: _____ titolo: HSDPU AVM numero: HER 5023/02		



The total weight allocated to the DPU is 7 Kg.

3.2 Electrical I/F

3.2.1 Telemetry and Telecommand

The DPU interfaces with the S/C TM and TC subsystems (CDMS) with a redundant couple of wires implementing the MIL-STD 1553 B in the long stub configuration (transformers coupling). Each DPU section (prime and redundant) is connected to both prime and redundant bus lines, as shown in Fig 3.2




Figure 3-1 Detailed DPU Spacecraft interface

The nominal bit rate is 100 Kbps with a burst mode of 300 Kbps (TBC).



3.2.2 Power

The DPU gets the power through the 28 V wire redundant power lines, separated for DPU DC/DC converter prime and DC/DC converter redundant. A S/C command decides which DPU is operated with the other in cold stand-by mode.

The total nominal power on the main 28V line is:

$$24 \pm 6 \text{ W (TBC)}$$

3.2.3 DC/DC Synchronisation

Each DPU DC/DC converter is free running at 131072 Hz + - 10% via an internally generated synchronisation signal.



3.3 Connectors and pin functions

From the prime DPU there will be 3 Cannon DEMA 9 ways connectors respectively to prime CDMS "A", prime CDMS "B" and prime PDU. The same will apply to the redundant DPU so that a total of 6 connectors and 6 cables will be used to electrically connect the DPU to the spacecraft.

3.3.1 DPU to PDU Prime Power Bus

Unit DPU
Connector ID J01
Connector type DEMA9P
Connector name TO PDU_P

Pin #	Signal Name	EMC Class	Wire	Connected to		
				Unit	Connector	Pin
1						
2	28_V_P		AWG26	PDU P		
3						
4	PWR_RET_P		AWG26	PDU P		
5						
6						
7	28_V_P		AWG26	PDU P		
8						
9	PWR_RET_P		AWG26	PDU P		

3.3.2 DPU-Prime to CDMS-Prime 1553B Bus A

Unit DPU
Connector ID J03
Connector type DEMA9S
Connector name FM P_CMDS_P

Pin #	Signal Name	EMC Class	Wire	Connected to		
				Unit	Connector	Pin
1						
2	Bus + A		AWG26	CDMS P		
3						
4						
5						
6	Bus - A		AWG26	CDMS P		
7						
8						
9						



IFSI
CNR

Herschel SPIRE

DPU Interface Control Document

Ref. : SPIRE-IFS-PRJ-000650

Issue: 1.1

Date: 11/02/2002

Page: 14 of 42

3.3.3 DPU-Prime to CDMS- Prime 1553B Bus B

Unit DPU
 Connector ID J04
 Connector type DEMA9S
 Connector name FM R_CMDS_P

Pin #	Signal Name	EMC Class	Wire	Connected to		
				Unit	Connector	Pin
1						
2	Bus + B		AWG26	CDMS P		
3						
4						
5						
6	Bus - B		AWG26	CDMS P		
7						
8						
9						

3.3.4 DPU to PDU Redundant Power Bus

Unit DPU
 Connector ID J02
 Connector type DEMA9P
 Connector name TO PDU_R

Pin #	Signal Name	EMC Class	Wire	Connected to		
				Unit	Connector	Pin
1						
2	28_V_R		AWG26	PDU R		
3						
4	PWR_RET_R		AWG26	PDU R		
5						
6						
7	28_V_R		AWG26	PDU R		
8						
9	PWR_RET_R		AWG26	PDU R		



IFSI
CNR

Herschel SPIRE

DPU Interface Control Document

Ref. : SPIRE-IFS-PRJ-000650

Issue: 1.1

Date: 11/02/2002

Page: 15 of 42

3.3.5 DPU-Redundant to CDMS-Redundant Bus A

Unit DPU
 Connector ID J05
 Connector type DEMA9S
 Connector name FM P_CMDS_R

Pin #	Signal Name	EMC Class	Wire	Connected to		
				Unit	Connector	Pin
1						
2	Bus + A		AWG26	CDMS R		
3						
4						
5						
6	Bus - A		AWG26	CDMS R		
7						
8						
9						

3.3.6 DPU-Redundant to CDMS-Redundant Bus B

Unit DPU
 Connector ID J06
 Connector type DEMA9S
 Connector name FM R_CMDS_R

Pin #	Signal Name	EMC Class	Wire	Connected to		
				Unit	Connector	Pin
1						
2	Bus + B		AWG26	CDMS R		
3						
4						
5						
6	Bus - B		AWG26	CDMS R		
7						
8						
9						

4 DPU - Subsystems interfaces

4.1 General Information

The DPU interacts with the subsystems via dedicated low speed bidirectional and high speed mono-directional serial interfaces.

The two physical subsystem units are logically divided into three independent units each connected to the DPU with one high speed and one low speed interface.

Both the DPU and the S/S (interfaces) are fully redundant, so that the total number of serial interfaces is 12.




Figure 4-1 DPU - Subsystems Interfaces schematic view

All interfaces adopt the balanced line drivers and receivers as shown in figure 4-2.




Figure 4-2 Balanced line drivers and receivers

4.2 Low Speed Interface

The low speed bidirectional I/F is organized as a bus with the DPU acting as controller so that all data transactions with the subsystem are initiated by DPU.

The low speed interface protocol is shown in figure 4-3.




Figure 4-3 Low speed interface protocol

With reference to the figure, the tolerances on the indicated time parameters are:



Parameter	Min. Value (TBC)	Max. Value (TBC)	Unit
T1	3.17	3.23	μs
T2	-30 nS	0.7	μs
T3	0.05	1.2	μs
T4	1.53	1.66	μs

Commands sent by the DPU via the TX lines are always received by all the subsystems, the address field of the command word selecting the relevant unit. One address is reserved as a broadcast command. The subsystem addressing is made according to the following table:

A0	A1	Subsystem
0	0	DCU
0	1	MCU
1	0	SCU
1	1	Broadcast

The DPU can send both commands and/or HK requests as signalled by the second start bit of the command word. When requested, the subsystems will send responses via the RX line.

A command is made of 2 start bits, 2 address bits, 28 data bits and 1 stop bit.

A HK request is issued by setting the second start bit according to the following table:

Start0	Start1	HK
1	1	No
1	0	Yes

The HK response will have the same form of the requesting command, the address field indicating the originating subsystem.

The command word data field can be subdivided in every way, the baseline is shown in the following table:

From	To	Description
D0	D7	Command identifier
D8	D27	Command parameters

As the selection of the input RX channel is done by the sub-unit address field of the last TX command sent, no command can be sent to a different sub-unit until the last HK RX corresponding to the last command sent is received. Figure 4-4 shows the transmission reception sequence.




Figure 4-4 Low speed interface – transmission reception protocol

In order to avoid system lock a TBD us timeout **TO** is defined. In any case, a new HK request cancels the previous request whether already sent or not.

The following table shows the timing requirements with and without HK request.

Parameter	Min value [us] TBC	Max value [us] TBC	Description
TO	TBD	TBD	Time-Out
t1	101	104	Command word length
t2	6.4	500 TBC [RD3]	HK response time
t3	10	NA	Time to next command
T	10	NA	No HK request
T	Minimum value between (t1+t2+t3) and TO		With HK request



The DPU side of the low speed I/F is shown in figure 4-5. The DPU originated clock line has a fixed frequency of 312.5 kHz. The clock signal generated by DPU is distributed to all subsystems and can be used for synchronisation purposes, after a dedicated broadcast command is issued (see section 4.4).




Figure 4-5 Detailed bi-directional low speed interface

The detailed subsystems commands lists are reported in sections 5 and 6.



4.3 High Speed Interface

The high speed data link (science data link) is made by three monodirectional fast synchronous serial input interfaces, each of which with 8 KW 16 bits FIFO. The FIFOs half full signal generates an interrupt on the DSP. Three independent interfaces are required since simultaneous data transfer can occur.

The high speed I/F will transfer data from ICU/DRU sub-units to DPU as 16 bit words using a clock up to 2.5 MHz (baseline 1 MHz TBC). Being the interface unidirectional, all signals are generated by ICU/DRU.

The DPU side of the 3 high speed I/F is shown in the following figure:




Figure 4-6 Detailed monodirectional high speed interface

The clock, gate and data signals coming from the subsystems are as in figure 4-7.




Figure 4-7 High speed interface protocol

Signal lines are defined as in figure and the clock frequency is 1 MHz (TBC). The tolerances on the indicated time parameters are:

Parameter	Min. Value (TBC)	Max. Value (TBC)	Unit
T1	990	1010	ns
T2	0	100	ns
T3	0	300	ns
T4	450	550	ns

4.4 DRU/ICU data

The SPIRE telemetry parameters can be split into two types:

1. **Science Parameters**: detector data plus those data required to process the detector data.
2. **Housekeeping parameters**: data required to monitor the configuration and health and safety status of the instrument.

Housekeeping parameters are provided on the *Low Speed RX* data line from DRU and ICU to the DPU in response to a HK request . Each request will return one or more data values within a 32 bit word. 28 bits are available for data.

The DPU will request the housekeeping data from the DRU/ICU subsystems at regular intervals (1sec TBC) and place them, along with the DPU parameters into a single housekeeping TM packet. There will be a single instance of each housekeeping parameter in a housekeeping TM packet. In the case of a value being invalid, the OBS will set a flag in the Housekeeping indicating this.

 <p>IFSI CNR</p>	<p>Herschel SPIRE</p> <p>DPU Interface Control Document</p>	<p>Ref. : SPIRE-IFS-PRJ-000650 Issue: 1.1 Date: 11/02/2002 Page: 23 of 42</p>
---	--	--

Science parameters are provided on the *High Speed data lines* from DRU and ICU to the DPU following a request for data issued on the Low Speed data line. The science information is provided in the form of frames containing a fixed set of science parameters.

The number of frame types per subsystems is:

- DCU: 10 (test pattern, all photometric arrays, both spectrometer arrays, 5* one detector array, 2 others TBD)
- SCU: 2 (test pattern, all data)
- MCU: 2 (test pattern, delta time + 2 other channels (selectable))

The number of acquisition rates available will be limited to 3 for the MCU and 4 for the DCU and SCU

Each frame is composed of :

- a header word (16bits);
- a frame time (TBD bits – see later)
- a number of data words;
- a check word (16bits)

Both word and frame definitions are subsystem dependent and will be described in sections 5 and 6 (TBW).

The DPU will copy the science data frames into a telemetry packet (including the check word). It will also check the header and the check word with the data in the frame and, if check fails, it will take action to re-synchronize with the data stream (TBC).

4.5 Data acquisition Timing

Each DRU/ICU subsystem maintains its own counter driven by the 312.5 kHz clock provided by the DPU on the low speed interface. Thus the counters remain in synchronization at all times and can provide the time to an accuracy of ~3 microseconds.

The counters are reset to 0 by a command from the DPU, which is broadcast to all three subsystems at the same time. Thus the counters should be identical (provided the reset pulse is generated from the received command in the three subsystems in a time that is identical, within <~3 microseconds).

The time taken to reset the counters after the DPU issues the command is not critical, as this is used only to provide a link to the absolute time maintained by the DPU (received from the S/C). The accuracy of this time value is 1000 microsec.

The counters are used to mark each frame with the elapsed time since the last reset command.

Because the frames from the FTS are generated asynchronously with the detector data frames, it is not possible to include data from different subsystems into a single TM packet. The DPU will therefore generate separately:

1. DCU science packets;
2. MCU science packets;
3. SCU science packets;

4. DPU science packets (TBC)

Each TM packet will contain, in addition to the standard header information and the data frames the absolute DPU time of the last counter reset command.

5 Low Speed Data I/F Protocol

5.1 Command Word

At any time after completion of a previous command/response exchange the DPU can send command words to the DRCU subsystems on the CMD line.

The 32-bit command word is divided into 5 fields as defined bellow:

- a 2-bit sync pattern : see table 5.1-a for details
- a 2-bit sub-unit address : see table 5.1-b for details
- a 8-bit command or command + parameter address : see table 5.1-c for details
- a 20-bit parameter when applicable*

*: filled with zero if the command does not require any parameter.

These 4 fields are concatenated as follow to form the 32-bits word:



Figure 5.1-a - Command Word Field Structure

- SYN1 - SYN0 : sync. pattern
SSA1 - SSA0 : subsystem address
CID7 to CID0 : command identifier
PAR19 to PAR0 : command parameter*
*: filled with zero if no used

Note : • MSB is transmitted first
• SYN1 = MSB
• PAR0 = LSB

SYN1	SYN0	Response
1	0	Yes
1	1	No

Table 5.1-b - Sync Pattern definition

SSA1	SSA0	Subsystem Name
0	0	DCU
0	1	MCU
1	0	SCU
1	1	Broadcast Command

Table 5.1-c - Subsystem address allocation

CID7	CID6 to CID0
0	command code (0 of 127)
1	parameter address (0 of 127)

Table 5.1-d - Command Identifier Structure

Note: the subsystems do not include any command buffering. If a subsystem is enabled to any reason to execute a command it will reply with a negative acknowledge and the last command is definitively lost.

5.2 Response Word

The response line (HK) enables command verification and DRCU sub-system housekeeping parameters reading by the DPU.

When a “set_parameter” command is received the subsystem responds to the DPU by transferring a command acknowledge word (positive or negative) on the response line. The positive acknowledgement is required for further command transfer after specific critical commands. When a “get_parameter” command is received the subsystem responds to the DPU by transferring the requested housekeeping parameter(s). (Housekeeping parameter polling is running typically at 1Hz).

The sub-system shall respond (leading bit of the response word) within a maximum delay of tbd clock periods (t2– see §4.2). The DPU S/W shall include a time-out in order to recover from a lack of response and then report the anomaly.

The 32-bit command response is divided into 3 fields, which are:

- a 2-bit sync pattern (SYN0 & SYN1),
- a 8-bit command or parameter address echo (CID7 to CID0),
- a 20-bit parameter (PAR19 to PAR0) or acknowledge code.

These 3 fields are concatenated as follow to form the 32-bits word:

SYN1-SYN0	00	CID7 to CID0	PAR19 to PAR0
-----------	----	--------------	---------------

If the subsystem address corresponds to the broadcast address the subsystems do not generate any response word to avoid collision at the DPU end.

A “negative” acknowledge (specific parameter field) may result from the following reasons:

- DRCU or DRCU subsystem is off
- A transmission error occurred: receiver does not recognise command identifier
 - A command is not allowed in a specific subsystem status (e.g. modification of FTS scan length when mechanism is scanning)



5.3 Command list

5.3.1 DCU specific command list

Command Name	Command Code	Arguments	Range List	Command verification
Set_photo_bias_freq		Channel id. Frequency divider	NA 64 to 511	?
Set_spectro_bias_freq		Channel id. Frequency divider	NA 64 to 511	?
Set_photo_bias_ampl		Channel id. Sine amplitude	0 to 3 0 to 255	?
Set_spectro_bias_ampl		Channel id. Sine amplitude	0 to 1 0 to 255	?
Set_photo_JFET_Vss		Channel id. Vss voltage	0 to 11 0 to 255	?
Set_spectro_JFET_Vss		Channel id. Vss voltage	0 to 2 0 to 255	?
Set_photo_JFET_pwr		On/Off word	See note x	?
Set_spectro_JFET_pwr		On/Off word	See note xx	?
Set_photo_heater_pwr		Channel id. On/off	NA	
Set_spectro_heater_pwr		Channel id. On/off	NA	
Set_photo_offset		Channel id. Offset value	0 to 287 0 to 7	
Set_spectro_offset		Channel id. Offset value	0 to 71 0 to 7	
Set_data_mode		Mode: 0 to 9	Test Pattern Photo. Offset Spectro. Offset Photo. Bolo. Spectro. Bolo. Photo. PLW Photo. PMW Photo. PSW Spectro. SLW Spectro. SSW	?
Set_multiple_frames		Nber of frames Frame Rate Divider	1 to 255 0 for continuous 1 to 255	
Command Name	Command Code	Arguments	Range List	Command verification



IFSI
CNR

Herschel SPIRE

DPU Interface Control Document

Ref. : SPIRE-IFS-PRJ-000650

Issue: 1.1

Date: 11/02/2002

Page: 27 of 42

Start_multiple_frames		Start / Stop		
Get_single_frame		NA		
Get_hk_channel		Channel id.	See AD2	
Reset_time_counter		NA	Broadcast cmd	

Note x: on/off word bit allocation is defined as follows: TBW

Note xx: on/off word bit allocation is defined as follows: TBW



5.3.2 MCU specific command list

Command Name	Command Code	Arguments	Comment	Command verification
Set_scan_length		Scan length	B0 to B21	?
Set_scan_speed		Scan Speed	B0 to B21 0: position mode	?
Set_SMEC_mode		Mode	Open loop Closed loop w encode Closed loop w back EMF	?
Start_SMEC		Start / Stop	Start: B0 = 1 Stop: BO = 0	?
Set_SMEC_position		Position from home	?	
Set_data_mode		Mode Data Selection	Jiggle / SMEC	?
Get_hk_channel		Channel	Scan length Scan speed Scan mean period SMEC Mode SMEC Position SMEC temp. MAC temp. ...	
Reset_time_counter		NA	Broadcast cmd	

5.3.3 SCU specific command list

Command Name	Command Code	Arguments	Comment	Command verification
Set_calibrator_current		Channel id. Current	Photometer Spectro. Flood Spectro. Point 0 to 255	
Set_heater_current		Channel id. Current	SP HS1 HS2 FPU 0 to 255	
Set_therm_on/off		On/Off word	See note xxx	
Set_S/S_pwr_on/off		On/Off word	See note xxxx	
Set_multiple_frames		Nber of frames Frame Rate	1 to 256 0 for continuous 1 to 256	
Start_multiple_frames		Start / Stop		
Get_single_frame		NA		
Get_housekeeping		Channel id.	See AD2	
Reset_time_counter		NA	Broadcast cmd	

Note xxx: on/off word bit allocation is defined as follows:

Bit weigh	Thermometer channel

Note xxxx: on/off word bit allocation is defined as follows:

Bit weigh	S/S
7 (MSB)	DCU_LIA_P
6	DCU_LIA_S
5	DCU_DAQ
4	DCU_BIAS_P
3	DCU_BIAS_S
2	MCU_MAC
1	MCU_SMEC
0 (LSB)	MCU_BSM



5.4 Constraints on the command sequencing

The purpose of this chapter is to give constraints related to the command sequencing when applicable. Depending of the status of a sub-system following a low-level command, the next command may have to be delayed in order to give chance to the subsystem to execute the command. A typical example corresponds to a cryo-cooler recycling after sending the SP pump heating command. In that case the DPU shall wait before sending the next command the necessarily time to the sorption pump to reach 40 K.

TBW

5.5 Typical commanding scenario

This scenario is given as an example only.

Action	DCU Status	Data Transfer
DCU power-on	DCU default	T3 @ 16 Hz
Set_Bias_amplitude	Configuration	
Set_Bias_Frequency	“	
...		
...		
Start_multiple_frame(stop)	DCU configured	No data
Set_data_mode(photometer)		
Set_multiple_frames(4,16Hz)		
Start_multiple_frame(start)	“Observing”	T4 @ 16 Hz
...		

Asynchronously with those commands, the DPU will send regularly requests (typically @ 1 Hz - 1 per 1 or 2 parameters) for housekeeping parameters. It will also send the “Set_heater_current” command at the same rate order to achieve FPU temperature stabilisation.



6 High Speed Data I/F Protocol

6.1 General Information

The Data Interface is dedicated to data transfer from subsystem to DPU. Three independent “Data Interface” are required allowing simultaneous DRCU data transfer.

This interface is unidirectional: data are transferred from the DRCU sub-units to the DPU acquisition electronics. Fixed data packets are defined according to sub-unit operating mode. This data packet contents both scientific data (i.e. bolometer signal) and/or housekeeping parameters.

6.2 Overall Interface Diagram

The Command Interface diagram is given in figure 6.2. Prime and Redundant interfaces are shown.




Figure 6.2-a



6.3 Word definition

Word definition is subsystem dependent. Data are currently 16-bit encoded and correspond to bolometer signal, mechanisms motion parameters, instrument temperature and all other housekeeping channels.

In order to deal with the latch-up effect of the analogue to digital converters, which cause the generation of wrong data until the converter recovers full performances, a specific “invalid” data identifier is defined. This avoids the DRCU to transfer unpredictable packet length following a cosmic ray impact on the converter and later on-ground misanalysis.

These data words are defined as follow:




Figure 6.3-a - Data Word Definition

DAT15 to DAT0: data

Note: • MSB (DAT15) is transmitted first

6.4 Frame Definition

Data frame length and structure are defined regarding the DRCU sub-unit and its mode of operation. The sub-systems data structures are encapsulated into a common frame structure as described bellow.

The frame is composed of:

- a header word
- a frame time
- a number of data words
- a data structure
- a check word

6.4.1 Header

The “header” field is a 16-bit word placed at the head of the frame. Along with the “length” field and the check word it allows data consistency checking. In case the check fails the DPU takes action to re-synchronize with the data stream. The “header” is itself composed of the following elementary fields:

- header pattern: 1 byte / AA hexadecimal
- ADC latch-up flags: 6 bits /
- 2 spare bits

The purpose of the ADC latch-up flag word is to keep track of an analog to digital converter latch-up event, which affects the integrity of the digitized data. When a flag or more is set the related

 IFSI CNR	Herschel SPIRE DPU Interface Control Document	Ref. : SPIRE-IFS-PRJ-000650 Issue: 1.1 Date: 11/02/2002 Page: 33 of 42
---	---	---

data of the current frame have to be discarded during on-ground data processing. The number significant of flags depends on the data interface mode: 6 corresponding to the “Photo. Full Array” mode. See table above for details

DCU Configuration	FST	# of flags
Photo. Array Subset	T1	1
Spectro. Array Subset	T1	1
Photo. Full Array	T2	6
Spectro. Full Array	T2	2
Test Pattern	T3	0
Photo. Offset table	T2	0
Spectro offset table	T2	0

6.4.2 Frame time

The “frame time” field follows the “header”. It is a 32-bit word filled with the contents of the subsystem “time tag” counters. In order to keep data frame synchronization for the 3 subsystems this counter is driving by a single clock signal and reset by a broadcast command. The clock is derived from the CLK line of the Command interface and the resolution is then 3.2 μ s. The full range of the counter is then above 13740 s (229 min); this means the DPU have to sent the reset command at least every 229 min in order to keep synchronization between the 3 DRCU sub-systems.

The subsystem time counter shall be effectively reset within 10 (TBC) μ s from the command reception and with a maximum skew between subsystems of 3 μ s.


6.4.3 Length

The “length” field (16 bits) follows the “frame time” field. It indicates the number of 16-bit words of the frame (including all the fields). Along with the “header” and “check word” fields this field allows frame consistency checking by the receiver unit.

6.4.4 Data structure

6.4.4.1 DCU Frames Definition

The four frame structures of the DCU are defined as follows:



The following cross table shows the corresponding Frame Structure Type for each DCU configuration status:

DCU Configuration	FST	Length
Photo. Array Subset	T1	See Note
Spectro. Array Subset	T1	See Note
Photo. Full Array	T2	301
Spectro. Full Array	T2	69
Test Pattern	T3	301
Photo. Offset table	T2	301
Spectro. Offset table	T2	69

Remind: the DCU data interface configuration is configured by means of the “Set_Data_Mode” command.

Note: Frame length depends on the detector selected subset (Band 1 2 or 3 for photometer and band 1 or 2 for spectrometer).


For the T2 frame length it assumed:

- the photometer is composed of 288 bolometers
- the spectrometer is composed of 56 bolometers
- along with the imaging bolometers we transfer 8 thermometry bolometers



6.4.4.2 MCU Frame Definition

The two frame structures of the MCU are defined as follows:




The following cross table shows the corresponding Frame Structure Type for each MCU configuration status:

Configuration Status	FST	Length
Nominal	T4	6
Spectrometer	T5	6

6.4.4.3 SCU Frame Definition

The two frame structures of the SCU are defined as follows:



The following cross table shows the corresponding Frame Structure Type for each SCU configuration status:

Configuration Status	FST	Length
Nominal	T6	
Test Pattern	T7	

 IFSI CNR	Herschel SPIRE DPU Interface Control Document	Ref. : SPIRE-IFS-PRJ-000650 Issue: 1.1 Date: 11/02/2002 Page: 36 of 42
---	---	---

6.4.5 Check word

The “check” word ends the data frame. Along with the “header” and “length” field it allows frame consistency checking.

6.5 Test pattern

The purpose of this mode is to generate variable and predictable digital data for test and verification activities. Instead of transmitting a fixed pattern it implements a pseudo random generator.



7 Connectors and pin functions

From the prime DPU there will be 3 Cannon DBMA25P connectors respectively to DCU, MCU and SCU, carrying both low speed and high speed interfaces signals.

The same will apply for the redounded DPU so that a total of 6 connectors and a total of 6 cables will be used to interconnect the subsystems. The connectors and cables pin function are defined in the following tables.

7.1 DPU to DCU - Prime

Unit DPU
Connector ID J07
Connector type DBMA25P
Connector name TO DCU_P

Pin #	Signal Name	EMC Class	Wire	Connected to		
				Unit	Connector	Pin
1	LCLK_DCU_SHD					
2	LCLK_DCU_P+		AWG26	DRU		
3	TX_DCU_P+		AWG26	DRU		
4	RX_DCU_P+		AWG26	DRU		
5	RX_SHD					
6						
7						
8	HCLK_DCU_P+		AWG26	DRU		
9	HCLK_SHD					
10	DAT_DCU_P+		AWG26	DRU		
11	GAT_DCU_P+		AWG26	DRU		
12	GAT_SHD					
13						
14						
15	LCLK_DCU_P-		AWG26	DRU		
16	TX_DCU_P-		AWG26	DRU		
17	RX_DCU_P-		AWG26	DRU		
18						
19						
20						
21	HCLK_DCU_P-		AWG26	DRU		
22	DAT_DCU_P-		AWG26	DRU		
23	DAT_SHD					
24	GAT_DCU_P-		AWG26	DRU		
25						



IFSI
CNR

Herschel SPIRE

DPU Interface Control Document

Ref. : SPIRE-IFS-PRJ-000650

Issue: 1.1

Date: 11/02/2002

Page: 38 of 42

7.2 DPU to MCU - Prime

Unit DPU
 Connector ID J08
 Connector type DBMA25P
 Connector name TO MCU_P

Pin #	Signal Name	EMC Class	Wire	Connected to		
				Unit	Connector	Pin
1	LCLK_MCU_SHD					
2	LCLK_MCU_P+		AWG26	ICU	J08	
3	TX_MCU_P+		AWG26	ICU	J08	
4	RX_MCU_P+		AWG26	ICU	J08	
5	RX_SHD					
6						
7						
8	HCLK_MCU_P+		AWG26	ICU	J08	
9	HCLK_SHD					
10	DAT_MCU_P+		AWG26	ICU	J08	
11	GAT_MCU_P+		AWG26	ICU	J08	
12	GAT_SHD					
13						
14						
15	LCLK_MCU_P-		AWG26	ICU	J08	
16	TX_MCU_P-		AWG26	ICU	J08	
17	RX_MCU_P-		AWG26	ICU	J08	
18						
19						
20						
21	HCLK_MCU_P-		AWG26	ICU	J08	
22	DAT_MCU_P-		AWG26	ICU	J08	
23	DAT_SHD					
24	GAT_MCU_P-		AWG26	ICU	J08	
25						



IFSI
CNR

Herschel SPIRE

DPU Interface Control Document

Ref. : SPIRE-IFS-PRJ-000650

Issue: 1.1

Date: 11/02/2002

Page: 39 of 42

7.3 DPU to SCU - Prime

Unit DPU
 Connector ID J09
 Connector type DBMA25P
 Connector name TO SCU_P

Pin #	Signal Name	EMC Class	Wire	Connected to		
				Unit	Connector	Pin
1	LCLK_SCU_SHD					
2	LCLK_SCU_P+		AWG26	ICU		
3	TX_SCU_P+		AWG26	ICU		
4	RX_SCU_P+		AWG26	ICU		
5	RX_SHD					
6						
7						
8	HCLK_SCU_P+		AWG26	ICU		
9	HCLK_SHD					
10	DAT_SCU_P+		AWG26	ICU		
11	GAT_SCU_P+		AWG26	ICU		
12	GAT_SHD					
13						
14						
15	LCLK_SCU_P-		AWG26	ICU		
16	TX_SCU_P-		AWG26	ICU		
17	RX_SCU_P-		AWG26	ICU		
18						
19						
20						
21	HCLK_SCU_P-		AWG26	ICU		
22	DAT_SCU_P-		AWG26	ICU		
23	DAT_SHD					
24	GAT_SCU_P-		AWG26	ICU		
25						



IFSI
CNR

Herschel SPIRE

DPU Interface Control Document

Ref. : SPIRE-IFS-PRJ-000650

Issue: 1.1

Date: 11/02/2002

Page: 40 of 42

7.4 DPU to DCU - Redundant

Unit DPU
 Connector ID J10
 Connector type DBMA25P
 Connector name TO DCU_R

Pin #	Signal Name	EMC Class	Wire	Connected to		
				Unit	Connector	Pin
1	LCLK_DCU_SHD					
2	LCLK_DCU_P+		AWG26	DRU		
3	TX_DCU_P+		AWG26	DRU		
4	RX_DCU_P+		AWG26	DRU		
5	RX_SHD					
6						
7						
8	HCLK_DCU_P+		AWG26	DRU		
9	HCLK_SHD					
10	DAT_DCU_P+		AWG26	DRU		
11	GAT_DCU_P+		AWG26	DRU		
12	GAT_SHD					
13						
14						
15	LCLK_DCU_P-		AWG26	DRU		
16	TX_DCU_P-		AWG26	DRU		
17	RX_DCU_P-		AWG26	DRU		
18						
19						
20						
21	HCLK_DCU_P-		AWG26	DRU		
22	DAT_DCU_P-		AWG26	DRU		
23	DAT_SHD					
24	GAT_DCU_P-		AWG26	DRU		
25						



IFSI
CNR

Herschel SPIRE

DPU Interface Control Document

Ref. : SPIRE-IFS-PRJ-000650

Issue: 1.1

Date: 11/02/2002

Page: 41 of 42

7.5 DPU to MCU - Redundant

Unit DPU
 Connector ID J11
 Connector type DBMA25P
 Connector name TO MCU_R

Pin #	Signal Name	EMC Class	Wire	Connected to		
				Unit	Connector	Pin
1	LCLK_MCU_SHD					
2	LCLK_MCU_P+		AWG26	ICU		
3	TX_MCU_P+		AWG26	ICU		
4	RX_MCU_P+		AWG26	ICU		
5	RX_SHD					
6						
7						
8	HCLK_MCU_P+		AWG26	ICU		
9	HCLK_SHD					
10	DAT_MCU_P+		AWG26	ICU		
11	GAT_MCU_P+		AWG26	ICU		
12	GAT_SHD					
13						
14						
15	LCLK_MCU_P-		AWG26	ICU		
16	TX_MCU_P-		AWG26	ICU		
17	RX_MCU_P-		AWG26	ICU		
18						
19						
20						
21	HCLK_MCU_P-		AWG26	ICU		
22	DAT_MCU_P-		AWG26	ICU		
23	DAT_SHD					
24	GAT_MCU_P-		AWG26	ICU		
25						



IFSI
CNR

Herschel SPIRE

DPU Interface Control Document

Ref. : SPIRE-IFS-PRJ-000650

Issue: 1.1

Date: 11/02/2002

Page: 42 of 42

7.6 DPU to SCU - Redundant

Unit DPU
 Connector ID J12
 Connector type DBMA25P
 Connector name TO SCU_R

Pin #	Signal Name	EMC Class	Wire	Connected to		
				Unit	Connector	Pin
1	LCLK_SCU_SHD					
2	LCLK_SCU_P+		AWG26	ICU		
3	TX_SCU_P+		AWG26	ICU		
4	RX_SCU_P+		AWG26	ICU		
5	RX_SHD					
6						
7						
8	HCLK_SCU_P+		AWG26	ICU		
9	HCLK_SHD					
10	DAT_SCU_P+		AWG26	ICU		
11	GAT_SCU_P+		AWG26	ICU		
12	GAT_SHD					
13						
14						
15	LCLK_SCU_P-		AWG26	ICU		
16	TX_SCU_P-		AWG26	ICU		
17	RX_SCU_P-		AWG26	ICU		
18						
19						
20						
21	HCLK_SCU_P-		AWG26	ICU		
22	DAT_SCU_P-		AWG26	ICU		
23	DAT_SHD					
24	GAT_SCU_P-		AWG26	ICU		
25						