



CARLO GAVAZZI SPACE S.p.A.

HSO/FIRST-DPU

DOCUMENT TYPE : TEST REPORT

DRD : -

TITLE: EM PAYLOAD & SPACECRAFT INTERFACE BOARD P/N DPU-EM-200.00-0 S/N 05 TEST REPORT

DOCUMENT No: DPU-RP-CGS-032

PAGE: 1 OF 88

ISSUE No: 1


DATE: 13/05/2002

PREPARED BY: G. NEGRONI

APPROVED BY: M. VITTA

	YES	NO		
Product Assurance	<input checked="" type="checkbox"/>	<input type="checkbox"/>	_____	_____
			Approval Signature	Date
Configuration Control	<input checked="" type="checkbox"/>	<input type="checkbox"/>	_____	_____
			Approval Signature	Date
Project Control	<input type="checkbox"/>	<input checked="" type="checkbox"/>	_____	_____
			Approval Signature	Date
Engineering	<input checked="" type="checkbox"/>	<input type="checkbox"/>	_____	_____
			Approval Signature	Date
Managing Director	<input type="checkbox"/>	<input checked="" type="checkbox"/>	_____	_____
			Approval Signature	Date
CGS Program Manager	<input checked="" type="checkbox"/>	<input type="checkbox"/>	_____	_____
			Approval Signature	Date
Higher Level Contractor	<input type="checkbox"/>	<input type="checkbox"/>	_____	_____
			Approval Signature	Date
Customer	<input type="checkbox"/>	<input type="checkbox"/>	_____	_____
			Approval Signature	Date
Data Management			_____	_____
			Signature	Date

DOCUMENT CHANGE RECORD

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST- DPU	DOC N°: DPU-RP-CGS-032 ISSUE :1 DATE: 25/08/2006 PAGE : 2 OF 88
-----------------------------------------------------------------------------------------------------------------	---------------------------	--------------------------------------------------------------------------

ISSUE N°	DATE	CHANGE AUTHORITY	PAGES AFFECTED	REMARKS
1	13/05/2002			



CARLO GAVAZZI SPACE S.p.A.

HSO/FIRST-DPU

DOC N°: DPU-RP-CGS-032

ISSUE :1 DATE: 25/08/2006

PAGE : 3 OF 88

LIST OF VALID PAGES

PAGE	ISSUE N°	PAGE	ISSUE N°	PAGE	ISSUE N°	PAGE	ISSUE N°	PAGE	ISSUE N°
1-88	1								



CARLO GAVAZZI SPACE S.p.A.

HSO/FIRST-DPU

DOC N°: DPU-RP-CGS-032

ISSUE :1 DATE: 25/08/2006

PAGE : 4 OF 88

TABLE OF CONTENTS

1	<u>SCOPE.....</u>	<u>7</u>
2	<u>DOCUMENTS</u>	<u>8</u>
2.1	APPLICABLE DOCUMENTS	8
2.2	REFERENCE DOCUMENTS	8
3	<u>PARTICIPANTS REQUIRED.....</u>	<u>9</u>
3.1	GENERAL	9
3.2	RESPONSIBILITY.....	9
3.3	QA WITNESS OF TESTS AND SIGN-OFF	9
3.4	NON-CONFORMANCE AND FAILURES.....	9
3.5	CALIBRATION REQUIREMENTS	9
4	<u>TEST CONDITIONS.....</u>	<u>10</u>
5	<u>TEST ARTICLE.....</u>	<u>11</u>
6	<u>INSTRUMENTATION AND TEST EQUIPMENT.....</u>	<u>12</u>
7	<u>TEST CONFIGURATION</u>	<u>13</u>
8	<u>TEST DATA SHEETS.....</u>	<u>15</u>
8.1	DATA SHEETS FILLING UP	15
9	<u>PROCEDURE VARIATION SHEETS</u>	<u>83</u>
10	<u>CONCLUSIONS.....</u>	<u>84</u>
11	<u>PRINTOUTS.....</u>	<u>85</u>
11.1	PRINTOUT 01 (SEE STEP 8.25)	85
11.2	PRINTOUT 02 (SEE STEP 8.28)	86
11.3	PRINTOUT 03 (SEE STEP 8.42)	87
11.4	PRINTOUT 04 (SEE STEP 8.45)	88



CARLO GAVAZZI SPACE S.p.A.

HSO/FIRST-DPU

DOC N°: DPU-RP-CGS-032

ISSUE :1 DATE: 25/08/2006

PAGE : 5 OF 88

LIST OF ACRONYMS

AD#	Applicable Document number #
CGS	Carlo Gavazzi Space SpA
DM	Data Memory
DPU	Data Processing Unit
DDC	Data Device Corporation
DM	Data Memory
DPR	Dual Port Ram
EEPROM	Electrically Erasable Programmable Read Only Memory
EF	Empty FIFO
EM	Engineering Model
EPROM	Erasable Programmable Read Only Memory
EQM	Engineering Qualification Model
FIRST	Far Infra-Red and Sub-millimeter Telescope
FF	Full FIFO
FM	Flight Model
FPGA	Field Programmable Gate Array
FS	Flight Spare
FSDL	Fast Science Data Link
HF	Half Full FIFO
HIFI	Heterodyne Instrument for First
HSO	Herschel Space Observatory
IFSI	Istituto per la Fisica dello Spazio Interplanetario
IF	Interface
LSL	Low Speed Link
PA	Product Assurance
PACS	Photoconductor Array Camera and Spectrometer
PCB	Printed Circuit Board
PM	Program Memory
PROM	Programmable Read Only Memory
PL	Payload



CARLO GAVAZZI SPACE S.p.A.

HSO/FIRST- DPU

DOC N°: DPU-RP-CGS-032

ISSUE :1 DATE: 25/08/2006

PAGE : 6 OF 88

P/N	Part Number
RAM	Random Access Memory
RD#	Reference Document number #
S/N	Serial Number
SPIRE	Spectral and Photometric Imaging Receiver
TE	Test Equipment

 CARLO GAVAZZI SPACE S.p.A.	<h1>HSO/FIRST-DPU</h1>	DOC N°: DPU-RP-CGS-032 ISSUE :1 DATE: 25/08/2006 PAGE : 7 OF 88
-----------------------------------------------------------------------------------------------------------------	------------------------	--------------------------------------------------------------------------

1 SCOPE

The aim of the present document is to provide a detailed test report of “Payload & Spacecraft Interface” board P/N DPU-EM-200.00-0 S/N 05 to be used in the Data Processing Units, developed in the framework of the HSO/FIRST program. Particularly it must be tested each of the following functions:

1. Power-On Reset generation.
2. External Hardware Reset generation
3. Control Logic Reset generation
- 4.a Fast Science Data Link interfaces (FSDL) (Only for HIFI)
- 4.b Fast Science Data Link interfaces (FSDL) (Only for SPIRE)
- 5.a Low Speed Link interface (LSL) (Only for HIFI)
- 5.b Low Speed Link interface (LSL) (Only for SPIRE)
6. Analog inputs
7. MIL-STD-1553 Clock generation
8. MIL-STD-1553 interface

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	DOC N°: DPU-RP-CGS-032 ISSUE :1 DATE: 25/08/2006 PAGE : 8 OF 88
-----------------------------------------------------------------------------------------------------------------	----------------------	--------------------------------------------------------------------------

2 DOCUMENTS

2.1 *Applicable Documents*

The current issue of the following documents is applicable:

- [AD1]: DPU-SP-CGS-002 "Payload & Spacecraft Interface Board Specification"
- [AD2]: DPU-PL-CGS-001 "Product Assurance Plan for FIRST-DPU"
- [AD3]: DPU-PR-CGS-002 "EM Payload & Spacecraft Interface Board Test Procedure"

2.2 *Reference Documents*

To test the board the user needs the current issue of the following documents:

- [RD1]: Radiation Tolerant 32/40-BIT IEEE Floating Point DSP Microprocessor Data Book Temic
- [RD2]: DPU-SP-CGS-001 "First CPU Board Specification"
- [RD3]: Space Level MIL-STD-1553 BC/RT/MT Advanced Communication Engine Terminal BU-61582 Data Book ILC Data Device Corporation 1995
- [RD4]: MIL-STD-1553 BC/RT/MT Advance Communication Engine (ACE) Data Book ILC Data Device Corporation

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST- DPU	DOC N°: DPU-RP-CGS-032 ISSUE :1 DATE: 25/08/2006 PAGE : 9 OF 88
-----------------------------------------------------------------------------------------------------------------	---------------------------	--------------------------------------------------------------------------

3 PARTICIPANTS REQUIRED

3.1 General

All tests shall be performed under QA surveillance in accordance with and following detailed procedure of CGS PA Plan [AD2].

The test shall be notified to the Customer as applicable.

3.2 Responsibility

The technical responsibilities for testing and test results is of the Engineering department.

Project and test managers are responsible for the test program. The test engineer is responsible for the correct execution of the test program and for the fulfilment of the requirements, for measurement and recording and for the preparation of the test report.

QA is responsible for ensuring that all the agreed procedures are carefully observed, that test equipment and instrumentation used during testing are calibrated and within validity date, that the test results are recorded in the relative Test Report and signed by the operators and QA witness, that all non conforming condition and test results are properly documented and notified to the customer and that all requirements of applicable PA Plan, Specification and Statement Of Work pertaining to the acceptance tests, are fully satisfied.

3.3 QA witness of Tests and Sign-off

QA inspector, or its delegate, shall witness the tests described in this procedure in accordance to the requirement specified in the applicable PA Plans.

3.4 Non-conformance and failures

Any malfunction occurred during the tests shall be processed according to the Non-Conformance Procedure.

3.5 Calibration Requirements

All instruments used for testing shall be calibrated.

Evidence of certification shall be provided by a label attached to the instruments itself, showing the calibration date, the expire date and the signature of the operator.

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST- DPU	DOC N°: DPU-RP-CGS-032 ISSUE :1 DATE: 25/08/2006 PAGE : 10 OF 88
-----------------------------------------------------------------------------------------------------------------	---------------------------	---------------------------------------------------------------------------

4 TEST CONDITIONS

- The Unit shall be tested in its defined configuration: it shall be properly mounted, all the electrical loads (if any) shall be present and the unit interface function(s) shall be simulated.
- Unless otherwise specified, all the measurements are to be performed at the following ambient conditions:
 - Temperature : $22^{\circ}\text{C} \pm 3^{\circ}\text{C}$
 - Relative humidity: $55\% \pm 10\% \text{ RH}$
 - Pressure : Ambient
 - Cleanliness : NA
- All tests, unless otherwise specified, shall be performed internally to CGS laboratories in a proper clean area.
General disposition shall be applied to maximise personnel safety from potential hazards.
- Skilled personnel shall be employed.
- All used instruments shall meet the necessary accuracy and shall not degrade the UUT performance.

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST- DPU	DOC N°: DPU-RP-CGS-032 ISSUE :1 DATE: 25/08/2006 PAGE : 11 OF 88
-----------------------------------------------------------------------------------------------------------------	---------------------------	---------------------------------------------------------------------------

5 TEST ARTICLE

The test article consists of:

- PL IF Board, P/N DPU-EM-200.00-0, Model EM.

Before starting the test, the P/N and S/N of the test article to be tested shall be recorded on the step-by-step procedure sheets under the table cell "UNIT UNDER TEST".

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	DOC N°: DPU-RP-CGS-032 ISSUE :1 DATE: 25/08/2006 PAGE : 12 OF 88
-----------------------------------------------------------------------------------------------------------------	----------------------	---------------------------------------------------------------------------

6 INSTRUMENTATION AND TEST EQUIPMENT

The complete list of the instruments used during the test shall be reported in the following table. The list shall be filled up during tests and reported in Test Report.

PROJECT: HSO/FIRST-DPU							
N.	EQUIPMENT	MANUFACTURER	P/N	S/N	ACCURACY	NEXT CAL. DATE	REMARKS
1	OSCILLOSCOPE	TEKTRONIX	TDS620	B020528	-	21/04/03	-
2	POWER SUPPLY	TOP WARD	6303A	667104	-	-	-
3	POWER SUPPLY	TOP WARD	6303A	998095	-	-	-
4	MULTIMETER	HP	34401A	5415111	-	22/04/03	-

Table 6-1

To test serial links (FSDL and LSL) will be used a custom TE. It shall be called, in this document, as IFSI Simulator.

 CARLO GAVAZZI SPACE S.p.A.	<h1>HSO/FIRST-DPU</h1>	DOC N°: DPU-PR-CGS-032 ISSUE : 1 DATE: 25/08/2006 PAGE : 13 OF 88
-----------------------------------------------------------------------------------------------------------------	------------------------	-------------------------------------------------------------------------

7 TEST CONFIGURATION

Test set up is provided on Picture 7-1.

To supply power to the boards, use the apposite male connector to be plugged in slot 3 (P1) of the motherboard and make the following connections between Power Suppliers and wires:

- Red wire: +5V
- Orange wire: +2.5V
- Green wire: -15V
- Blue wire: +15V
- Brown wire: GROUND

Each connector of IFSI Simulator has to be connected with the correspondent connector wired to the motherboard (the name of sub-system which the link is referred is indicated on each connector).




CARLO GAVAZZI SPACE S.p.A.

HSO/FIRST-DPU

DOC N°: DPU-RP-CGS-032

ISSUE : 1 DATE: 25/08/2006

PAGE : 14 OF 88



Picture 7-1

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE: 25/08/2006 PAGE : 15 OF 88
-----------------------------------------------------------------------------------------------------------------	----------------------	-------------------------------------------------------------------------

8 TEST DATA SHEETS

The step-by-step procedure sheets are provided in the following pages¹.

8.1 Data Sheets filling up

The following fields of the data sheets:

- UUT DATA (including Model, Item, P/N, S/N)
- Measured value


shall be filled up during the test performances and shall be part of the Test Report together with printouts, photographs, etc. eventually useful to document the test execution/result.

Remarks field shall be used as a minimum to provide, where appropriate, reference to NCRs and PVS.


Test Report reference data shall be added in the relevant field.

Each data sheet (including the attachments) shall be certified by QA stamp and signature together with the Test Conductor signature and date.


¹ Components, connectors, jumpers, etc. are referred, where not indicated, to the PL IF Board. When all the boards are considered the word "unit" is used.

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 17 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 17 OF 88


TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
1	Power-On Reset generation			
1.1	Connect the probe channel 1 of the digital scope to the RES_1553 signal CN1 pin 36. Select positive slope trigger on CH1. Set acquisition mode NORMAL		OK	
1.2	Supply electrical power to the unit		OK	
1.3	Verify the negative pulse width	> 20 ms	85 ms	
DATE 08/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE	CUSTOMER	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 18 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 18 OF 88


TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
2	External Hardware Reset generation			
2.1	Insert the EZ ICE probe in the JTAG plug (JP12) of CPU Board		OK	
2.2	Supply electrical power to the unit	Green led on (CPU Board)	OK	
2.3	Open the program ADSP-21020 Emulator		OK	
2.4	Type Enter two times to end Row JTAG and Opcode Scan Test		OK	
2.5	From menu Memory select "Program"	PM window appears	OK	
2.6	From menu Memory select "Data"	DM window appears	OK	
2.7	From menu File select "Load File..."	A prompt window appears	OK	
2.8	In the HSO folder select "hsoconf.ach"	"RAM" (left side mem. loc.)	OK	
2.9	Select Data Memory Windows		OK	
DATE 08/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE	CUSTOMER	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 19 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 19 OF 88


TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
2.10	Write 0000000800 in the address location 82000000		OK	
2.11	Connect the probe channel 1 oscilloscope with pin 7 of U2 (or pin 36 of CN1)		OK	
2.12	Verify signal on channel 1 of the oscilloscope	Low	Low	
2.13	Connect the probe channel 1 oscilloscope with pin 22 of U17		OK	
2.14	Verify signal on channel 1 of the oscilloscope	Low	Low	
2.15	Connect the probe channel 1 oscilloscope with pin 22 of U16		OK	
2.16	Verify signal on channel 1 of the oscilloscope	Low	Low	
2.17	Connect the probe channel 1 oscilloscope with pin 22 of U24		OK	
2.18	Verify signal on channel 1 of the oscilloscope	Low	Low	
DATE 08/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE	CUSTOMER	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 20 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 20 OF 88


TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
2.19	Connect the probe channel 1 oscilloscope with pin 22 of U23		OK	
2.20	Verify signal on channel 1 of the oscilloscope	Low	Low	
2.21	Select Data Memory Windows		OK	
2.22	Write 0000000000 in the address location 82000000		OK	
2.23	Connect the probe channel 1 oscilloscope with pin 7 of U2 (or pin 36 of CN1)		OK	
2.24	Verify signal on channel 1 of the oscilloscope	High	High	
2.25	Connect the probe channel 1 oscilloscope with pin 22 of U17		OK	
2.26	Verify signal on channel 1 of the oscilloscope	High	High	
2.27	Connect the probe channel 1 oscilloscope with pin 22 of U16		OK	
DATE 08/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE	CUSTOMER	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 21 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 21 OF 88


TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
2.28	Verify signal on channel 1 of the oscilloscope	High	High	
2.29	Connect the probe channel 1 oscilloscope with pin 22 of U24		OK	
2.30	Verify signal on channel 1 of the oscilloscope	High	High	
2.31	Connect the probe channel 1 oscilloscope with pin 22 of U23		OK	
2.32	Verify signal on channel 1 of the oscilloscope	High	High	
DATE 08/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE	CUSTOMER	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 22 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 22 OF 88


TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
3	Control Logic Reset generation			
3.1	Insert the EZ ICE probe in the JTAG plug (JP12) of CPU Board		OK	
3.2	Supply electrical power to the unit	Green led on (CPU Board)	OK	
3.3	Open the program ADSP-21020 Emulator		OK	
3.4	Type Enter two times to end Row JTAG and Opcode Scan Test		OK	
3.5	From menu Memory select "Program"	PM window appears	OK	
3.6	From menu Memory select "Data"	DM window appears	OK	
3.7	From menu File select "Load File..."	A prompt window appears	OK	
3.8	In the HSO folder select "hsoconf.ach"	"RAM" (left side mem. loc.)	OK	
3.9	Select Data Memory Windows		OK	
DATE 08/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE	CUSTOMER	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 23 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 23 OF 88


TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
3.10	Write 0000000100 in the address location 8d000000		OK	
3.11	Connect the probe channel 1 oscilloscope with pin 22 of U17		OK	
3.12	Verify signal on channel 1 of the oscilloscope	Low	Low	
3.13	Write 0000000200 in the address location 8d000000		OK	
3.14	Connect the probe channel 1 oscilloscope with pin 22 of U16		OK	
3.15	Verify signal on channel 1 of the oscilloscope	Low	Low	
3.16	Write 0000000400 in the address location 8d000000		OK	
3.17	Connect the probe channel 1 oscilloscope with pin 22 of U24		OK	
3.18	Verify signal on channel 1 of the oscilloscope	Low	Low	
DATE 08/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE	CUSTOMER	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 24 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 24 OF 88


TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
3.19	Write 0000000800 in the address location 8d000000		OK	
3.20	Connect the probe channel 1 oscilloscope with pin 22 of U23		OK	
3.21	Verify signal on channel 1 of the oscilloscope	Low	Low	
3.22	Write 0000001000 in the address location 8d000000		OK	
3.23	Connect the probe channel 1 oscilloscope with pin 7 of U2 (or pin 36 of CN1)		OK	
3.24	Verify signal on channel 1 of the oscilloscope	Low	Low	
3.25	Write 0000800000 in the address location 8d000000		OK	
3.26	Connect the probe channel 1 oscilloscope with pin 7 of U2 (or pin 36 of CN1)		OK	
3.27	Verify signal on channel 1 of the oscilloscope	Low	Low	
DATE 08/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE	CUSTOMER	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 25 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 25 OF 88


TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
3.28	Connect the probe channel 1 oscilloscope with pin 22 of U17		OK	
3.29	Verify signal on channel 1 of the oscilloscope	Low	Low	
3.30	Connect the probe channel 1 oscilloscope with pin 22 of U16		OK	
3.31	Verify signal on channel 1 of the oscilloscope	Low	Low	
3.32	Connect the probe channel 1 oscilloscope with pin 22 of U24		OK	
3.33	Verify signal on channel 1 of the oscilloscope	Low	Low	
3.34	Connect the probe channel 1 oscilloscope with pin 22 of U23		OK	
3.35	Verify signal on channel 1 of the oscilloscope	Low	Low	
DATE 08/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE	CUSTOMER	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 26 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 26 OF 88


TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE			UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS	
4.a	Fast Science Data Link interfaces (HIFI configuration)				
4.a.1	Insert the EZ ICE probe in the JTAG plug (JP12) of CPU Board		N.A.	Serial number 05 is in SPIRE configuration	
4.a.2	Supply electrical power to the unit	Green led on (CPU Board)	N.A.		
4.a.3	Open the program ADSP-21020 Emulator		N.A.		
4.a.4	Type Enter two times to end Row JTAG and Opcode Scan Test		N.A.		
4.a.5	From menu Memory select “Program”	PM window appears	N.A.		
4.a.6	From menu Memory select “Data”	DM window appears	N.A.		
4.a.7	From menu File select “Load File...”	A prompt window appears	N.A.		
4.a.8	In the HSO folder select “hsoconfc.ach”	“RAM” (left side mem. loc.)	N.A.		
DATE 08/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE		CUSTOMER	
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05			

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 27 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 27 OF 88


STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
4.a.9	From menu File select “Load File...”	A prompt window appears	N.A.	
4.a.10	In the HSO folder select “fifot0.exe”		N.A.	
4.a.11	From menu Execute select “CBUG”	CBUG window appears	N.A.	
4.a.12	From menu Execution select “Restart”		N.A.	
4.a.13	Search line “ // === BREAK POINT to load FIFO “ in the program		N.A.	
4.a.14	Double click on “for (i=0; i<1200; ++i) { “	“ * “ appears	N.A.	
4.a.15	Search line “ // === BREAK POINT to read i and j“ in the program		N.A.	
4.a.16	Double click on “ * Fifodat[0][k]= * fifoadd0 “	“ * “ appears	N.A.	
4.a.17	From menu Execution of emulator select “Continue”		N.A.	
DATE 08/05/02		TEST CONDUCTOR	PRODUCT ASSURANCE	CUSTOMER
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE			UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05	
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 28 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 28 OF 88


4.a.18	Search line “ // === BREAK POINT to load FIFO “ in the program		N.A.		
4.a.19	Double click on “for (i=0; i<1200; ++i) { “	“ * “ disappears	N.A.		
4.a.20	Open the program HIFI1.exe on IFSI Simulator	A DOS window appears	N.A.		
4.a.21	Press “L”		N.A.		
4.a.22	Type “D1” and press “Enter”		N.A.		
4.a.23	Press “R”	FIFO TX	N.A.		
4.a.24	Press “R”	FIFO TX	N.A.		
4.a.25	Press “L”		N.A.		
4.a.26	Type “D4” and press “Enter”		N.A.		
4.a.27	Press “R”	FIFO TX	N.A.		
DATE 08/05/02		TEST CONDUCTOR		PRODUCT ASSURANCE	CUSTOMER
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE				UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05	
STEP N°	TEST SEQUENCE		EXPECTED VALUE	MEASURED VALUE	REMARKS
4.a.28	From menu Execution of emulator select “Continue”			N.A.	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 29 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 29 OF 88


4.a.29	From menu Data of emulator select “Print”		N.A.	
4.a.30	Type “i”		N.A.	
4.a.31	Select “OK”	2048	N.A.	
4.a.32	From menu Data of emulator select “Print”		N.A.	
4.a.33	Type “j”		N.A.	
4.a.34	Select “OK”	2048	N.A.	
4.a.35	Close the “CBUG” window		N.A.	
4.a.36	From menu Execution select “Chip Reset”		N.A.	
4.a.37	Select “OK”		N.A.	
4.a.38	From menu Execution select “Assembly Breaks”		N.A.	
DATE 08/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE		CUSTOMER
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
4.a.39	Select “Delete All”		N.A.	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 30 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 30 OF 88


4.a.40	From menu File select “Load File...”	A prompt window appears	N.A.		
4.a.41	In the HSO folder select “hsoconfc.ach”	“RAM” (left side mem. loc.)	N.A.		
4.a.42	From menu File select “Load File...”	A prompt window appears	N.A.		
4.a.43	In the HSO folder select “fifot1.exe”		N.A.		
4.a.44	From menu Execute select “CBUG”	CBUG window appears	N.A.		
4.a.45	From menu Execution select “Restart”		N.A.		
4.a.46	Search line “ // === BREAK POINT to load FIFO “ in the program		N.A.		
4.a.47	Double click on “for (i=0; i<1200; ++i) { “	“ * “ appears	N.A.		
4.a.48	Search line “ // === BREAK POINT to read i and j” in the program		N.A.		
DATE 08/05/02		TEST CONDUCTOR		PRODUCT ASSURANCE	CUSTOMER
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE				UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05	
STEP N°	TEST SEQUENCE		EXPECTED VALUE	MEASURED VALUE	REMARKS
4.a.49	Double click on “ * Fifodat[1][k]= * fifoadd1 “		“ * “ appears	N.A.	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 31 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 31 OF 88


4.a.50	From menu Execution of emulator select “Continue”		N.A.		
4.a.51	Search line “ // === BREAK POINT to load FIFO “ in the program		N.A.		
4.a.52	Double click on “for (i=0; i<1200; ++i) { “	“ * “ disappears	N.A.		
4.a.53	Open the program HIF1.exe on IFSI Simulator	A DOS window appears	N.A.		
4.a.54	Press “F”		N.A.		
4.a.55	Type “1” and press “Enter”		N.A.		
4.a.56	Press “L”		N.A.		
4.a.57	Type “D1” and press “Enter”		N.A.		
4.a.58	Press “R”	FIFO TX	N.A.		
DATE 08/05/02		TEST CONDUCTOR		PRODUCT ASSURANCE	CUSTOMER
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE				UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05	
STEP N°	TEST SEQUENCE		EXPECTED VALUE	MEASURED VALUE	REMARKS
4.a.59	Press “R”		FIFO TX	N.A.	
4.a.60	Press “L”			N.A.	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 32 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 32 OF 88


4.a.61	Type “D4” and press “Enter”		N.A.		
4.a.62	Press “R”	FIFO TX	N.A.		
4.a.63	From menu Execution of emulator select “Continue”		N.A.		
4.a.64	From menu Data of emulator select “Print”		N.A.		
4.a.65	Type “i”		N.A.		
4.a.66	Select “OK”	2048	N.A.		
4.a.67	From menu Data of emulator select “Print”		N.A.		
4.a.68	Type “j”		N.A.		
4.a.69	Select “OK”	2048	N.A.		
DATE 08/05/02		TEST CONDUCTOR		PRODUCT ASSURANCE	CUSTOMER
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE				UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05	
STEP N°	TEST SEQUENCE		EXPECTED VALUE	MEASURED VALUE	REMARKS
4.a.70	Close the “CBUG” window			N.A.	
4.a.71	From menu Execution select “Chip Reset”			N.A.	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 33 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 33 OF 88


4.a.72	Select “OK”		N.A.	
4.a.73	From menu Execution select “Assembly Breaks”		N.A.	
4.a.74	Select “Delete All”		N.A.	
4.a.75	From menu File select “Load File...”	A prompt window appears	N.A.	
4.a.76	In the HSO folder select “hsoconfc.ach”	“RAM” (left side mem. loc.)	N.A.	
4.a.77	From menu File select “Load File...”	A prompt window appears	N.A.	
4.a.78	In the HSO folder select “fifot2.exe”		N.A.	
4.a.79	From menu Execute select “CBUG”	CBUG window appears	N.A.	
DATE 08/05/02		TEST CONDUCTOR	PRODUCT ASSURANCE	CUSTOMER
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
4.a.80	From menu Execution select “Restart”		N.A.	
4.a.81	Search line “ // === BREAK POINT to load FIFO “ in the program		N.A.	
4.a.82	Double click on “for (i=0; i<1200; ++i) { “	“ * “ appears	N.A.	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 34 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 34 OF 88


4.a.83	Search line “ // === BREAK POINT to read i and j” in the program		N.A.		
4.a.84	Double click on “*Fifodat[2][k]=*fifoadd2 “	“ * “ appears	N.A.		
4.a.85	From menu Execution of emulator select “Continue”		N.A.		
4.a.86	Search line “// === BREAK POINT to load FIFO “ in the program		N.A.		
4.a.87	Double click on “for (i=0; i<1200; ++i) { “	“ * “ disappears	N.A.		
4.a.88	Open the program HIF11.exe on IFSI Simulator	A DOS window appears	N.A.		
DATE 08/05/02		TEST CONDUCTOR		PRODUCT ASSURANCE	CUSTOMER
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE				UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05	
STEP N°	TEST SEQUENCE		EXPECTED VALUE	MEASURED VALUE	REMARKS
4.a.89	Press “F”			N.A.	
4.a.90	Type “2” and press “Enter”			N.A.	
4.a.91	Press “L”			N.A.	
4.a.92	Type “D1” and press “Enter”			N.A.	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 35 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 35 OF 88

4.a.93	Press “R”	FIFO TX	N.A.	
4.a.94	Press “R”	FIFO TX	N.A.	
4.a.95	Press “L”		N.A.	
4.a.96	Type “D4” and press “Enter”		N.A.	
4.a.97	Press “R”	FIFO TX	N.A.	
4.a.98	From menu Execution of emulator select “Continue”		N.A.	
4.a.99	From menu Data of emulator select “Print”		N.A.	
DATE 08/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE	CUSTOMER	
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
4.a.100	Type “i”		N.A.	
4.a.101	Select “OK”	2048	N.A.	
4.a.102	From menu Data of emulator select “Print”		N.A.	
4.a.103	Type “j”		N.A.	


 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 36 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 36 OF 88

4.a.104	Select “OK”	2048	N.A.		
4.a.105	Close the “CBUG” window		N.A.		
4.a.106	From menu Execution select “Chip Reset”		N.A.		
4.a.107	Select “OK”		N.A.		
4.a.108	From menu Execution select “Assembly Breaks”		N.A.		
4.a.109	Select “Delete All”		N.A.		
4.a.110	From menu File select “Load File...”	A prompt window appears	N.A.		
DATE 08/05/02		TEST CONDUCTOR		PRODUCT ASSURANCE	CUSTOMER
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE				UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05	
STEP N°	TEST SEQUENCE		EXPECTED VALUE	MEASURED VALUE	REMARKS
4.a.111	In the HSO folder select “hsoconfc.ach”		“RAM” (left side mem. loc.)	N.A.	
4.a.112	From menu File select “Load File...”		A prompt window appears	N.A.	
4.a.113	In the HSO folder select “fifot3.exe”			N.A.	
4.a.114	From menu Execute select “CBUG”		CBUG window appears	N.A.	


 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 37 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 37 OF 88

4.a.115	From menu Execution select "Restart"		N.A.	
4.a.116	Search line " // === BREAK POINT to load FIFO " in the program		N.A.	
4.a.117	Double click on "for (i=0; i<1200; ++i) { "	" * " appears	N.A.	
4.a.118	Search line " // === BREAK POINT to read i and j" in the program		N.A.	
4.a.119	Double click on "*Fifodat[3][k]=*fifoad3 "	" * " appears	N.A.	
DATE 08/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE	CUSTOMER	


TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
4.a.120	From menu Execution of emulator select "Continue"		N.A.	
4.a.121	Search line " // === BREAK POINT to load FIFO " in the program		N.A.	
4.a.122	Double click on "for (i=0; i<1200; ++i) { "	" * " disappears	N.A.	
4.a.123	Open the program HIFI1.exe on IFSI Simulator	A DOS window appears	N.A.	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 38 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 38 OF 88


4.a.124	Press “F”		N.A.		
4.a.125	Type “3” and press “Enter”		N.A.		
4.a.126	Press “L”		N.A.		
4.a.127	Type “D1” and press “Enter”		N.A.		
4.a.128	Press “R”	FIFO TX	N.A.		
4.a.129	Press “R”	FIFO TX	N.A.		
DATE 08/05/02		TEST CONDUCTOR		PRODUCT ASSURANCE	CUSTOMER
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE			UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS	
4.a.130	Press “L”		N.A.		
4.a.131	Type “D4” and press “Enter”		N.A.		
4.a.132	Press “R”	FIFO TX	N.A.		
4.a.133	From menu Execution of emulator select “Continue”		N.A.		
4.a.134	From menu Data of emulator select “Print”		N.A.		

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 39 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 39 OF 88


4.a.135	Type “i”			N.A.	
4.a.136	Select “OK”		2048	N.A.	
4.a.137	From menu Data of emulator select “Print”			N.A.	
4.a.138	Type “j”			N.A.	
4.a.139	Select “OK”		2048	N.A.	
DATE 08/05/02		TEST CONDUCTOR	PRODUCT ASSURANCE		CUSTOMER
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE			UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE		EXPECTED VALUE	MEASURED VALUE	REMARKS
4.b	Fast Science Data Link interfaces (SPIRE configuration)				
4.b.1	Insert the EZ ICE probe in the JTAG plug (JP12) of CPU Board			OK	
4.b.2	Supply electrical power to the unit		Green led on (CPU Board)	OK	
4.b.3	Open the program ADSP-21020 Emulator			OK	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 40 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 40 OF 88


4.b.4	Type Enter two times to end Row JTAG and Opcode Scan Test		OK	
4.b.5	From menu Memory select “Program”	P.M. window appears	OK	
4.b.6	From menu Memory select “Data”	D.M. window appears	OK	
4.b.7	From menu File select “Load File...”	A prompt window appears	OK	
4.b.8	In the HSO folder select “hsoconfc.ach”	“RAM” (left side mem. loc.)	OK	
DATE 08/05/02		TEST CONDUCTOR	PRODUCT ASSURANCE	CUSTOMER
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
4.b.9	From menu File select “Load File...”	A prompt window appears	OK	
4.b.10	In the HSO folder select “fifot0.exe”	“RAM” (left side mem. loc.)	OK	
4.b.11	From menu Execute select “CBUG”	CBUG window appears	OK	
4.b.12	From menu Execution select “Restart”		OK	
4.b.13	Search line “ // === BREAK POINT to load FIFO “ in the program		OK	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 41 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 41 OF 88


4.b.14	Double click on “for (i=0; i<1200; ++i) { “	“ * “ appears	OK	
4.b.15	Search line “ // === BREAK POINT to read i and j” in the program		OK	
4.b.16	Double click on “ * Fifodat[0][k]= * fifoadd0 “	“ * “ appears	OK	
4.b.17	From menu Execution of emulator select “Continue”		OK	
DATE 08/05/02		TEST CONDUCTOR	PRODUCT ASSURANCE	CUSTOMER
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
4.b.18	Search line “ // === BREAK POINT to load FIFO “ in the program		OK	
4.b.19	Double click on “for (i=0; i<1200; ++i) { “	“ * “ disappears	OK	
4.b.20	Open the program SPIRE.exe on IFSI Simulator	A DOS window appears	OK	
4.b.21	Press “L”		OK	
4.b.22	Type “D1” and press “Enter”		OK	
4.b.23	Press “R”	FIFO TX	OK	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 42 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 42 OF 88


4.b.24	Press “R”	FIFO TX	OK	
4.b.25	Press “L”		OK	
4.b.26	Type “D4” and press “Enter”		OK	
4.b.27	Press “R”	FIFO TX	OK	
DATE 08/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE	CUSTOMER	
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
4.b.28	From menu Execution of emulator select “Continue”		OK	
4.b.29	From menu Data of emulator select “Print”		OK	
4.b.30	Type “i”		OK	
4.b.31	Select “OK”	2048	2048	
4.b.32	From menu Data of emulator select “Print”		OK	
4.b.33	Type “j”		OK	
4.b.34	Select “OK”	2048	2048	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 43 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 43 OF 88


4.b.35	Close the “CBUG” window		OK	
4.b.36	From menu Execution select “Chip Reset”		OK	
4.b.37	Select “OK”		OK	
4.b.38	From menu Execution select “Assembly Breaks”		OK	
DATE 08/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE	CUSTOMER	
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
4.b.39	Select “Delete All”		OK	
4.b.40	From menu File select “Load File...”	A prompt window appears	OK	
4.b.41	In the HSO folder select “hsoconfc.ach”	“RAM” (left side mem. loc.)	OK	
4.b.42	From menu File select “Load File...”	A prompt window appears	OK	
4.b.43	In the HSO folder select “fifot1.exe”	“RAM” (left side mem. loc.)	OK	
4.b.44	From menu Execute select “CBUG”	CBUG window appears	OK	
4.b.45	From menu Execution select “Restart”		OK	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 44 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 44 OF 88


4.b.46	Search line “ // === BREAK POINT to load FIFO “ in the program		OK	
4.b.47	Double click on “for (i=0; i<1200; ++i) { “	“ * “ appears	OK	
4.b.48	Search line “ // === BREAK POINT to read i and j“ in the program		OK	
DATE 08/05/02		TEST CONDUCTOR	PRODUCT ASSURANCE	CUSTOMER
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
4.b.49	Double click on “ * Fifodat[1][k]= * fifoadd1 “	“ * “ appears	OK	
4.b.50	From menu Execution of emulator select “Continue”		OK	
4.b.51	Search line “ // === BREAK POINT to load FIFO “ in the program		OK	
4.b.52	Double click on “for (i=0; i<1200; ++i) { “	“ * “ disappears	OK	
4.b.53	Open the program SPIRE.exe on IFSI Simulator	A DOS window appears	OK	
4.b.54	Press “F”		OK	
4.b.55	Type “1” and press “Enter”		OK	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 45 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 45 OF 88


4.b.56	Press “L”		OK	
4.b.57	Type “D1” and press “Enter”		OK	
4.b.58	Press “R”	FIFO TX	OK	
DATE 08/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE	CUSTOMER	
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
4.b.59	Press “R”	FIFO TX	OK	
4.b.60	Press “L”		OK	
4.b.61	Type “D4” and press “Enter”		OK	
4.b.62	Press “R”	FIFO TX	OK	
4.b.63	From menu Execution of emulator select “Continue”		OK	
4.b.64	From menu Data of emulator select “Print”		OK	
4.b.65	Type “I”		OK	
4.b.66	Select “OK”	2048	2048	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 46 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 46 OF 88


4.b.67	From menu Data of emulator select “Print”		OK	
4.b.68	Type “j”		OK	
4.b.69	Select “OK”	2048	2048	
DATE 08/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE	CUSTOMER	
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
4.b.70	Close the “CBUG” window		OK	
4.b.71	Select “OK”		OK	
4.b.72	From menu Execution select “Assembly Breaks”		OK	
4.b.73	Select “Delete All”		OK	
4.b.74	From menu File select “Load File...”	A prompt window appears	OK	
4.b.75	In the HSO folder select “hsoconfc.ach”	“RAM” (left side mem. loc.)	OK	
4.b.76	From menu File select “Load File...”	A prompt window appears	OK	
4.b.77	In the HSO folder select “fifot2.exe”	“RAM” (left side mem. loc.)	OK	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 47 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 47 OF 88

4.b.78	From menu Execute select “CBUG”	CBUG window appears	OK	
4.b.79	From menu Execution select “Restart”		OK	
DATE 08/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE	CUSTOMER	
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
4.b.80	Search line “ // === BREAK POINT to load FIFO “ in the program		OK	
4.b.81	Double click on “for (i=0; i<1200; ++i) { “	“ * “ appears	OK	
4.b.82	Search line “ // === BREAK POINT to read i and j“ in the program		OK	
4.b.83	Double click on “*Fifodat[2][k]=*fifoad2 “	“ * “ appears	OK	
4.b.84	From menu Execution of emulator select “Continue”		OK	
4.b.85	Search line “// === BREAK POINT to load FIFO “ in the program		OK	
4.b.86	Double click on “for (i=0; i<1200; ++i) { “	“ * “ disappears	OK	
4.b.87	Open the program SPIRE.exe on IFSI Simulator	A DOS window appears	OK	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 48 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 48 OF 88


4.b.88	Press “F”		OK	
DATE 08/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE	CUSTOMER	
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
4.b.89	Type “2” and press “Enter”		OK	
4.b.90	Press “L”		OK	
4.b.91	Type “D1” and press “Enter”		OK	
4.b.92	Press “R”	FIFO TX	OK	
4.b.93	Press “R”	FIFO TX	OK	
4.b.94	Press “L”		OK	
4.b.95	Type “D4” and press “Enter”		OK	
4.b.96	Press “R”	FIFO TX	OK	
4.b.97	From menu Execution of emulator select “Continue”		OK	
4.b.98	From menu Data of emulator select “Print”		OK	




TEST PROCEDURE REFERENCE
DOC N°: DPU-PR-CGS-002
ISSUE : 3
DATE : 06/02/2002
PAGE : 49 OF 85

TEST REPORT REFERENCE
DOC N°: DPU-RP-CGS-032
ISSUE : 1
DATE : 13/05/2002
PAGE : 49 OF 88


[illegible]

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 50 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 50 OF 88


DATE 08/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE		CUSTOMER
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
5.a	Low Speed Link interface (HIFI configuration)			
5.a.1	Insert the EZ ICE probe in the JTAG plug (JP12) of CPU Board		N.A.	Serial number 05 is in SPIRE configuration
5.a.2	Supply electrical power to the unit	Green led on (CPU Board)	N.A.	
5.a.3	Open the program ADSP-21020 Emulator		N.A.	
5.a.4	Type Enter two times to end Row JTAG and Opcode Scan Test		N.A.	
5.a.5	From menu Memory select "Program"	P.M. window appears	N.A.	
5.a.6	From menu Memory select "Data"	D.M. window appears	N.A.	
5.a.7	From menu File select "Load File..."	A prompt window appears	N.A.	
5.a.8	In the HSO folder select "hsoconfc.ach"	"RAM" (left side mem. loc.)	N.A.	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 51 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 51 OF 88


5.a.9	From menu File select “Load File...”	A prompt window appears	N.A.	
DATE 08/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE	CUSTOMER	
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
5.a.10	In the HSO folder select “memtest.exe”	“RAM” (left side mem. loc.)	N.A.	
5.a.11	From menu Execute select “CBUG”	CBUG window appears	N.A.	
5.a.12	From menu Execution select “Restart”		N.A.	
5.a.13	Search line “ //Test LowSpeed I/F “ in the program		N.A.	
5.a.14	Double click on “for (i=0; i<10; ++i) { “	“ * “ appears	N.A.	
5.a.15	Search end of the program		N.A.	
5.a.16	Double click on “}”	“ * “ appears	N.A.	
5.a.17	Open the program HIFI1.exe	A DOS window appears	N.A.	
5.a.18	From menu Execution of emulator select “Continue”		N.A.	
5.a.19	From menu Execution of emulator select “Continue”		N.A.	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 52 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 52 OF 88


5.a.20	From menu Data of emulator select “Print”		N.A.	
DATE 08/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE	CUSTOMER	
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
5.a.21	Type “i”		N.A.	
5.a.22	Select “OK”	8000	N.A.	
5.a.23	From menu Data of emulator select “Print”		N.A.	
5.a.24	Type “n_ lsTx”		N.A.	
5.a.25	Select “OK”	16	N.A.	
5.a.26	From menu Execution of emulator select “Restart”		N.A.	
5.a.27	Select HIFI1.exe window		N.A.	
5.a.28	Press “S”		N.A.	
5.a.29	Type “1” and press “Enter”		N.A.	
5.a.30	From menu Execution of emulator select “Continue”		N.A.	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 53 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 53 OF 88


5.a.31	From menu Execution of emulator select “Continue”		N.A.	
DATE 08/05/02		TEST CONDUCTOR	PRODUCT ASSURANCE	CUSTOMER
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE			UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05	
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
5.a.32	From menu Data of emulator select “Print”		N.A.	
5.a.33	Type “i”		N.A.	
5.a.34	Select “OK”	8000	N.A.	
5.a.35	From menu Data of emulator select “Print”		N.A.	
5.a.36	Type “n_ lsTx”		N.A.	
5.a.37	Select “OK”	16	N.A.	
5.a.38	From menu Execution select “Restart”		N.A.	
5.a.39	Select HIFI1.exe window		N.A.	
5.a.40	Press “S”		N.A.	
5.a.41	Type “2” and press “Enter”		N.A.	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 54 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 54 OF 88


5.a.42	From menu Execution of emulator select “Continue”			N.A.	
DATE 08/05/02		TEST CONDUCTOR	PRODUCT ASSURANCE		CUSTOMER
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE			UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE		EXPECTED VALUE	MEASURED VALUE	REMARKS
5.a.43	From menu Execution of emulator select “Continue”			N.A.	
5.a.44	From menu Data of emulator select “Print”			N.A.	
5.a.45	Type “i”			N.A.	
5.a.46	Select “OK”		8000	N.A.	
5.a.47	From menu Data of emulator select “Print”			N.A.	
5.a.48	Type “n_ lsTx”			N.A.	
5.a.49	Select “OK”		16	N.A.	
5.a.50	From menu Execution select “Restart”			N.A.	
5.a.51	Select HIFI1.exe window			N.A.	
5.a.52	Press “S”			N.A.	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 55 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 55 OF 88


5.a.53	Type “3” and press “Enter”			N.A.	
DATE 08/05/02		TEST CONDUCTOR	PRODUCT ASSURANCE		CUSTOMER
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE			UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE		EXPECTED VALUE	MEASURED VALUE	REMARKS
5.a.54	From menu Execution of emulator select “Continue”			N.A.	
5.a.55	From menu Execution of emulator select “Continue”			N.A.	
5.a.56	From menu Data of emulator select “Print”			N.A.	
5.a.57	Type “i”			N.A.	
5.a.58	Select “OK”		8000	N.A.	
5.a.59	From menu Data of emulator select “Print”			N.A.	
5.a.60	Type “n_ lsTx”			N.A.	
5.a.61	Select “OK”		16	N.A.	
5.a.62	From menu Execution select “Restart”			N.A.	
5.a.63	Select HIFI1.exe window			N.A.	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 56 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 56 OF 88


5.a.64	Press “S”		N.A.	
DATE 08/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE	CUSTOMER	
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
5.a.65	Type “4” and press “Enter”		N.A.	
5.a.66	From menu Execution of emulator select “Continue”		N.A.	
5.a.67	From menu Execution of emulator select “Continue”		N.A.	
5.a.68	From menu Data of emulator select “Print”		N.A.	
5.a.69	Type “i”		N.A.	
5.a.70	Select “OK”	8000	N.A.	
5.a.71	From menu Data of emulator select “Print”		N.A.	
5.a.72	Type “n_ lsTx”		N.A.	
5.a.73	Select “OK”	16	N.A.	
5.a.74	From menu Execution select “Restart”		N.A.	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 57 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 57 OF 88


5.a.75	Select HIFI1.exe window		N.A.	
DATE 08/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE	CUSTOMER	
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
5.a.76	Press “S”		N.A.	
5.a.77	Type “5” and press “Enter”		N.A.	
5.a.78	From menu Execution of emulator select “Continue”		N.A.	
5.a.79	From menu Execution of emulator select “Continue”		N.A.	
5.a.80	From menu Data of emulator select “Print”		N.A.	
5.a.81	Type “i”		N.A.	
5.a.82	Select “OK”	8000	N.A.	
5.a.83	From menu Data of emulator select “Print”		N.A.	
5.a.84	Type “n_ lsTx”		N.A.	
5.a.85	Select “OK”	16	N.A.	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 58 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 58 OF 88


5.a.86	From menu Execution select "Restart"		N.A.	
DATE 08/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE		CUSTOMER
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
5.a.87	Select HIFI1.exe window		N.A.	
5.a.88	Press "S"		N.A.	
5.a.89	Type "6" and press "Enter"		N.A.	
5.a.90	From menu Execution of emulator select "Continue"		N.A.	
5.a.91	From menu Execution of emulator select "Continue"		N.A.	
5.a.92	From menu Data of emulator select "Print"		N.A.	
5.a.93	Type "i"		N.A.	
5.a.94	Select "OK"	8000	N.A.	
5.a.95	From menu Data of emulator select "Print"		N.A.	
5.a.96	Type "n_ lsTx"		N.A.	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 59 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 59 OF 88


5.a.97	Select “OK”	16	N.A.	
DATE 08/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE	CUSTOMER	
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
5.a.98	Close the “CBUG” window		N.A.	
5.a.99	From menu Execution select “Chip Reset”		N.A.	
5.a.100	Select “N.A.”		N.A.	
5.a.101	From menu Execution select “Assembly Breaks”		N.A.	
5.a.102	Select “Delete All”		N.A.	
5.a.103	From menu File select “Load File...”	A prompt window appears	N.A.	
5.a.104	In the HSO folder select “hsoconfc.ach”	“RAM” (left side mem. loc.)	N.A.	
5.a.105	From menu File select “Load File...”	A prompt window appears	N.A.	
5.a.106	In the HSO folder select “hk_test.exe”	“RAM” (left side mem. loc.)	N.A.	
5.a.107	From menu Execute select “CBUG”	CBUG window appears	N.A.	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 60 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 60 OF 88


DATE 08/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE		CUSTOMER
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
5.a.108	From menu Execution select “Restart”		N.A.	
5.a.109	Search line “ //Test LowSpeed I/F “ in the program		N.A.	
5.a.110	Double click on “for (i=0; i<10; ++i) { “	“ * “ appears	N.A.	
5.a.111	Search end of the program		N.A.	
5.a.112	Double click on “}“	“ * “ appears	N.A.	
5.a.113	Select HIF11.exe window	A DOS window appears	N.A.	
5.a.114	Press “S”		N.A.	
5.a.115	Type “0” and press “Enter”		N.A.	
5.a.116	From menu Execution of emulator select “Continue”		N.A.	
5.a.117	From menu Execution of emulator select “Continue”		N.A.	
5.a.118	Check the DM content on address 8c000001	“835a5aa500”	N.A.	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 61 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 61 OF 88


DATE 08/05/02		TEST CONDUCTOR		PRODUCT ASSURANCE		CUSTOMER	
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE				UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05			
STEP N°	TEST SEQUENCE			EXPECTED VALUE	MEASURED VALUE	REMARKS	
5.a.119	From menu Execute select “CBUG”			CBUG window appears	N.A.		
5.a.120	From menu Execution select “Restart”				N.A.		
5.a.121	Search line “ //Test LowSpeed I/F “ in the program				N.A.		
5.a.122	Double click on “for (i=0; i<10; ++i) { “			“ * “ appears	N.A.		
5.a.123	Search end of the program				N.A.		
5.a.124	Double click on “}“			“ * “ appears	N.A.		
5.a.125	Select HIFI1.exe window			A DOS window appears	N.A.		
5.a.126	Press “S”				N.A.		
5.a.127	Type “1” and press “Enter”				N.A.		
5.a.128	From menu Execution of emulator select “Continue”				N.A.		
5.a.129	From menu Execution of emulator select “Continue”				N.A.		

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 62 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 62 OF 88


DATE 08/05/02		TEST CONDUCTOR		PRODUCT ASSURANCE		CUSTOMER	
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE				UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05			
STEP N°	TEST SEQUENCE			EXPECTED VALUE	MEASURED VALUE	REMARKS	
5.a.130	Check the DM content on address 8c000001			“835a5aa500”	N.A.		
5.a.131	From menu Execute select “CBUG”			CBUG window appears	N.A.		
5.a.132	From menu Execution select “Restart”				N.A.		
5.a.133	Select HIFI1.exe window			A DOS window appears	N.A.		
5.a.134	Press “S”				N.A.		
5.a.135	Type “2” and press “Enter”				N.A.		
5.a.136	From menu Execution of emulator select “Continue”				N.A.		
5.a.137	From menu Execution of emulator select “Continue”				N.A.		
5.a.138	Check the DM content on address 8c000001			“835a5aa500”	N.A.		

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 63 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 63 OF 88


DATE 08/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE		CUSTOMER
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
5.b	Low Speed Link interface (SPIRE configuration)			
5.b.1	Insert the EZ ICE probe in the JTAG plug (JP12) of CPU Board		OK	
5.b.2	Supply electrical power to the unit	Green led on (CPU Board)	OK	
5.b.3	Open the program ADSP-21020 Emulator		OK	
5.b.4	Type Enter two times to end Row JTAG and Opcode Scan Test		OK	
5.b.5	From menu Memory select “Program”	P.M. window appears	OK	
5.b.6	From menu Memory select “Data”	D.M. window appears	OK	
5.b.7	From menu File select “Load File...”	A prompt window appears	OK	
5.b.8	In the HSO folder select “hsoconfc.ach”	“RAM” (left side mem. loc.)	OK	
5.b.9	From menu File select “Load File...”	A prompt window appears	OK	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 64 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 64 OF 88


DATE 08/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE		CUSTOMER
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
5.b.10	In the HSO folder select “memtest.exe”	“RAM” (left side mem. loc.)	OK	
5.b.11	From menu Execute select “CBUG”	CBUG window appears	OK	
5.b.12	From menu Execution select “Restart”		OK	
5.b.13	Search line “ //Test LowSpeed I/F “ in the program		OK	
5.b.14	Double click on “for (i=0; i<10; ++i) { “	“ * “ appears	OK	
5.b.15	Search end of the program		OK	
5.b.16	Double click on “}“	“ * “ appears	OK	
5.b.17	Open the program SPIRE.exe on IFSI Simulator	A DOS window appears	OK	
5.b.18	From menu Execution of emulator select “Continue”		OK	
5.b.19	From menu Execution of emulator select “Continue”		OK	
5.b.20	From menu Data of emulator select “Print”		OK	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 65 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 65 OF 88


DATE 08/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE		CUSTOMER
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
5.b.21	Type “i”		OK	
5.b.22	Select “OK”	8000	8000	
5.b.23	From menu Data of emulator select “Print”		OK	
5.b.24	Type “n_ lsTx”		OK	
5.b.25	Select “OK”	16	16	
5.b.26	From menu Execution of emulator select “Restart”		OK	
5.b.27	Select SPIRE.exe window		OK	
5.b.28	Press “S”		OK	
5.b.29	Type “1” and press “Enter”		OK	
5.b.30	From menu Execution of emulator select “Continue”		OK	
5.b.31	From menu Execution of emulator select “Continue”		OK	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 66 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 66 OF 88


DATE 08/05/02		TEST CONDUCTOR		PRODUCT ASSURANCE		CUSTOMER	
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE				UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05			
STEP N°	TEST SEQUENCE			EXPECTED VALUE	MEASURED VALUE		REMARKS
5.b.32	From menu Data of emulator select “Print”				OK		
5.b.33	Type “i”				OK		
5.b.34	Select “OK”			8000	8000		
5.b.35	From menu Data of emulator select “Print”				OK		
5.b.36	Type “n_ lsTx”				OK		
5.b.37	Select “OK”			16	16		
5.b.38	From menu Execution select “Restart”				OK		
5.b.39	Select SPIRE.exe window				OK		
5.b.40	Press “S”				OK		
5.b.41	Type “2” and press “Enter”				OK		
5.b.42	From menu Execution of emulator select “Continue”				OK		

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 67 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 67 OF 88


DATE 08/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE		CUSTOMER
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
5.b.43	From menu Execution of emulator select “Continue”		OK	
5.b.44	From menu Data of emulator select “Print”		OK	
5.b.45	Type “i”		OK	
5.b.46	Select “OK”	8000	8000	
5.b.47	From menu Data of emulator select “Print”		OK	
5.b.48	Type “n_ lsTx”		OK	
5.b.49	Select “OK”	16	16	
5.b.50	Close the “CBUG” window		OK	
5.b.51	From menu Execution select “Chip Reset”		OK	
5.b.52	Select “OK”		OK	
5.b.53	From menu Execution select “Assembly Breaks”		OK	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 68 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 68 OF 88


DATE 08/05/02		TEST CONDUCTOR		PRODUCT ASSURANCE		CUSTOMER	
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE				UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05			
STEP N°	TEST SEQUENCE			EXPECTED VALUE	MEASURED VALUE	REMARKS	
5.b.54	Select “Delete All”				OK		
5.b.55	From menu File select “Load File...”			A prompt window appears	OK		
5.b.56	In the HSO folder select “hsoconfc.ach”			“RAM” (left side mem. loc.)	OK		
5.b.57	From menu File select “Load File...”			A prompt window appears	OK		
5.b.58	In the HSO folder select “hk_test.exe”			“RAM” (left side mem. loc.)	OK		
5.b.59	From menu Execute select “CBUG”			CBUG window appears	OK		
5.b.60	From menu Execution select “Restart”				OK		
5.b.61	Search line “ //Test LowSpeed I/F “ in the program				OK		
5.b.62	Double click on “for (i=0; i<10; ++i) { “			“ * “ appears	OK		
5.b.63	Search end of the program				OK		
DATE 08/05/02		TEST CONDUCTOR		PRODUCT ASSURANCE		CUSTOMER	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 69 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 69 OF 88


TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
5.b.64	Double click on “}”	“ * “ appears	OK	
5.b.65	Select HIFI1.exe window	A DOS window appears	OK	
5.b.66	Press “S”		OK	
5.b.67	Type “0” and press “Enter”		OK	
5.b.68	From menu Execution of emulator select “Continue”		OK	
5.b.69	From menu Execution of emulator select “Continue”		OK	
5.b.70	Check the DM content on address 8c000001	“835a5aa5”	OK	
5.b.71	From menu Execute select “CBUG”	CBUG window appears	OK	
5.b.72	From menu Execution select “Restart”		OK	
5.b.73	Search line “ //Test LowSpeed I/F “ in the program		OK	
5.b.74	Double click on “for (i=0; i<10; ++i) { “	“ * “ appears	OK	
DATE 08/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE	CUSTOMER	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 70 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 70 OF 88


TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
5.b.75	Search end of the program		OK	
5.b.76	Double click on “}”	“ * “ appears	OK	
5.b.77	Select SPIRE.exe window	A DOS window appears	OK	
5.b.78	Press “S”		OK	
5.b.79	Type “1” and press “Enter”		OK	
5.b.80	From menu Execution of emulator select “Continue”		OK	
5.b.81	From menu Execution of emulator select “Continue”		OK	
5.b.82	Check the DM content on address 8c000001	“835a5aa5” “935a5aa5”	OK	See PVS 01
5.b.83	From menu Execute select “CBUG”	CBUG window appears	OK	
5.b.84	From menu Execution select “Restart”		OK	
5.b.85	Select SPIRE.exe window	A DOS window appears	OK	
DATE 08/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE	CUSTOMER	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 71 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 71 OF 88


TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
5.b.86	Press "S"		OK	
5.b.87	Type "2" and press "Enter"		OK	
5.b.88	From menu Execution of emulator select "Continue"		OK	
5.b.89	From menu Execution of emulator select "Continue"		OK	
5.b.90	Check the DM content on address 8c000001	"835a5aa5" "a35a5aa5"	OK	See PVS 01
DATE 08/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE	CUSTOMER	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 72 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 72 OF 88


TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
6	Analog inputs			
6.1	Insert the EZ ICE probe in the JTAG plug (JP12) of CPU Board		OK	
6.2	Supply electrical power to the unit	Green led on (CPU Board)	OK	
6.3	Open the program ADSP-21020 Emulator		OK	
6.4	Type Enter two times to end Row JTAG and Opcode Scan Test		OK	
6.5	From menu Memory select "Program"	P.M. window appears	OK	
6.6	From menu Memory select "Data"	D.M. window appears	OK	
6.7	From menu File select "Load File..."	A prompt window appears	OK	
6.8	In the HSO folder select "hsoconf.ach"	"RAM" (left side mem. loc.)	OK	
6.9	Set the output of the Power supply to 100 mV		OK	
DATE 09/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE	CUSTOMER	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 73 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 73 OF 88


TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
6.10	Connect the output signal to the AINP0 input P2 pin A10 and short to AGND all the unused Analog inputs		OK	
6.11	In the DM address 8f008000 write "0000000000"		OK	
6.12	Check DM content on address 8f008001	48÷56	50	
6.13	Set the output of the Power supply to 2,5V		OK	
6.14	In the DM address 8f008000 write "0000000000"		OK	
6.15	Check DM content on address 8f008001	7E0÷81E	7F0	
6.16	Set the output of the Power supply to 5V		OK	
6.17	In the DM address 8f008000 write "0000000000"		OK	
6.18	Check DM content on address 8f008001	FD0÷FFF	FDF	
DATE 09/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE	CUSTOMER	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 74 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 74 OF 88


TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
6.19	Repeat the steps from 6.9 to 6.18 using signals AINP1, AINP2, AINP3, AINP4, AINP5 and AINP6 (P2 pin B10, C10, A12, B12, C12 and A14) and writing 1÷6 in the DM address 8f008000		AINP1= (51, 7E7, FE7); AINP2= (54, 7EF, FE9); AINP3= (50, 7E8, FEF); AINP4= (52, 7F0, FEB); AINP5= (49, 7E8, FE4); AINP6= (53, 7E7, FEF).	
6.20	In the DM address 8f008000 write "0000000700"		OK	
6.21	Check DM content on address 8f008001	7E0÷81E	7F2	
DATE 09/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE	CUSTOMER	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 75 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 75 OF 88


TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
7	MIL-STD-1553 Clock generation			
7.1	Connect the probe channel 1 of the digital scope to the pin 19 of U2		OK	
7.2	Verify the clock frequency	16 MHz \pm 1%	16.01 MHz	
DATE 09/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE	CUSTOMER	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 76 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 76 OF 88


TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS
8	MIL-STD-1553 interface			
8.1	Insert CPU board in its own slot (1) on the motherboard		OK	
8.2	Insert PL IF board in its own slot (2) on the motherboard		OK	
8.3	Insert the EZ ICE probe in the JTAG plug of CPU board (JP12)		OK	
8.4	Connect Channel A connector to 1553TE		OK	
8.5	Supply electrical power to the unit	Green led on (CPU board)	OK	
8.6	Open the program ADSP-21020 Emulator		OK	
8.7	Type Enter two times to end Row JTAG and Opcode Scan Test		OK	
8.8	From menu Memory select "Program"	PM window appears	OK	
8.9	From menu Memory select "Data"	DM window appears	OK	
DATE 09/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE	CUSTOMER	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 77 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 77 OF 88


TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE			UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS	
8.10	From menu File select “Load File...”	A prompt window appears	OK		
8.11	In the HSO folder select “boot.ach”		OK		
8.12	From menu File select “Load File...”	A prompt window appears	OK		
8.13	In the HSO folder select “drv1553A.exe”		OK		
8.14	From menu Execution select CBUG	CBUG window appears	OK		
8.15	Open program “Bus-Tools 1553” on 1553TE		OK		
8.16	Double click on BM icon in the Bus.btm window		OK		
8.17	Select “Run” in the Bus Monitor Initialization window		OK		
8.18	Select Channel A and enable RX and TX		OK		
8.19	Select “No” in the Bus Tools Windows Application		OK		
DATE 09/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE		CUSTOMER	
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE		UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05			

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 78 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 78 OF 88


STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS	
8.20	From menu Execution of Emulator select “Restart”		OK		
8.21	From menu Execution of Emulator select “Continue”	Value received by Bus Tool increases from 0000 to AAAA	OK		
8.22	Connect the probe channel 1 oscilloscope with pin 1 of T1		OK		
8.23	Connect the probe channel 2 oscilloscope with pin 3 of T1		OK		
8.24	In the “Math” menu of the oscilloscope set CH1-CH2		OK		
8.25	Verify signal on channel M of the oscilloscope	Sequence of pulses (amplitude 36Vpp minimum, 54Vpp maximum)	53 V	See Printout 01	
8.26	Connect the probe channel 1 oscilloscope with pin 5 of T1		OK		
8.27	Connect the probe channel 2 oscilloscope with pin 7 of T1		OK		
DATE 09/05/02		TEST CONDUCTOR		PRODUCT ASSURANCE	CUSTOMER
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE				UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05	
STEP N°	TEST SEQUENCE	EXPECTED VALUE	MEASURED VALUE	REMARKS	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 79 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 79 OF 88

8.28	Verify signal on channel M of the oscilloscope	Sequence of pulses (amplitude 18Vpp minimum 27Vpp maximum)	26 V	See Printout 02	
8.29	Select “Stop” on “Bus Tools		OK		
8.30	Stop the program on the emulator		OK		
8.31	From menu Execution of Emulator select “Chip Reset”		OK		
8.32	Select “OK”		OK		
8.33	Connect Channel B connector to 1553TE		OK		
8.34	Repeat step from 8.10 to 8.12		OK		
8.35	In the HSO folder select “drv1553B.exe”		OK		
8.36	From menu Execution select CBUG	CBUG window appears	OK		
DATE 09/05/02		TEST CONDUCTOR		PRODUCT ASSURANCE	CUSTOMER
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE				UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05	
STEP N°	TEST SEQUENCE		EXPECTED VALUE	MEASURED VALUE	REMARKS
8.37	From menu Execution of Emulator select “Restart”			OK	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 80 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 80 OF 88

8.38	From menu Execution of Emulator select “Continue”	Value received by Bus Tool increases from 0000 to AAAA	OK		
8.39	Connect the probe channel 1 oscilloscope with pin 1 of T2		OK		
8.40	Connect the probe channel 2 oscilloscope with pin 3 of T2		OK		
8.41	In the “Math” menu of the oscilloscope set CH1-CH2		OK		
8.42	Verify signal on channel M of the oscilloscope	Sequence of pulses (amplitude 36Vpp minimum, 54Vpp maximum)	54 V	See Printout 03	
8.43	Connect the probe channel 1 oscilloscope with pin 5 of T2		OK		
8.44	Connect the probe channel 2 oscilloscope with pin 7 of T2		OK		
DATE 09/05/02		TEST CONDUCTOR		PRODUCT ASSURANCE	CUSTOMER
TITLE: PAYLOAD & SPACECRAFT INTERFACE BOARD TEST PROCEDURE			UNIT UNDER TEST: DPU-EM-200.00-0 S/N: 05		
STEP N°	TEST SEQUENCE		EXPECTED VALUE	MEASURED VALUE	REMARKS
8.45	Verify signal on channel M of the oscilloscope		Sequence of pulses (amplitude 18Vpp minimum 27Vpp maximum)	27 V	See Printout 04

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	TEST PROCEDURE REFERENCE	TEST REPORT REFERENCE
		DOC N°: DPU-PR-CGS-002 ISSUE : 3 DATE : 06/02/2002 PAGE : 81 OF 85	DOC N°: DPU-RP-CGS-032 ISSUE : 1 DATE : 13/05/2002 PAGE : 81 OF 88

DATE 09/05/02	TEST CONDUCTOR	PRODUCT ASSURANCE	CUSTOMER	

 CARLO GAVAZZI SPACE S.p.A.	HSO/FIRST-DPU	DOC N°: DPU-RP-CGS-032 ISSUE :1 DATE: 25/08/2006 PAGE : 83 OF 88
-----------------------------------------------------------------------------------------------------------------	----------------------	---------------------------------------------------------------------------

9 PROCEDURE VARIATION SHEETS

PROCEDURE VARIATION SHEET 01			
Test procedure Ref.: DPU-PR-CGS-002 Issue3		Page revised: 71, 72	Para. revised: (Step) 5.b.82, 5.b.90
<p>Description of changes:</p> <p>5.b.82 EXPECTED VALUE: 835a5aa5 becomes: 935a5aa5</p> <p>5.b.90 EXPECTED VALUE: 835a5aa5 becomes: a35a5aa5</p>			
<p>Reason for changes:</p> <p>The first nibble of the reply word determinates the channel that is replying.</p>			
CONCURRENCE			
TEST COND	P.A.	ENG.	CUSTOMER

 CARLO GAVAZZI SPACE S.p.A.	<h1>HSO/FIRST-DPU</h1>	DOC N°: DPU-RP-CGS-032 ISSUE :1 DATE: 25/08/2006 PAGE : 84 OF 88
-----------------------------------------------------------------------------------------------------------------	------------------------	---------------------------------------------------------------------------

10 CONCLUSIONS

The unit PL IF Board DPU-EM-200.00-0 S/N 05 was tested according to the specification DPU-SP-CGS-002 Issue 1 and following the procedures DPU-PR-CGS-002 Issue3.

The results of the tests are contained in this document. All the measurements are in agreement with the specifications.



CARLO GAVAZZI SPACE S.p.A.

HSO/FIRST-DPU


DOC N°: DPU-RP-CGS-032

ISSUE :1 DATE: 25/08/2006

PAGE : 85 OF 88

11 PRINTOUTS

11.1 Printout 01 (see step 8.25)



M: Primary side 1553

09/05/2002



CARLO GAVAZZI SPACE S.p.A.


HSO/FIRST-DPU

DOC N°: DPU-RP-CGS-032

ISSUE :1 DATE: 25/08/2006

PAGE : 86 OF 88

11.2 Printout 02 (see step 8.28)



M: Secondary side 1553

09/05/2002



CARLO GAVAZZI SPACE S.p.A.


HSO/FIRST-DPU

DOC N°: DPU-RP-CGS-032

ISSUE :1 DATE: 25/08/2006

PAGE : 87 OF 88

11.3 Printout 03 (see step 8.42)



M: Primary side 1553

09/05/2002



CARLO GAVAZZI SPACE S.p.A.


HSO/FIRST-DPU

DOC N°: DPU-RP-CGS-032

ISSUE :1 DATE: 25/08/2006

PAGE : 88 OF 88

11.4 Printout 04 (see step 8.45)



M: Secondary side 1553

09/05/2002