

Switch OFF the SCU Thermometry
 File: H_FCP_SPI_SCUF.xls
 Author: R. Biggins



Procedure Summary

Objectives

The objective of this procedure is to switch OFF the SCU Thermometry

Summary of Constraints

n/a

Spacecraft Configuration

Start of Procedure

SPIRE is in SCU_ON mode

End of Procedure

SPIRE is in DRCU_ON mode

Reference File(s)

Input Command Sequences

Output Command Sequences

HFSSCUF


Referenced Displays

ANDs GRDs SLDs
 SA_6_559
 SA_7_559


Configuration Control Information

DATE	FOP ISSUE	VERSION	MODIFICATION DESCRIPTION	AUTHOR	SPR REF
07/08/2007		1	Created	R. Biggins	
15/01/2008		2	Update due to initial testing against the simulator: - TCs updated due to new DB	R. Biggins	


Switch OFF the SCU Thermometry
 File: H_FCP_SPI_SCUF.xls
 Author: R. Biggins



Procedure Flowchart Overview



Switch OFF the SCU Thermometry
 File: H_FCP_SPI_SCUF.xls
 Author: R. Biggins



Step No.	Time	Activity/Remarks	TC/TLM	Display/ Branch
Beginning of Procedure				
HFSSCUF Switch OFF SCU				
SSID :				
1		Prerequisite check		Next Step: 2
		Verify Telemetry MODE SM00M500	= SCU_ON	AND=SA_6_559
		Verify Telemetry SCUTEMPSTAT SM_1F520	= FFFF <hex>	AND=SA_7_559
		Verify Telemetry SUBKSTAT SMK0F520	= 1 <hex>	AND=SA_7_559
2		Set default start conditions		Next Step: 3
	ET=+00.00.00 UT=+00.00.00	SET_OBS_STEP SET_OBS_STEP Command Parameter(s) : OBSERVATION_STEP SP03N500 TC Control Flags : GBM IL DSE ---- -- -- SSID : 370	SC003500 0 <hex>	
	ET=+00.00.00 UT=+00.00.00	SET_BBID SET_BBID Command Parameter(s) : BUILDING_BLOCK_ID SP01N500 TC Control Flags : GBM IL DSE --- -- -- SSID : 370	SC001500 80010001 <hex>	
	ET=+00.00.02 UT=+00.00.02	SET_OBS_STEP SET_OBS_STEP Command Parameter(s) : OBSERVATION_STEP SP03N500 TC Control Flags : GBM IL DSE --- -- -- SSID : 370	SC003500 1 <hex>	

Switch OFF the SCU Thermometry
 File: H_FCP_SPI_SCUF.xls
 Author: R. Biggins



Step No.	Time	Activity/Remarks	TC/TLM	Display/ Branch
	ET=+00.00.00 UT=+00.00.00	SET_OBSID SET_OBSID Command Parameter(s) : OBSERVATION_ID SP00N500 TC Control Flags : GBM IL DSE --- -- --- SSID : 370	SC000500 B0000000 <hex>	
	ET=+00.00.01 UT=+00.00.01	SET_OBS_STEP SET_OBS_STEP Command Parameter(s) : OBSERVATION_STEP SP03N500 TC Control Flags : GBM IL DSE --- -- --- SSID : 370	SC003500 0 <hex>	
	ET=+00.00.00 UT=+00.00.00	SET_BBID SET_BBID Command Parameter(s) : BUILDING_BLOCK_ID SP01N500 TC Control Flags : GBM IL DSE --- -- --- SSID : 370	SC001500 80000000 <hex>	
	ET=+00.00.01 UT=+00.00.01	SET_OBS_STEP SET_OBS_STEP Command Parameter(s) : OBSERVATION_STEP SP03N500 TC Control Flags : GBM IL DSE --- -- --- SSID : 370	SC003500 0 <hex>	
	ET=+00.00.01 UT=+00.00.01	SET_BBID SET_BBID Command Parameter(s) : BUILDING_BLOCK_ID SP01N500 TC Control Flags : GBM IL DSE --- -- --- SSID : 370	SC001500 80020001 <hex>	

Switch OFF the SCU Thermometry
 File: H_FCP_SPI_SCUF.xls
 Author: R. Biggins



Step No.	Time	Activity/Remarks	TC/TLM	Display/ Branch
	ET=+00.00.02 UT=+00.00.02	SET_OBS_STEP Command Parameter(s) : OBSERVATION_STEP TC Control Flags : SSID : 370	SET_OBS_STEP SP03N500 GBM IL DSE --- -- --- SC003500 1 <hex>	
3		Set procedure conditions		Next Step: 4
	ET=+00.00.01 UT=+00.00.01	RESET_DRCU_COUNTERS TC Control Flags : SSID : 370	RESET_DRCU_COUNTERS GBM IL DSE --- -- --- SCD00505	
	ET=+00.00.01 UT=+00.00.01	SET_OBSID Command Parameter(s) : OBSERVATION_ID TC Control Flags : SSID : 370	SET_OBSID SP00N500 GBM IL DSE --- -- --- SC000500 OBS_ID	
	ET=+00.00.01 UT=+00.00.01	SET_OBS_STEP Command Parameter(s) : OBSERVATION_STEP TC Control Flags : SSID : 370	SET_OBS_STEP SP03N500 GBM IL DSE --- -- --- SC003500 0 <hex>	
	ET=+00.00.01 UT=+00.00.01	SET_BBID Command Parameter(s) : BUILDING_BLOCK_ID TC Control Flags : SSID : 370	SET_BBID SP01N500 GBM IL DSE --- -- --- SC001500 80000000 <hex>	

Switch OFF the SCU Thermometry
File: H_FCP_SPI_SCUF.xls
Author: R. Biggins




Step No.	Time	Activity/Remarks	TC/TLM	Display/ Branch
	ET=+00.00.01 UT=+00.00.01	SET_OBS_STEP SET_OBS_STEP Command Parameter(s) : OBSERVATION_STEP SP03N500 TC Control Flags : GBM IL DSE --- -- SSID : 370	SC003500 0 <hex>	
	ET=+00.00.00 UT=+00.00.00	SET_BBID SET_BBID Command Parameter(s) : BUILDING_BLOCK_ID SP01N500 TC Control Flags : GBM IL DSE --- -- SSID : 370	SC001500 8a0c0001 <hex>	
	ET=+00.00.01 UT=+00.00.01	SET_OBS_MODE SET_OBS_MODE Command Parameter(s) : OBSERVING_MODE SP02N500 TC Control Flags : GBM IL DSE --- -- SSID : 370	SC002500 1ff <hex>	
		Verify Telemetry MODE SM00M500	= SCU_OFF	AND=SA_7_559
4		Switch ON SCU Thermometry		Next Step: 5
	ET=+00.00.01 UT=+00.00.01	Send DRCU command to SetTempOnOff SEND_DRCU_COMMAND Command Parameter(s) : DRCUCOMMAND SPD4N505 OVERRIDE SPD9N505 TC Control Flags : GBM IL DSE --- -- SSID : 370	SCD06505 A0850000 <hex> 0 <hex> (Def)	
		Verify Telemetry SCUTEMPSTAT SM_1F520	= 0000 <hex>	AND=SA_7_559

Switch OFF the SCU Thermometry
File: H_FCP_SPI_SCUF.xls
Author: R. Biggins




Step No.	Time	Activity/Remarks	TC/TLM	Display/ Branch
	ET=+00.00.00 UT=+00.00.00	Send DRCU command to SetSubKOnOff SEND_DRCU_COMMAND Command Parameter(s) : DRCUCOMMAND SPD4N505 OVERRIDE SPD9N505 TC Control Flags : GBM IL DSE --- -- --- SSID : 370	SCD06505 A0860000 <hex> 0 <hex> (Def)	
		Verify Telemetry SUBKSTAT SMK0F520	= 0 <hex>	AND=SA_7_559
	ET=+00.00.01 UT=+00.00.01	Send DRCU command SEND_DRCU_COMMAND Command Parameter(s) : DRCUCOMMAND SPD4N505 OVERRIDE SPD9N505 TC Control Flags : GBM IL DSE --- -- --- SSID : 370	SCD06505 A0C40000 <hex> 0 <hex> (Def)	
	ET=+00.00.00 UT=+00.00.00	Send DRCU command SEND_DRCU_COMMAND Command Parameter(s) : DRCUCOMMAND SPD4N505 OVERRIDE SPD9N505 TC Control Flags : GBM IL DSE --- -- --- SSID : 370	SCD06505 A0C50000 <hex> 0 <hex> (Def)	
	ET=+00.00.01 UT=+00.00.01	Send DRCU command SEND_DRCU_COMMAND Command Parameter(s) : DRCUCOMMAND SPD4N505 OVERRIDE SPD9N505 TC Control Flags : GBM IL DSE --- -- --- SSID : 370	SCD06505 A0C60000 <hex> 0 <hex> (Def)	
	ET=+00.00.00 UT=+00.00.00	Send DRCU command SEND_DRCU_COMMAND Command Parameter(s) : DRCUCOMMAND SPD4N505 OVERRIDE SPD9N505 TC Control Flags : GBM IL DSE --- -- --- SSID : 370	SCD06505 A0C70000 <hex> 0 <hex> (Def)	

Switch OFF the SCU Thermometry
File: H_FCP_SPI_SCUF.xls
Author: R. Biggins




Step No.	Time	Activity/Remarks	TC/TLM	Display/ Branch
	ET=+00.00.01 UT=+00.00.01	Send DRCU command SEND_DRCU_COMMAND Command Parameter(s) : DRCUCOMMAND SPD4N505 OVERRIDE SPD9N505 TC Control Flags : GBM IL DSE --- -- --- SSID : 370	SCD06505 A0C80000 <hex> 0 <hex> (Def)	
	ET=+00.00.00 UT=+00.00.00	Send DRCU command SEND_DRCU_COMMAND Command Parameter(s) : DRCUCOMMAND SPD4N505 OVERRIDE SPD9N505 TC Control Flags : GBM IL DSE --- -- --- SSID : 370	SCD06505 A0CA0000 <hex> 0 <hex> (Def)	
	ET=+00.00.01 UT=+00.00.01	Send DRCU command SEND_DRCU_COMMAND Command Parameter(s) : DRCUCOMMAND SPD4N505 OVERRIDE SPD9N505 TC Control Flags : GBM IL DSE --- -- --- SSID : 370	SCD06505 A0CC0000 <hex> 0 <hex> (Def)	
	ET=+00.00.00 UT=+00.00.00	SET_OBS_MODE SET_OBS_MODE Command Parameter(s) : OBSERVING_MODE SP02N500 TC Control Flags : GBM IL DSE --- -- --- SSID : 370	SC002500 100 <hex>	
		Verify Telemetry MODE SM00M500	= DRCU_ON	AND=SA_7_559
5		Set default end conditions		Next Step: END

Switch OFF the SCU Thermometry
 File: H_FCP_SPI_SCUF.xls
 Author: R. Biggins



Step No.	Time	Activity/Remarks	TC/TLM	Display/ Branch
	ET=+00.00.00 UT=+00.00.00	SET_OBS_STEP SET_OBS_STEP Command Parameter(s) : OBSERVATION_STEP SP03N500 TC Control Flags : GBM IL DSE --- -- --- SSID : 370	SC003500 0 <hex>	
	ET=+00.00.01 UT=+00.00.01	SET_BBID SET_BBID Command Parameter(s) : BUILDING_BLOCK_ID SP01N500 TC Control Flags : GBM IL DSE --- -- --- SSID : 370	SC001500 80000000 <hex>	
	ET=+00.00.02 UT=+00.00.02	SET_OBS_STEP SET_OBS_STEP Command Parameter(s) : OBSERVATION_STEP SP03N500 TC Control Flags : GBM IL DSE --- -- --- SSID : 370	SC003500 0 <hex>	
	ET=+00.00.00 UT=+00.00.00	SET_BBID SET_BBID Command Parameter(s) : BUILDING_BLOCK_ID SP01N500 TC Control Flags : GBM IL DSE --- -- --- SSID : 370	SC001500 80030001 <hex>	
	ET=+00.00.02 UT=+00.00.02	SET_OBS_STEP SET_OBS_STEP Command Parameter(s) : OBSERVATION_STEP SP03N500 TC Control Flags : GBM IL DSE --- -- --- SSID : 370	SC003500 1 <hex>	

Switch OFF the SCU Thermometry
 File: H_FCP_SPI_SCUF.xls
 Author: R. Biggins



Step No.	Time	Activity/Remarks	TC/TLM	Display/ Branch
	ET=+00.00.00 UT=+00.00.00	SET_OBSID SET_OBSID Command Parameter(s) : OBSERVATION_ID SP00N500 TC Control Flags : GBM IL DSE --- -- --- SSID : 370	SC000500 B0000000 <hex>	
	ET=+00.00.01 UT=+00.00.01	SET_OBS_STEP SET_OBS_STEP Command Parameter(s) : OBSERVATION_STEP SP03N500 TC Control Flags : GBM IL DSE --- -- --- SSID : 370	SC003500 0 <hex>	
	ET=+00.00.00 UT=+00.00.00	SET_BBID SET_BBID Command Parameter(s) : BUILDING_BLOCK_ID SP01N500 TC Control Flags : GBM IL DSE --- -- --- SSID : 370	SC001500 80000000 <hex>	

End of Procedure