



HerM33es : Herschel M33 extended survey

PACS Data Products Delivery User's Guide

M. Boquien, C. Kramer
March 1st, 2012

1. Introduction

This document describes the delivery of the PACS photometer high level data products of the Herschel Open Time Key Project HerM33es (Herschel M33 extended survey; P.I.: C. Kramer) to the Herschel Science Center.

In the framework of HerM33es, we use all three instruments onboard the ESA Herschel Space Observatory (Pilbratt, G. L., et al. 2010, A&A, 518, L1) to study the dusty and gaseous ISM in M33. One focus of HerM33es is on maps of the FIR continuum observed with PACS (Poglitsch, A., et al. 2010, A&A, 518, L2) and SPIRE (Griffin, M. J., et al. 2010, A&A, 518, L3), covering the entire galaxy. A second focus lies on observing diagnostic FIR and submillimeter cooling lines [C II], [O I], [N II], and H₂O, toward a 2'×40' strip along the major axis with PACS and HIFI (de Graauw, Th., et al. 2010, A&A, 518, L6).

This delivery includes the PACS imaging of M33. The SPIRE imaging data products have already been delivered in October 2011. More details on the project can be found in the paper by C. Kramer et al. (2010, A&A, 518, 67).

2. PACS Observations, Data Reduction, and the final MAPS

2.1 PACS Observations

M33 was mapped with PACS & SPIRE in parallel mode in two orthogonal directions, in 6.3 h on January 7, 2010. Observations were executed with slow scan speed of 20"/s, covering a region of about 70'×70'. Data were taken simultaneously with the PACS green and red channel, centered on 100 and 160 μm. SPIRE observations were taken simultaneously at 250, 350, and 500 μm.

2.2 PACS Data Reduction

PACS data were reduced in a standard way to level 1 using HIPE 8.0.1:

- Calibration blocks were removed and the latest version of the calibration tree was obtained from HIPE
- Bad and saturated pixels were flagged
- Frames were converted to units of Volt
- Astrometry was added
- Finally flat field correction and conversion to units of Jy was performed

From level 1 data cubes, the maps were made using the Scanamorphos software (Roussel 2012, submitted; <http://www2.iap.fr/users/roussel/herschel/>), version 16. In a first step the HIPE level 1 data cubes were converted to a Scanamorphos-compatible format while preserving the Badpixels, Nonscience, Saturation, and Glitchmask masks. From then we converted the cubes to IDL structures. Scanamorphos was run with the /parallel option.

2.3 PACS Maps

The two maps for each of the PACS bands (100 and 160 μm) are delivered as 5-extension FITS files. For each plane the plate scale is 1.70" and 2.85" at 100 and 160 μm . The 5 planes are:

1. signal map in Jy/pixel,
2. error map in Jy/pixel,
3. total drifts (excluding flux calibration offsets),
4. weight map,
5. signal map weighted to exclude noisy scans.

The absolute flux calibration is about 5%.

Acknowledgments: MB thanks H. Roussel for her outstanding support using Scanamorphos and rapid modifications to adapt it to the specificities of the aforementioned observations.



HerM33es : Herschel M33 extended survey

SPIRE Data Products Delivery User's Guide

E.M. Xilouris, C. Kramer, D. Calzetti
October 4th, 2011

1. Introduction

This document describes the delivery of the high level data products of the Herschel Open Time Key Project HerM33es (Herschel M33 extended survey; P.I.: C. Kramer) to the Herschel Science Center.

In the framework of HerM33es we use all three instruments onboard the ESA Herschel Space Observatory (Pilbratt, G. L., et al. 2010, A&A, 518, L1) to study the dusty and gaseous ISM in M33. One focus of HerM33es is on maps of the FIR continuum observed with PACS (Poglitsch, A., et al. 2010, A&A, 518, L2) and SPIRE (Griffin, M. J., et al. 2010, A&A, 518, L3), covering the entire galaxy. A second focus lies on observing diagnostic FIR and submillimeter cooling lines [C II], [O I], [N II], and H₂O, toward a 2'x40' strip along the major axis with PACS and HIFI (de Graauw, Th., et al. 2010, A&A, 518, L6). This delivery includes the SPIRE imaging of M33.

More details on the project can be found in the paper by C. Kramer et al. (2010, A&A, 518, 67).

2. SPIRE Observations, Data Reduction, and the final Maps

2.1 SPIRE Observations

M33 was mapped with PACS & SPIRE in parallel mode in two orthogonal directions, in 6.3 h on January 7, 2010. Observations were executed with slow scan speed of 20"/s, covering a region of about 70'x70'. Data were taken simultaneously with the PACS green and red channel, centered on 100 and 160 μ m. SPIRE observations were taken simultaneously at 250, 350, and 500 μ m.

2.2 SPIRE Data Reduction

SPIRE data were reduced using HIPE 7.0 with the updated calibration scheme (spire_cal_7_0). Standard detector timeline pipeline was used to remove cosmic rays, flux calibrate the data, and apply temperature drift and response corrections. Then we applied an iterative process to remove residual baseline signals that appear as stripes in the maps (described in detail in Bendo, G. J., et al. 2010, A&A, 518, L65). A "naive" mapping projection was applied to the data and maps with pixel size of 6", 10", and 14" were created for the 250, 350, and 500 μ m data, respectively. Finally, we subtracted median background signals from the images. The factors K4E/K4P (0.9828, 0.9834, 0.9710 for 250, 350 and 500 μ m respectively) have been applied to the data to convert to extended source calibration (see Spire Observer's Manual, version 2.4, page 52). No colour correction has been applied to the data. For the colour correction the user is referred to Table 5.3 of the manual (page 52).

2.3 SPIRE Maps

The three maps for each of the SPIRE bands (250, 350, 500 μm) are delivered as single-extension FITS files. The pixel scale of the SPIRE maps is wavelength-dependent: 6" at 250 μm , 10" at 350 μm , and 14" at 500 μm . The flux units are Jy/beam. The reported resolutions are 18.3"x17.0", 24.7"x23.2" and 37.0"x33.4" for the 250, 350 and 500 μm bands respectively while the average beam area is 423, 751 and 1587 arcsec² for the 250, 350 and 500 μm bands respectively (see Spire Observer's Manual, version 2.4, page 50, Table 5.2). Current flux calibration accuracy (October 2011) is estimated conservatively at $\sim 7\%$, dominated by the 5% absolute uncertainty in the Neptune model. For extended emission, like in the case of M33, the SPIRE flux calibration is now in the regime of $\sim 10\text{-}15\%$ (Spire Observer's Manual, version 2.4, page 55).