

DLCM anomaly
 File: H_CRP_CCU_DLCLCR.xls
 Author: E. Picallo



Procedure Summary

Objectives

This procedure describes the steps to identify and recover from a DLCM anomaly.

A detailed analysis of the possible anomalies during DLCM can be found in HP-2-PANT-AN-0032 "CCU Failure Mode Analyses" (pages 58 to 63), e.g:

- no heater current when DLCM mode is "heating"
- no DLCM heating status in HK although heated correctly (measurement in data set as expected)
- continuous heating status (after the heating period)
- no arm activation or no arm desactivation
- anomalies in current or voltage measurements (not measured, unstable, zero or at full scale...)

The recovery action, according to HP-2-PANT-AN-0032, shall be to switch OFF the CCU that is not operating correctly and use only the other CCU to perform the DLCM.

Summary of Constraints

In case of a permanent CCU failure, it will be switched OFF and declared invalid (i.e. the corresponding sensors and HK data shall not be acquired anymore). Then, only the remaining CCU shall be used for acquisition of cryostat temperatures and pressures, and for DLCM or valves operation.

Spacecraft Configuration

Start of Procedure

CCU A and CCU B ON

End of Procedure

one CCU ON and one CCU OFF

Reference File(s)

Input Command Sequences

Output Command Sequences

Referenced Displays

ANDs GRDs SLDs
 ZAZ9P999

Configuration Control Information

DATE	FOP ISSUE	VERSION	MODIFICATION DESCRIPTION	AUTHOR	SPR REF
------	-----------	---------	--------------------------	--------	---------

Status : Version 2 - Unchanged
 Last Checkin: 06/04/09

DLCM anomaly
File: H_CRP_CCU_DLCR.xls
Author: E. Picallo




24/02/09	2.1	1	Created	E. Picallo	
06/04/09	2.3	2	Step 1 (detection of an anomaly) most likely performed during a DLCM run (H_FCP_CCU_DLCM) comment added	E. Picallo	

DLCM anomaly
File: H_CRP_CCU_DLCR.xls
Author: E. Picallo



Procedure Flowchart Overview



DLCM anomaly
 File: H_CRP_CCU_DLCR.xls
 Author: E. Picallo



Step No.	Time	Activity/Remarks	TC/TLM	Display/ Branch
Beginning of Procedure				
<p><i>TC Seq. Name :HRKDLCR (DLCM anomaly)</i></p> <p><i>TimeTag Type:</i> <i>Sub Schedule ID:</i></p> <p style="text-align: center;"><input type="checkbox"/></p>				
1		Anomaly detection on DLCM		Next Step: 2
		<p>One of the described anomalies in HP-2-PANT-AN-0032 is detected during the DLCM execution, e.g:</p> <ul style="list-style-type: none"> - no heater current when DLCM mode is "heating" - no DLCM heating status in HK although heated correctly (measurement in data set as expected) - continuous heating status (after the heating period) - no arm activation or no arm desactivation - anomalies in current or voltage measurements (not measured, unstable, zero or at full scale...) 		
		<p>So, the detection of a DLCM anomaly most likely will be observed during the execution of procedure H_FCP_CCU_DLCM . For completeness the list of CCU telemetry parameters that can be affected by the anomaly are reported in this step</p>		
1.1		Detection of any anomaly on CCU A parameters during DLCM		<input type="checkbox"/>
1.1.1		Check DLCM status in HK data		<input type="checkbox"/>
		Verify the CCU A arming mode telemetry DLCMHArm_st A KM037300		AND=ZAZ9P999
		Verify State of CCU A DLCM heater Telemetry DLCMheat_stat MA KM634300		AND=ZAZ9P999
		Verify State of CCU A DLCM sequencer (execution phase) DLCM_stat MA KM622300		AND=ZAZ9P999
		Verify CCU A Pre-Post Calibration status Telemetry Pre_post_cal MA KM628300		AND=ZAZ9P999
1.1.2		Check DLCM voltage and current		<input type="checkbox"/>
		Verify Voltage DLCM1 heater CCU A Telemetry CCU_A_DLCM_V KD272300		AND=ZAZ9P999
		Verify Current DLCM1 heater CCU A Telemetry CCU_A_DLCM_I KD273300		AND=ZAZ9P999

DLCM anomaly
 File: H_CRP_CCU_DLCR.xls
 Author: E. Picallo



Step No.	Time	Activity/Remarks	TC/TLM	Display/ Branch
1.1.3		Check DLCM temperature evolution		<input type="checkbox"/>
		Verify DLCM2 temperature Telemetry C100_0_T102 KD200302		AND=ZAZ9P999
		Verify DLCM1 temperature Telemetry C100_0_T105 KD201302		AND=ZAZ9P999
1.1.4		Check DLCM Pre/Post-heating measurement parameters		<input type="checkbox"/>
		Verify Mur of CCU A in pre-heating calibration Telemetry CCU_A_Mur_pre KD600300		AND=ZAZ9P999
		Verify Mu0 of CCU A in pre-heating calibration Telemetry CCU_A_Mu0_pre KD601300		AND=ZAZ9P999
		Verify Mir of CCU A in pre-heating calibration Telemetry CCU_A_Mir_pre KD602300		AND=ZAZ9P999
		Verify Mi0 of CCU A in pre-heating calibration Telemetry CCU_A_Mi0_pre KD603300		AND=ZAZ9P999
		Verify Mi0 of CCU A in post-heating calibration Telemetry CCU_A_Mi0_post KD610300		AND=ZAZ9P999
		Verify Mir of CCU A in post-heating calibration Telemetry CCU_A_Mir_post KD611300		AND=ZAZ9P999
		Verify Mu0 of CCU A in post-heating calibration Telemetry CCU_A_Mu0_post KD612300		AND=ZAZ9P999
		Verify Mur of CCU A in post-heating calibration Telemetry CCU_A_Mur_post KD613300		AND=ZAZ9P999
1.2		Detection of any anomaly on CCU B parameters during DLCM		<input type="checkbox"/>
1.2.1		Check DLCM status in HK data		<input type="checkbox"/>
		Verify the CCU B arming mode telemetry DLCMHArm_st B KM037301		AND=ZAZ9P999
		Verify State of CCU B DLCM heater Telemetry DLCMheat_stat MB KM634301		AND=ZAZ9P999
		Verify State of CCU B DLCM sequencer (execution phase) DLCM_stat MB KM622301		AND=ZAZ9P999
		Verify CCU B Pre-Post Calibration status Telemetry Pre_post_cal MB KM628301		AND=ZAZ9P999

DLCM anomaly
 File: H_CRP_CCU_DLCR.xls
 Author: E. Picallo



Step No.	Time	Activity/Remarks	TC/TLM	Display/ Branch
1.2.2		<i>Check DLCM voltage and current</i>		<input type="checkbox"/>
		Verify Voltage DLCM2 heater CCU B Telemetry CCU_B_DLCM_V KD272301		AND=ZAZ9P999
		Verify Current DLCM2 heater CCU B Telemetry CCU_B_DLCM_I KD273301		AND=ZAZ9P999
1.2.3		<i>Check DLCM temperature evolution</i>		<input type="checkbox"/>
		Verify DLCM1 Temperature Telemetry C100_0_T101 KD200303		AND=ZAZ9P999
		Verify DLCM2 Temperature Telemetry C100_0_T104 KD201303		AND=ZAZ9P999
1.2.4		<i>Check DLCM Pre/Post-heating measurement parameters</i>		<input type="checkbox"/>
		Verify Mur of CCU B in pre-heating calibration Telemetry CCU_B_Mur_pre KD600301		AND=ZAZ9P999
		Verify Mu0 of CCU B in pre-heating calibration Telemetry CCU_B_Mu0_pre KD601301		AND=ZAZ9P999
		Verify Mir of CCU B in pre-heating calibration Telemetry CCU_B_Mir_pre KD602301		AND=ZAZ9P999
		Verify Mi0 of CCU B in pre-heating calibration Telemetry CCU_B_Mi0_pre KD603301		AND=ZAZ9P999
		Verify Mi0 of CCU B in post-heating calibration Telemetry CCU_B_Mi0_post KD610301		AND=ZAZ9P999
		Verify Mir of CCU B in post-heating calibration Telemetry CCU_B_Mir_post KD611301		AND=ZAZ9P999
		Verify Mu0 of CCU B in post-heating calibration Telemetry CCU_B_Mu0_post KD612301		AND=ZAZ9P999
		Verify Mur of CCU B in post-heating calibration Telemetry CCU_B_Mur_post KD613301		AND=ZAZ9P999
2		<i>Switch OFF the failed CCU</i>		Next Step: 3
		Call the contingency procedure H_CRP_CCU_CCUR to switch OFF the failed CCU		
		Execute Procedure: H_CRP_CCU_CCUR CCU Anomaly		

DLCM anomaly
 File: H_CRP_CCU_DLCR.xls
 Author: E. Picallo



Step No.	Time	Activity/Remarks	TC/TLM	Display/ Branch
3		<i>DLCM was performed using both CCU A & B (yes/no)?</i>		Next Step: yes 4 no 5
4		<i>Use only the data coming from the valid CCU to estimate the helium content</i>		Next Step: END
5		<i>Perform DLCM using the other CCU</i>		Next Step: END
		In the called procedure, H_FCP_CCU_DLCM, choose the option to perform a DLCM using only the healthy CCU.		
		Execute Procedure: H_FCP_CCU_DLCM CCU DLCM		
End of Procedure				