

Tx2 and TM encoder in use configuration for MR
File: H_CRP_TTC_T2MR.xls
Author: E. Picallo



Procedure Summary

Objectives

This procedure describes the steps needed to change the TM bit rate to 150 kbps when the downlink and the uplink are already established.

This procedure does not use the logical addressing, thus must be executed under Ground control (the commands used cannot be inserted in the MTL).

Summary of Constraints

XPND2 and the TM encoder are configured using TC(8,4,115,9), TC(8,4,115,18) and TC(8,4,115,20), thus the status of the ASW function "TTC Management" has to be "running".

Note that:

- the value of the TM modulation index is always 1.2;
- the value of the RNG modulation index, when CM and RNG are ON, is always 0.6;
- the value of the Output power level is always - 4dBm;
- the External reference and Internal bit pattern generator are always OFF.

If the ASW function "On board Scheduling" is stopped the TCs can not be added into the MTL.
If the function is running, up to four time-tagged TCs are released per second.

It is recommended to command ON the coherent and ranging mode parameters by Ground only after confirmation of onboard lock.

Spacecraft Configuration

Start of Procedure

CDMU in default configuration;
Downlink active via TX2 and TWTA2;
TM bit rate set to any value;
XPND configuration: CM OFF or CM ON and RNG OFF or CM ON and RNG ON.

End of Procedure

CDMU in default configuration;
Downlink active via TX2 and TWTA2;
TM bit rate equal to 150 kbps;
XPND configuration: CM and RNG unchanged.

Reference File(s)

Input Command Sequences

Output Command Sequences

HRRT2MR1
HRRT2MR2
HRRT2MR3

Referenced Displays

Tx2 and TM encoder in use configuration for MR
 File: H_CRP_TTC_T2MR.xls
 Author: E. Picallo



ANDs **GRDs** **SLDs**
 ZAZ7I999
 ZAZ7J999


Configuration Control Information

DATE	FOP ISSUE	VERSION	MODIFICATION DESCRIPTION	AUTHOR	SPR REF
30/07/08	1	1	Created	E. Picallo	
16/12/08	2	2	TC DCT18170 Configure Xpnd mask update TCs XPND Config & TM ENC Config blocked TC XPND Config do not update CM and RM	E. Picallo	
07/04/09	2.3	3	Step 6: wrong command description, the TC DC03F170 is a TC(8,4,115,17) corrected	E. Picallo	

Tx2 and TM encoder in use configuration for MR
 File: H_CRP_TTC_T2MR.xls
 Author: E. Picallo



Procedure Flowchart Overview



Tx2 and TM encoder in use configuration for MR
 File: H_CRP_TTC_T2MR.xls
 Author: E. Picallo



Step No.	Time	Activity/Remarks	TC/TLM	Display/ Branch
Beginning of Procedure				
TC Seq. Name :HRRT2MRI (Tx2 for MR initial) Tx2 and TM encoder in use configuration for MR TimeTag Type: N Sub Schedule ID: <input type="checkbox"/>				
1		Acquire ENC and XPND status		Next Step: 2
		Verify RX2 AGC Level Telemetry X2 AGC TMuplnc RMB41442	>= -141.0 dbmW	AND=ZAZ7I999
		Verify RX2 Lock statusTelemetry X2 Rx Lock - RL RMB45442	= Locked	AND=ZAZ7I999
		Verify Telemetry TME_BITRATE DEMRF160		AND=ZAZ7J999
		Verify Low Rate-1 status Telemetry X2 LowRate-1 MD RMB51442		AND=ZAZ7I999
		Verify Low Rate-2 status Telemetry X2 LowRate-2 MD RMB52442		AND=ZAZ7I999
		Verify Medium Rate Modulator status Telemetry X2 MedRate-MRM RMB50442	= OFF	AND=ZAZ7I999
		Verify High Rate Modulator status Telemetry X2 HIRateMD-HRM RMB49442		AND=ZAZ7I999
		Verify Coherent Mode status Telemetry X2 Coher MOD-CM RMB47442		AND=ZAZ7I999
		Verify Ranging Modulator status Telemetry X2 Rang MD - RM RMB48442		AND=ZAZ7I999
2		Current TM bit rate? LR1 (500 bps) LR2 (5K kps) HR (1.5 Mbps)		Next Step: LR1 3 LR2 8 HR 12
TC Seq. Name :HRRT2MR1 (Tx2 from LR1 to MR) Tx2 and TM encoder configuration from LR1 to MR TimeTag Type: N Sub Schedule ID: <input type="checkbox"/>				
3		Warning		Next Step: 4

Tx2 and TM encoder in use configuration for MR
 File: H_CRP_TTC_T2MR.xls
 Author: E. Picallo



Step No.	Time	Activity/Remarks	TC/TLM	Display/ Branch																																																																																																																																						
		<p>The current TM bit rate is not MR. Therefore a TM bit rate switch will be performed.</p> <p>A specific feature of this switching, is that it shall be done by several TC. Specifically, separate TC will be necessary to set-up the TM encoder, and the XPND.</p> <p>In the time interval between those TC, the TM flux will be some TM disruption, and no CLCW will be available to acknowledge the TC. Therefore send those TCs blocked (encoded in a single CLTU) or send TCs TT.</p>																																																																																																																																								
4		<p>Set the parameters and send TC(8,4,115,9) to configure the XPND2</p>		Next Step: 5																																																																																																																																						
		<p>Execute Telecommand</p> <p style="text-align: center;">XpndConfigure_Templ</p> <p>Command Parameter(s) :</p> <table border="0"> <tr> <td>XpndId</td> <td>DH018170</td> <td>XpndB</td> <td></td> </tr> <tr> <td>XpndConfMask1Unus</td> <td>DH220170</td> <td>11 <bin></td> <td></td> </tr> <tr> <td>XpndConfMask1_ER</td> <td>DH221170</td> <td>ON</td> <td></td> </tr> <tr> <td>XpndConfMask1_CM</td> <td>DH222170</td> <td>OFF (Def)</td> <td></td> </tr> <tr> <td>XpndConfMask1_RM</td> <td>DH223170</td> <td>OFF (Def)</td> <td></td> </tr> <tr> <td>XpndConfMask1_HRM</td> <td>DH224170</td> <td>ON</td> <td></td> </tr> <tr> <td>XpndConfMask1_MRM</td> <td>DH225170</td> <td>ON</td> <td></td> </tr> <tr> <td>XpndConfMask1LRM1</td> <td>DH226170</td> <td>ON</td> <td></td> </tr> <tr> <td>XpndConfMask1LRM2</td> <td>DH227170</td> <td>ON</td> <td></td> </tr> <tr> <td>XpndConfMask1_RMI</td> <td>DH228170</td> <td>Update</td> <td></td> </tr> <tr> <td>XpndConfMask1_TMI</td> <td>DH229170</td> <td>Update</td> <td></td> </tr> <tr> <td colspan="4"> </td> </tr> <tr> <td>XpndConfMask2_PG</td> <td>DH230170</td> <td>ON</td> <td></td> </tr> <tr> <td>XpndConfMask2Unus</td> <td>DH231170</td> <td>1111111111 <bin></td> <td></td> </tr> <tr> <td>XpndConfMask2OPLS</td> <td>DH232170</td> <td>Update</td> <td></td> </tr> <tr> <td>XpndConfDW1Unus</td> <td>DH020170</td> <td>0 <dec> (Def)</td> <td></td> </tr> <tr> <td>XpndConfDW1_ER</td> <td>DH021170</td> <td>OFF (Def)</td> <td></td> </tr> <tr> <td>XpndConfDW1_CM</td> <td>DH022170</td> <td>OFF (Def)</td> <td></td> </tr> <tr> <td>XpndConfDW1_RM</td> <td>DH023170</td> <td>OFF (Def)</td> <td></td> </tr> <tr> <td>XpndConfDW1_HRM</td> <td>DH024170</td> <td>OFF (Def)</td> <td></td> </tr> <tr> <td>XpndConfDW1_MRM</td> <td>DH025170</td> <td>ON</td> <td></td> </tr> <tr> <td>XpndConfDW1LRM1</td> <td>DH026170</td> <td>OFF (Def)</td> <td></td> </tr> <tr> <td>XpndConfDW1LRM2</td> <td>DH027170</td> <td>OFF (Def)</td> <td></td> </tr> <tr> <td>XpndConfDW1_RMI</td> <td>DH028170</td> <td>0.6</td> <td></td> </tr> <tr> <td>XpndConfDW1_TMI</td> <td>DH029170</td> <td>1.2</td> <td></td> </tr> <tr> <td>XpndConfDW2_PG</td> <td>DH030170</td> <td>OFF (Def)</td> <td></td> </tr> <tr> <td>XpndConfDW2Unus</td> <td>DH031170</td> <td>0 <dec> (Def)</td> <td></td> </tr> <tr> <td colspan="4"> </td> </tr> <tr> <td>XpndConfDW2OPLS</td> <td>DH032170</td> <td>-4</td> <td></td> </tr> <tr> <td colspan="4">TC Control Flags :</td> </tr> <tr> <td></td> <td>GBM IL DSE</td> <td></td> <td></td> </tr> <tr> <td></td> <td>-SY -- ---</td> <td></td> <td></td> </tr> <tr> <td colspan="4">Subsch. ID : 10</td> </tr> <tr> <td colspan="4">Det. descr. : TEMPLATE Configure Xpnd TC(8,4,115,9)</td> </tr> </table>	XpndId	DH018170	XpndB		XpndConfMask1Unus	DH220170	11 <bin>		XpndConfMask1_ER	DH221170	ON		XpndConfMask1_CM	DH222170	OFF (Def)		XpndConfMask1_RM	DH223170	OFF (Def)		XpndConfMask1_HRM	DH224170	ON		XpndConfMask1_MRM	DH225170	ON		XpndConfMask1LRM1	DH226170	ON		XpndConfMask1LRM2	DH227170	ON		XpndConfMask1_RMI	DH228170	Update		XpndConfMask1_TMI	DH229170	Update						XpndConfMask2_PG	DH230170	ON		XpndConfMask2Unus	DH231170	1111111111 <bin>		XpndConfMask2OPLS	DH232170	Update		XpndConfDW1Unus	DH020170	0 <dec> (Def)		XpndConfDW1_ER	DH021170	OFF (Def)		XpndConfDW1_CM	DH022170	OFF (Def)		XpndConfDW1_RM	DH023170	OFF (Def)		XpndConfDW1_HRM	DH024170	OFF (Def)		XpndConfDW1_MRM	DH025170	ON		XpndConfDW1LRM1	DH026170	OFF (Def)		XpndConfDW1LRM2	DH027170	OFF (Def)		XpndConfDW1_RMI	DH028170	0.6		XpndConfDW1_TMI	DH029170	1.2		XpndConfDW2_PG	DH030170	OFF (Def)		XpndConfDW2Unus	DH031170	0 <dec> (Def)						XpndConfDW2OPLS	DH032170	-4		TC Control Flags :					GBM IL DSE				-SY -- ---			Subsch. ID : 10				Det. descr. : TEMPLATE Configure Xpnd TC(8,4,115,9)			
XpndId	DH018170	XpndB																																																																																																																																								
XpndConfMask1Unus	DH220170	11 <bin>																																																																																																																																								
XpndConfMask1_ER	DH221170	ON																																																																																																																																								
XpndConfMask1_CM	DH222170	OFF (Def)																																																																																																																																								
XpndConfMask1_RM	DH223170	OFF (Def)																																																																																																																																								
XpndConfMask1_HRM	DH224170	ON																																																																																																																																								
XpndConfMask1_MRM	DH225170	ON																																																																																																																																								
XpndConfMask1LRM1	DH226170	ON																																																																																																																																								
XpndConfMask1LRM2	DH227170	ON																																																																																																																																								
XpndConfMask1_RMI	DH228170	Update																																																																																																																																								
XpndConfMask1_TMI	DH229170	Update																																																																																																																																								
XpndConfMask2_PG	DH230170	ON																																																																																																																																								
XpndConfMask2Unus	DH231170	1111111111 <bin>																																																																																																																																								
XpndConfMask2OPLS	DH232170	Update																																																																																																																																								
XpndConfDW1Unus	DH020170	0 <dec> (Def)																																																																																																																																								
XpndConfDW1_ER	DH021170	OFF (Def)																																																																																																																																								
XpndConfDW1_CM	DH022170	OFF (Def)																																																																																																																																								
XpndConfDW1_RM	DH023170	OFF (Def)																																																																																																																																								
XpndConfDW1_HRM	DH024170	OFF (Def)																																																																																																																																								
XpndConfDW1_MRM	DH025170	ON																																																																																																																																								
XpndConfDW1LRM1	DH026170	OFF (Def)																																																																																																																																								
XpndConfDW1LRM2	DH027170	OFF (Def)																																																																																																																																								
XpndConfDW1_RMI	DH028170	0.6																																																																																																																																								
XpndConfDW1_TMI	DH029170	1.2																																																																																																																																								
XpndConfDW2_PG	DH030170	OFF (Def)																																																																																																																																								
XpndConfDW2Unus	DH031170	0 <dec> (Def)																																																																																																																																								
XpndConfDW2OPLS	DH032170	-4																																																																																																																																								
TC Control Flags :																																																																																																																																										
	GBM IL DSE																																																																																																																																									
	-SY -- ---																																																																																																																																									
Subsch. ID : 10																																																																																																																																										
Det. descr. : TEMPLATE Configure Xpnd TC(8,4,115,9)																																																																																																																																										

 | |

Tx2 and TM encoder in use configuration for MR
 File: H_CRP_TTC_T2MR.xls
 Author: E. Picallo



Step No.	Time	Activity/Remarks	TC/TLM	Display/ Branch
		Notice that in the configuration of the XPND the coherent mode is unchanged. Although if the receiver losses lock for more than 0.2 s, then the transponder reverts back to noncoherent mode. When receiver locks again, the transponder automatically returns to the memorised mode.		
5		Send TC(8,4,115,20) to configure the TM encoder to 150 kbps		Next Step: 6
		Execute Telecommand TtcConfTmEncInUseMedium TC Control Flags : <div style="text-align: right;">GBM IL DSE -E- -- ---</div> Subsch. ID : 10 Det. descr. : TTC: Config TM Enc In Use Mode Medium 150 kbps, TC(8,4,115,20)	DC22F170	
6		Send TC(8,4,115,17) to switch OFF the TM subsampling		Next Step: 7
		Execute Telecommand TtcSwitchTmSubsamploff TC Control Flags : <div style="text-align: right;">GBM IL DSE --Y -- ---</div> Subsch. ID : 10 Det. descr. : TTC: Switch TM Subsampling Off TC(8,4,115,17)	DC03F170	
7		Enable the downlink of all periodic HK packets		Next Step: 15
		Execute procedures H_FCP_DHS_1003 (Set the default values for the TRANSMIT/STORAGE flags with TC(14,5)) H_FCP_DHS_1009 (Enable the default HK (essential + periodic) packets with TC(14,1))		
TC Seq. Name :HRRT2MR2 (Tx2 from LR2 to MR) Tx2 and TM encoder in use configuration from LR2 to MR TimeTag Type: N Sub Schedule ID: <input type="checkbox"/>				

Tx2 and TM encoder in use configuration for MR
 File: H_CRP_TTC_T2MR.xls
 Author: E. Picallo



Step No.	Time	Activity/Remarks	TC/TLM	Display/ Branch																																																																																																																																										
8		Warning		Next Step: 9																																																																																																																																										
		<p>The current TM bit rate is not MR. Therefore a TM bit rate switch will be performed.</p> <p>A specific feature of this switching, is that it shall be done by several TC. Specifically, separate TC will be necessary to set-up the TM encoder, and the XPND.</p> <p>In the time interval between those TC, the TM flux will be some TM disruption, and no CLCW will be available to acknowledge the TC. Therefore send those TCs blocked (encoded in a single CLTU) or send TCs TT.</p>																																																																																																																																												
9		Set the parameters and send TC(8,4,115,9) to configure the XPND2		Next Step: 10																																																																																																																																										
		<p>Execute Telecommand</p> <p style="text-align: center;">XpndConfigure_Templ</p> <p>Command Parameter(s) :</p> <table border="0"> <tr> <td>XpndId</td> <td>DH018170</td> <td>XpndB</td> <td></td> </tr> <tr> <td>XpndConfMask1Unus</td> <td>DH220170</td> <td>11 <bin></td> <td></td> </tr> <tr> <td>XpndConfMask1_ER</td> <td>DH221170</td> <td>ON</td> <td></td> </tr> <tr> <td>XpndConfMask1_CM</td> <td>DH222170</td> <td>OFF (Def)</td> <td></td> </tr> <tr> <td>XpndConfMask1_RM</td> <td>DH223170</td> <td>OFF (Def)</td> <td></td> </tr> <tr> <td>XpndConfMask1_HRM</td> <td>DH224170</td> <td>ON</td> <td></td> </tr> <tr> <td>XpndConfMask1_MRM</td> <td>DH225170</td> <td>ON</td> <td></td> </tr> <tr> <td>XpndConfMask1LRM1</td> <td>DH226170</td> <td>ON</td> <td></td> </tr> <tr> <td>XpndConfMask1LRM2</td> <td>DH227170</td> <td>ON</td> <td></td> </tr> <tr> <td>XpndConfMask1_RMI</td> <td>DH228170</td> <td>Update</td> <td></td> </tr> <tr> <td>XpndConfMask1_TMI</td> <td>DH229170</td> <td>Update</td> <td></td> </tr> <tr> <td colspan="4"> </td> </tr> <tr> <td>XpndConfMask2_PG</td> <td>DH230170</td> <td>ON</td> <td></td> </tr> <tr> <td>XpndConfMask2Unus</td> <td>DH231170</td> <td>1111111111 <bin></td> <td></td> </tr> <tr> <td>XpndConfMask2OPLS</td> <td>DH232170</td> <td>Update</td> <td></td> </tr> <tr> <td>XpndConfDW1Unus</td> <td>DH020170</td> <td>0 <dec> (Def)</td> <td></td> </tr> <tr> <td>XpndConfDW1_ER</td> <td>DH021170</td> <td>OFF (Def)</td> <td></td> </tr> <tr> <td>XpndConfDW1_CM</td> <td>DH022170</td> <td>OFF (Def)</td> <td></td> </tr> <tr> <td>XpndConfDW1_RM</td> <td>DH023170</td> <td>OFF (Def)</td> <td></td> </tr> <tr> <td>XpndConfDW1_HRM</td> <td>DH024170</td> <td>OFF (Def)</td> <td></td> </tr> <tr> <td>XpndConfDW1_MRM</td> <td>DH025170</td> <td>ON</td> <td></td> </tr> <tr> <td>XpndConfDW1LRM1</td> <td>DH026170</td> <td>OFF (Def)</td> <td></td> </tr> <tr> <td>XpndConfDW1LRM2</td> <td>DH027170</td> <td>OFF (Def)</td> <td></td> </tr> <tr> <td>XpndConfDW1_RMI</td> <td>DH028170</td> <td>0.6</td> <td></td> </tr> <tr> <td>XpndConfDW1_TMI</td> <td>DH029170</td> <td>1.2</td> <td></td> </tr> <tr> <td>XpndConfDW2_PG</td> <td>DH030170</td> <td>OFF (Def)</td> <td></td> </tr> <tr> <td>XpndConfDW2Unus</td> <td>DH031170</td> <td>0 <dec> (Def)</td> <td></td> </tr> <tr> <td colspan="4"> </td> </tr> <tr> <td>XpndConfDW2OPLS</td> <td>DH032170</td> <td>-4</td> <td></td> </tr> <tr> <td colspan="4"> </td> </tr> <tr> <td colspan="4">TC Control Flags :</td> </tr> <tr> <td></td> <td>GBM IL DSE</td> <td></td> <td></td> </tr> <tr> <td></td> <td>-SY -- ---</td> <td></td> <td></td> </tr> <tr> <td colspan="4">Subsch. ID : 10</td> </tr> <tr> <td colspan="4">Det. descr. : TEMPLATE Configure Xpnd TC(8,4,115,9)</td> </tr> </table>	XpndId	DH018170	XpndB		XpndConfMask1Unus	DH220170	11 <bin>		XpndConfMask1_ER	DH221170	ON		XpndConfMask1_CM	DH222170	OFF (Def)		XpndConfMask1_RM	DH223170	OFF (Def)		XpndConfMask1_HRM	DH224170	ON		XpndConfMask1_MRM	DH225170	ON		XpndConfMask1LRM1	DH226170	ON		XpndConfMask1LRM2	DH227170	ON		XpndConfMask1_RMI	DH228170	Update		XpndConfMask1_TMI	DH229170	Update						XpndConfMask2_PG	DH230170	ON		XpndConfMask2Unus	DH231170	1111111111 <bin>		XpndConfMask2OPLS	DH232170	Update		XpndConfDW1Unus	DH020170	0 <dec> (Def)		XpndConfDW1_ER	DH021170	OFF (Def)		XpndConfDW1_CM	DH022170	OFF (Def)		XpndConfDW1_RM	DH023170	OFF (Def)		XpndConfDW1_HRM	DH024170	OFF (Def)		XpndConfDW1_MRM	DH025170	ON		XpndConfDW1LRM1	DH026170	OFF (Def)		XpndConfDW1LRM2	DH027170	OFF (Def)		XpndConfDW1_RMI	DH028170	0.6		XpndConfDW1_TMI	DH029170	1.2		XpndConfDW2_PG	DH030170	OFF (Def)		XpndConfDW2Unus	DH031170	0 <dec> (Def)						XpndConfDW2OPLS	DH032170	-4						TC Control Flags :					GBM IL DSE				-SY -- ---			Subsch. ID : 10				Det. descr. : TEMPLATE Configure Xpnd TC(8,4,115,9)			
XpndId	DH018170	XpndB																																																																																																																																												
XpndConfMask1Unus	DH220170	11 <bin>																																																																																																																																												
XpndConfMask1_ER	DH221170	ON																																																																																																																																												
XpndConfMask1_CM	DH222170	OFF (Def)																																																																																																																																												
XpndConfMask1_RM	DH223170	OFF (Def)																																																																																																																																												
XpndConfMask1_HRM	DH224170	ON																																																																																																																																												
XpndConfMask1_MRM	DH225170	ON																																																																																																																																												
XpndConfMask1LRM1	DH226170	ON																																																																																																																																												
XpndConfMask1LRM2	DH227170	ON																																																																																																																																												
XpndConfMask1_RMI	DH228170	Update																																																																																																																																												
XpndConfMask1_TMI	DH229170	Update																																																																																																																																												
XpndConfMask2_PG	DH230170	ON																																																																																																																																												
XpndConfMask2Unus	DH231170	1111111111 <bin>																																																																																																																																												
XpndConfMask2OPLS	DH232170	Update																																																																																																																																												
XpndConfDW1Unus	DH020170	0 <dec> (Def)																																																																																																																																												
XpndConfDW1_ER	DH021170	OFF (Def)																																																																																																																																												
XpndConfDW1_CM	DH022170	OFF (Def)																																																																																																																																												
XpndConfDW1_RM	DH023170	OFF (Def)																																																																																																																																												
XpndConfDW1_HRM	DH024170	OFF (Def)																																																																																																																																												
XpndConfDW1_MRM	DH025170	ON																																																																																																																																												
XpndConfDW1LRM1	DH026170	OFF (Def)																																																																																																																																												
XpndConfDW1LRM2	DH027170	OFF (Def)																																																																																																																																												
XpndConfDW1_RMI	DH028170	0.6																																																																																																																																												
XpndConfDW1_TMI	DH029170	1.2																																																																																																																																												
XpndConfDW2_PG	DH030170	OFF (Def)																																																																																																																																												
XpndConfDW2Unus	DH031170	0 <dec> (Def)																																																																																																																																												
XpndConfDW2OPLS	DH032170	-4																																																																																																																																												
TC Control Flags :																																																																																																																																														
	GBM IL DSE																																																																																																																																													
	-SY -- ---																																																																																																																																													
Subsch. ID : 10																																																																																																																																														
Det. descr. : TEMPLATE Configure Xpnd TC(8,4,115,9)																																																																																																																																														

 | |

Tx2 and TM encoder in use configuration for MR
 File: H_CRP_TTC_T2MR.xls
 Author: E. Picallo



Step No.	Time	Activity/Remarks	TC/TLM	Display/ Branch
		Notice that in the configuration of the XPND the coherent mode is unchanged. Although if the receiver losses lock for more than 0.2 s, then the transponder reverts back to noncoherent mode. When receiver locks again, the transponder automatically returns to the memorised mode.		
10		Send TC(8,4,115,20) to configure the TM encoder to 150 kbps		Next Step: 11
		Execute Telecommand TtcConfTmEncInUseMedium TC Control Flags : GBM IL DSE -E- - - - Subsch. ID : 10 Det. descr. : TTC: Config TM Enc In Use Mode Medium 150 kbps, TC(8,4,115,20)	DC22F170	
11		Enable the downlink of all periodic HK packets		Next Step: 15
		Execute procedures H_FCP_DHS_1003 (Set the default values for the TRANSMIT/STORAGE flags with TC(14,5)) H_FCP_DHS_1009 (Enable the default HK (essential + periodic) packets with TC(14,1))		
TC Seq. Name :HRRT2MR3 (Tx2 from HR to MR) TimeTag Type: N Sub Schedule ID: <input type="checkbox"/>				
12		Warning		Next Step: 13
		The current TM bit rate is not MR. Therefore a TM bit rate switch will be performed. A specific feature of this switching, is that it shall be done by several TC. Specifically, separate TC will be necessary to set-up the TM encoder, and the XPND. In the time interval between those TC, the TM flux will be some TM disruption, and no CLCW will be available to acknowledge the TC. Therefore send those TCs blocked (encoded in a single CLTU) or send TCs TT.		

Tx2 and TM encoder in use configuration for MR
 File: H_CRP_TTC_T2MR.xls
 Author: E. Picallo



Step No.	Time	Activity/Remarks	TC/TLM	Display/ Branch																																																																																																																												
13		Set the parameters and send TC(8,4,115,9) to configure the XPND2		Next Step: 14																																																																																																																												
		Execute Telecommand <p style="text-align: right;">XpndConfigure_Templ</p> Command Parameter(s) : <table style="width: 100%; border-collapse: collapse;"> <tr><td style="width: 30%;">XpndId</td><td style="width: 20%;">DH018170</td><td style="width: 30%;">XpndB</td><td style="width: 20%;">DCT18170</td></tr> <tr><td>XpndConfMask1Unus</td><td>DH220170</td><td>11 <bin></td><td></td></tr> <tr><td>XpndConfMask1_ER</td><td>DH221170</td><td>ON</td><td></td></tr> <tr><td>XpndConfMask1_CM</td><td>DH222170</td><td>OFF (Def)</td><td></td></tr> <tr><td>XpndConfMask1_RM</td><td>DH223170</td><td>OFF (Def)</td><td></td></tr> <tr><td>XpndConfMask1_HRM</td><td>DH224170</td><td>ON</td><td></td></tr> <tr><td>XpndConfMask1_MRM</td><td>DH225170</td><td>ON</td><td></td></tr> <tr><td>XpndConfMask1LRM1</td><td>DH226170</td><td>ON</td><td></td></tr> <tr><td>XpndConfMask1LRM2</td><td>DH227170</td><td>ON</td><td></td></tr> <tr><td>XpndConfMask1_RMI</td><td>DH228170</td><td>Update</td><td></td></tr> <tr><td>XpndConfMask1_TMI</td><td>DH229170</td><td>Update</td><td></td></tr> <tr><td colspan="4"> </td></tr> <tr><td>XpndConfMask2_PG</td><td>DH230170</td><td>ON</td><td></td></tr> <tr><td>XpndConfMask2Unus</td><td>DH231170</td><td>1111111111 <bin></td><td></td></tr> <tr><td>XpndConfMask2OPLS</td><td>DH232170</td><td>Update</td><td></td></tr> <tr><td>XpndConfDW1Unus</td><td>DH020170</td><td>0 <dec> (Def)</td><td></td></tr> <tr><td>XpndConfDW1_ER</td><td>DH021170</td><td>OFF (Def)</td><td></td></tr> <tr><td>XpndConfDW1_CM</td><td>DH022170</td><td>OFF (Def)</td><td></td></tr> <tr><td>XpndConfDW1_RM</td><td>DH023170</td><td>OFF (Def)</td><td></td></tr> <tr><td>XpndConfDW1_HRM</td><td>DH024170</td><td>OFF (Def)</td><td></td></tr> <tr><td>XpndConfDW1_MRM</td><td>DH025170</td><td>ON</td><td></td></tr> <tr><td>XpndConfDW1LRM1</td><td>DH026170</td><td>OFF (Def)</td><td></td></tr> <tr><td>XpndConfDW1LRM2</td><td>DH027170</td><td>OFF (Def)</td><td></td></tr> <tr><td>XpndConfDW1_RMI</td><td>DH028170</td><td>0.6</td><td></td></tr> <tr><td>XpndConfDW1_TMI</td><td>DH029170</td><td>1.2</td><td></td></tr> <tr><td>XpndConfDW2_PG</td><td>DH030170</td><td>OFF (Def)</td><td></td></tr> <tr><td>XpndConfDW2Unus</td><td>DH031170</td><td>0 <dec> (Def)</td><td></td></tr> <tr><td colspan="4"> </td></tr> <tr><td>XpndConfDW2OPLS</td><td>DH032170</td><td>-4</td><td></td></tr> </table> TC Control Flags : <table style="width: 100%; border-collapse: collapse;"> <tr><td style="width: 30%;"></td><td style="width: 20%;">GBM IL DSE</td><td style="width: 30%;"></td><td style="width: 20%;"></td></tr> <tr><td></td><td>-SY -- ---</td><td></td><td></td></tr> </table> Subsch. ID : 10 Det. descr. : TEMPLATE Configure Xpnd TC(8,4,115,9)	XpndId	DH018170	XpndB	DCT18170	XpndConfMask1Unus	DH220170	11 <bin>		XpndConfMask1_ER	DH221170	ON		XpndConfMask1_CM	DH222170	OFF (Def)		XpndConfMask1_RM	DH223170	OFF (Def)		XpndConfMask1_HRM	DH224170	ON		XpndConfMask1_MRM	DH225170	ON		XpndConfMask1LRM1	DH226170	ON		XpndConfMask1LRM2	DH227170	ON		XpndConfMask1_RMI	DH228170	Update		XpndConfMask1_TMI	DH229170	Update						XpndConfMask2_PG	DH230170	ON		XpndConfMask2Unus	DH231170	1111111111 <bin>		XpndConfMask2OPLS	DH232170	Update		XpndConfDW1Unus	DH020170	0 <dec> (Def)		XpndConfDW1_ER	DH021170	OFF (Def)		XpndConfDW1_CM	DH022170	OFF (Def)		XpndConfDW1_RM	DH023170	OFF (Def)		XpndConfDW1_HRM	DH024170	OFF (Def)		XpndConfDW1_MRM	DH025170	ON		XpndConfDW1LRM1	DH026170	OFF (Def)		XpndConfDW1LRM2	DH027170	OFF (Def)		XpndConfDW1_RMI	DH028170	0.6		XpndConfDW1_TMI	DH029170	1.2		XpndConfDW2_PG	DH030170	OFF (Def)		XpndConfDW2Unus	DH031170	0 <dec> (Def)						XpndConfDW2OPLS	DH032170	-4			GBM IL DSE				-SY -- ---				
XpndId	DH018170	XpndB	DCT18170																																																																																																																													
XpndConfMask1Unus	DH220170	11 <bin>																																																																																																																														
XpndConfMask1_ER	DH221170	ON																																																																																																																														
XpndConfMask1_CM	DH222170	OFF (Def)																																																																																																																														
XpndConfMask1_RM	DH223170	OFF (Def)																																																																																																																														
XpndConfMask1_HRM	DH224170	ON																																																																																																																														
XpndConfMask1_MRM	DH225170	ON																																																																																																																														
XpndConfMask1LRM1	DH226170	ON																																																																																																																														
XpndConfMask1LRM2	DH227170	ON																																																																																																																														
XpndConfMask1_RMI	DH228170	Update																																																																																																																														
XpndConfMask1_TMI	DH229170	Update																																																																																																																														
XpndConfMask2_PG	DH230170	ON																																																																																																																														
XpndConfMask2Unus	DH231170	1111111111 <bin>																																																																																																																														
XpndConfMask2OPLS	DH232170	Update																																																																																																																														
XpndConfDW1Unus	DH020170	0 <dec> (Def)																																																																																																																														
XpndConfDW1_ER	DH021170	OFF (Def)																																																																																																																														
XpndConfDW1_CM	DH022170	OFF (Def)																																																																																																																														
XpndConfDW1_RM	DH023170	OFF (Def)																																																																																																																														
XpndConfDW1_HRM	DH024170	OFF (Def)																																																																																																																														
XpndConfDW1_MRM	DH025170	ON																																																																																																																														
XpndConfDW1LRM1	DH026170	OFF (Def)																																																																																																																														
XpndConfDW1LRM2	DH027170	OFF (Def)																																																																																																																														
XpndConfDW1_RMI	DH028170	0.6																																																																																																																														
XpndConfDW1_TMI	DH029170	1.2																																																																																																																														
XpndConfDW2_PG	DH030170	OFF (Def)																																																																																																																														
XpndConfDW2Unus	DH031170	0 <dec> (Def)																																																																																																																														
XpndConfDW2OPLS	DH032170	-4																																																																																																																														
	GBM IL DSE																																																																																																																															
	-SY -- ---																																																																																																																															
		Notice that in the configuration of the XPND the coherent mode is unchanged. Although if the receiver losses lock for more than 0.2 s, then the transponder reverts back to noncoherent mode. When receiver locks again, the transponder automatically returns to the memorised mode.																																																																																																																														
14		Send TC(8,4,115,20) to configure the TM encoder to 150 kbps		Next Step: 15																																																																																																																												

Tx2 and TM encoder in use configuration for MR
 File: H_CRP_TTC_T2MR.xls
 Author: E. Picallo



Step No.	Time	Activity/Remarks	TC/TLM	Display/ Branch
		Execute Telecommand TtcConfTmEncInUseMedium <i>TC Control Flags :</i> Subsch. ID : 10 Det. descr. : TTC: Config TM Enc In Use Mode Medium 150 kbps, TC(8,4,115,20) GBM IL DSE -E- - - - -	DC22F170	
TC Seq. Name : HRRT2MRF (Tx2 for MR final) TimeTag Type: Sub Schedule ID: <input type="checkbox"/>				
15		Verify setting		Next Step: END
		Verify Telemetry TME_BITRATE DEMRF160	= 150 Kbps	AND=ZAZ7J999
		Verify Telemetry BSW_TM_MODE DEMF0160	= AllVc	AND=ZAZ7J999
		Verify Medium Rate Modulator status Telemetry X2 MedRate-MRM RMB50442	= ON	AND=ZAZ7I999
		Verify Coherent Mode status Telemetry X2 Coher MOD-CM RMB47442		AND=ZAZ7I999
		Verify Ranging Modulator status Telemetry X2 Rang MD - RM RMB48442		AND=ZAZ7I999
		Verify RNG Modulation Index Telemetry X2 RNGMD ID-RMI RMB53442	= 0.6 rad	AND=ZAZ7I999
End of Procedure				