

Start LOU Baffle Decontamination  
File: H\_FCP\_SYS\_LOU1.xls  
Author: E. Picallo



## Procedure Summary

### Objectives

This procedure describes the steps needed to start the decontamination of the LOU Baffle in case they would be covered with ice and that would blur the path between the LOU and HIFI FPU

### Summary of Constraints

By default the Lou Baffle Management function is running but the LOU Baffle controlling is disabled.

The LOU Baffle Management function shall be running before enable the LOU Baffle control.

The criteria to switch ON or OFF the LOU decontamination shall be determined by HIFI.

The maximum number and duration of ON cycles is limited by the following:

- never more than 20 hours of continuous operation
- at least 48 hours between two consecutive operations
- not more than 20 operations during in-orbit life

The required power for the decontamination is ~200W. Before starting it, the ground shall verify if there is enough available power regarding the power already used.

Never more than two heater lines shall be switched ON simultaneously

It is required to enable the TCS Diagnostic Packet in order to monitor the LOU median temperature parameter

### Spacecraft Configuration

#### Start of Procedure

LOU Baffle Management function started  
LOU Baffle Decontamination control disabled

#### End of Procedure

LOU Baffle Management function started  
LOU Baffle Decontamination control enabled

### Reference File(s)

#### Input Command Sequences

#### Output Command Sequences

HFYLOU1

### Referenced Displays

ANDs      GRDs      SLDs  
ZAZ9I999

Start LOU Baffle Decontamination  
 File: H\_FCP\_SYS\_LOU1.xls  
 Author: E. Picallo




**Configuration Control Information**

DATE	FOP ISSUE	VERSION	MODIFICATION DESCRIPTION	AUTHOR	SPR REF
04/08/08	1	1	Created	E. Picallo	
04/09/08		2	enabling of TCS diagnostic packet added. Updated with HPSDB v.7	E. Picallo	
26/11/08		3	LOU Baffle management status verified before function report	E. Picallo	
08/01/09	2	4	LOU baffle heating thresholds updated to [220K,230K] according to H-P-2-ASP-ID-1418 issue 4	E. Picallo	
24/02/09	2.1	5	Power constrain added	E. Picallo	

Start LOU Baffle Decontamination  
 File: H\_FCP\_SYS\_LOU1.xls  
 Author: E. Picallo



### Procedure Flowchart Overview



Start LOU Baffle Decontamination  
 File: H\_FCP\_SYS\_LOU1.xls  
 Author: E. Picallo



Step No.	Time	Activity/Remarks	TC/TLM	Display/ Branch
<b>Beginning of Procedure</b>				
TC Seq. Name : HFYLOU1 (Start Lou Baffle Dec) Start LOU Baffle Decontamination  TimeTag Type: N Sub Schedule ID:  <input type="checkbox"/>				
1		Check initial LOU temperature		Next Step: 2
		<b>At the beginning of the decontamination process, the initial LOU temperature should be in the range [130°K - 140°K]</b>		
		Verify LOU THERMISTOR 1 Telemetry LouBaffleTemp1                      ZMP17999	<= -133.15 degC >= -143.15 degC	AND=ZAZ9I999
		Verify LOU THERMISTOR 2 Telemetry LouBaffleTemp2                      ZMP18999	<= -133.15 degC >= -143.15 degC	AND=ZAZ9I999
		Verify LOU THERMISTOR 3 Telemetry LouBaffleTemp3                      ZMP19999	<= -133.15 degC >= -143.15 degC	AND=ZAZ9I999
2		Verify power margin		Next Step: 3
		<b>The required power for the decontamination is ~200W. Before starting it, the ground shall verify if there is enough available power regarding the power already used.</b>		
		<b>Warning: Required S/C preconditions are TBW</b>		
3		Verify the LOU Baffle Management function status		Next Step: 4
		<b>By default, the LOU Baffle management function should be always enabled.</b>		
		Verify LOU Baffle Management function status Telemetry LbSts                                      DEN66170	= Running	AND=ZAZ9I999
4		Is LOU Baffle Management function running (yes/no)?		Next Step: no 5 yes 6
5		Start Lou Baffle Management function		Next Step: 6

Start LOU Baffle Decontamination  
 File: H\_FCP\_SYS\_LOU1.xls  
 Author: E. Picallo



Step No.	Time	Activity/Remarks	TC/TLM	Display/ Branch
		<b>Call Procedure H_CRP_SYS_LOUM to Start the LOU Baffle management function</b>		
		Execute Procedure: H_CRP_SYS_LOUM Start/Stop Lou Baffle Management function		
6		Request the LOU Baffle Status Report		Next Step: 7
		<b>Call procedure H_FCP_SYS_LOUS to request the LOU Baffle Status Report</b>		
		Execute Procedure: H_FCP_SYS_LOUS Lou Baffle Management Status Report		
7		Is the LOU baffle configuration correct (yes/no)?		Next Step: no 8 yes 9
		<b>Check that the LOU baffle parameters, contained in the LOU Baffle Status Report, determined by HIFI, are correctly configured.</b>  The default parameter values are: - Low temperature Threshold : 220K = -53.15 C = 8480 RAW - High temperature Threshold : 230K = -43.15 C = 8816 RAW - Heater lines to be used are: LCL59&61		
		Verify Telemetry LouBafCtrlSts DEZA3170 = LouBCtrlStoppd		AND=ZAZ9I999
		<b>The initial LOU control status must be disabled (by enabling it, the LOU decontamination will start)</b>		
8		Modify LOU baffle parameters		Next Step: 9
		<b>If another configuration is required, call to: H_CRP_SYS_LOUP to change the parameter values.</b>		
		Execute Procedure: H_CRP_SYS_LOUP LOU Baffle Parameters Update		
9		Enable TCS Diag packet		Next Step: 10

Start LOU Baffle Decontamination  
 File: H\_FCP\_SYS\_LOU1.xls  
 Author: E. Picallo



Step No.	Time	Activity/Remarks	TC/TLM	Display/ Branch
		<b>It is required to enable the TCS Diagnostic Packet in order to monitor the LOU median temperature parameter.</b>		
		<b>Call procedure "Enable or disable the generation of an housekeeping or diagnostic packet" H_FCP_DHS_3033</b>  <b>1) Acquire the list of the current enabled TM packets</b> <b>2) Verify if the TCS Diagnostic packet is enabled:</b> <b>TCS -&gt; subtype=26, packet-ID=100</b> <b>3) If it is disabled, enable it</b>		
		Execute Procedure: <b>H_FCP_DHS_3033</b> <b>Enable or disable the generation of an housekeeping or diagnostic packet</b>		
10		<i>Enable LOU Baffle decontamination</i>		Next Step: 11
		<b>Send TC(8,4,118,1) Enable Lou Baffle Control to start the Lou Baffle controlling.</b>		
		Execute Telecommand <p style="text-align: center;"><b>EnableLouBaffleCtrl</b></p> <i>TC Control Flags :</i> <p style="text-align: center;">GBM IL DSE        --Y -- --</p> <i>Subsch. ID : 10</i> <i>Det. descr. : Enable Lou Baffle control TC(8,4,118,1)</i>	DCP03170	
10.1		<i>Acquire the Lou Baffle Management Status Report</i>		<input type="checkbox"/>
		<b>Call H_FCP_SYS_LOUS and verify that the Lou Baffle Control is enabled.</b>		
		Execute Procedure: <b>H_FCP_SYS_LOUS</b> <b>Lou Baffle Management Status Report</b>		
		Verify Telemetry <p style="text-align: center;"><b>LouBafCtrlSts</b>                      <b>DEZA3170</b></p> <p style="text-align: center;"><b>= LouBCtrlStartd</b></p>		AND=ZAZ9I999
11		<i>Wait the requested decontamination time</i>		Next Step: END
		<b>The duration of the decontamination cycle shall be determined by HIFI.</b>		



Start LOU Baffle Decontamination  
 File: H\_FCP\_SYS\_LOU1.xls  
 Author: E. Picallo



Step No.	Time	Activity/Remarks	TC/TLM	Display/ Branch
		<b>WARNING: if any heater anomaly is detected, a recovery action shall be taken to modify the pair of heaters used for decontamination, calling the contingency procedure H_CRP_SYS_LOUR (Recovery from a LOU heater failure).</b>		
		<b>Nominally, the two heaters used in the LOU Baffle decontamination are the corresponding to the LCL59 and LCL61</b>		
		Verify Telemetry LouDecH1_L59_1S WM42F565		AND=ZAZ9I999
		Verify Telemetry LouDecH1_L59_I WM411565		AND=ZAZ9I999
		Verify Telemetry LouDecH2_L61_1S WM72F565		AND=ZAZ9I999
		Verify Telemetry LouDecH2_L61_I WM711565		AND=ZAZ9I999
		<b>If the heater corresponding to LCL66 is used instead check:</b>		
		Verify Telemetry LouDecH3_L66_1S WM52F565		AND=ZAZ9I999
		Verify Telemetry LouDecH3_L66_I WM511565		AND=ZAZ9I999
<b>End of Procedure</b>				